

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 1 N. R. 10 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

AVON TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B																										B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 4

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-9

AV525

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON FEB EAST ON RAMD BET 5 & 8
66 LEAVE BROOK CRS S.W.
330 LEAVE BOTTOM
2640 TEMP 1/4 P
5289.90 E BDG 138.6 N OF P LAND LEVEL 2ND RATE
TIM. BR OAK & BURR O.
WEST COR WEST
2644.95 QUARTER SEC COR. BURR O. 18 S9W 44.22' &
RED OAK 10 N24E 69.96'
RED O 18 RED O 10} MARKED
5289.90 SEC COR
1833 HARRISON NORTH BETWEEN 8 & 9
983.4 BLK O 20
2211 W.O. 18
2640 QUARTER SEC COR {W.O. 14 N53E 23.76' W.O. 20
WEST 27.72', {W.O. 14 W.O. 20} MARKED
3286.80 BURR OAK 10
25640 COR TO SEC 4,5,8,9 BURR O 18 N64E 30.36',
BURR O 12 N37W 110.98', BURR O 10 S22W
53.46' LAND ROLLING 2ND RATE TIMBER BURR O.
1833 HARRISON JAN 30TH NORTH BET. SECS 4 & 5
402.6 BURR O 12
792 BOTTOM
1158.96 CREEK 11.88' CRS WEST
2310 LEFT BOTTOM
2640.00 QUARTER SEC COR {BURR O 10 N38W 13.86'
BURR O 12 N77E 36.96' {BURR O 10 BURR O 12}
MARKED}
2653.86 BURR O 12
2956.80 BURR O 10
4216.74 RED O 18
4827.90 INT. N BDG 88.44' W OF P {DOUBLE RED P 26
S14E 149.34' BURR O 12 S72W 59.4'} LAND
ROLLING 2ND RATE TIMBER BURR O.
1833 HARRISON EAST ON RAMD BET 4 & 9
99 ENTER S AREA OF MARSH
792 LEFT SAME CRS N
2640.00 TEMPY 1/4 P
5248.32 INT E BDY 33' N OF P. LAND SAME TIMBER W &
BURR O
COR. WEST
2624.16 QUARTER SEC COR {W.O. 20 N62E 42.9' W.O. 20
S88W 34.32' {W.O. 20 WO. 20} MARKED
5248.32 SEC COR
1851 MC VEAN VOL 1 PG 5 STATES NOTHING ABOUT MON. 2655.84
TO W 1/4 COR SEC 9 & 2638.68' TO N 1/4 COR SEC 9
1874 RUGER VOL 2 PG 144 & MAP #41 FD OLD STAKE & STUMPS
OF N,E, & SW B.TS STUMPS OF NW DUG UP. DROVE NEW
STAKE IN PLACE OF OLD ONE & SURROUNDED IT WITH 4 HH
STONES, 1328.25 VAR 3-59 TO N 1/16TH COR OF NE 1/4 SEC 8,
2656.5 VAR 3-59 TO N 1/4 COR SEC 8

DUG & FD HH 18X9X5" ON END SURROUNDED BY 1 LARGE HH AND
3 MEDIUM SIZE HH. REPLACED HH WITH ORANGE POLY MON. & SET
CARSONITE POST ON THE NE SIDE OF THE MON.

Donald Barnes
6-06-2005

SHEET 1 OF 4
CORNER CODE E-9

AV525

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

HH WAS IN HARMONY WITH RECORD DISTANCES AND OCCUPATION.
ACCEPTED HH.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes

Emboss

6-06-2005

SHEET 2 OF 4

CORNER CODE **E-9**

A.E. 7.08 REQUIREMENT

