

Paper weight-110# (minimum) Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
 CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

UNION TWP
ROCK COUNTY WI

IF AVAILABLE
 ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3				2				1				B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
 PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____
 East _____
 Hor. Datum _____ Vert. Datum _____
 LATITUDE _____ ELLIPS. HT. _____
 LONGITUDE _____
 NAD83(91) _____ NETWORK ADJ. YR 2010
 GPS (X) _____ TRAVERSE (X) X
 BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT ○ WITNESS MONUMENT

BEARINGS ARE BASED ON: --- ROCK COUNTY PROJECTION ---

FIELD BOOK _____ PAGE # _____
 OR OBSERVATION SHEET _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E 3

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON (NOV 10TH) T4N T10E 4TH MER WEST BETWEEN
SECS 6 & 7

990.0 MARSH
1650.0 LEFT ????
1828.20 WO 12
2640.00 QUARTER SEC COR {WO 12 S32E 27.72'; WO 18
N79W 21.78' WO 12 & WO 18} MARKED
5342.70 INT RANGE LINE OF RANGE 9E SET COR TO
SECS 6 & 7 {BURR O 12 N34E 27.72'; BURR O
S23E 31.02' LAND ROLLING 2ND RATE WITH WO
& BURR O TIMBER GROWTH HAZEL, GRASS, &
WEEDS NOV 11TH 1833

1863 LOCKE VOL 1 PG 193 & #5090 FD STAKE SET. 2630.1 TO
CENTER OF SEC 7 & 5260.2 TO S 1/4 COR SEC 7

1870 RUGER AUG #5089 REMON-124 EAST ON SOUTH LINE OF
SW 1/4 SEC 6 ON A VAR 7-27; OFFSET NORTH
18.48' AT

2720.52 INTERSECTED QUARTER LINE 36.30' NORTH OF
QUARTER CORNER. FOUND OLD STAKE AT
CORNER. COR VAR 7-04

EAST ON SOUTH LINE OF SE 1/4 SEC 6
ON A VAR 7-10; AT

2648.58 INTERSECTED EAST BOUNDARY LINE AT
CORNER. EDWARD RUGER COUNTY SURVEYOR.

1870 RUGER VOL 2 PG 50 STONE MON SET BY SELF. VAR7-18
2722.49 TO STONE MON SET BY SELF @ NW COR SEC 7,
VAR 5-31 2631.75 TO SET HH 24X9X8 SURROUNDED BY 4
HH @ CENTER OF SEC 7.

1904 KERCH VOL 3 PG 21 MONUMENT 2657.4X TO MON @ NE
COR SEC 7, USED TO SUBDIVIDE SEC 7

1912 KERCH VOL 3 PG 70 MON 2730.14 TO MON @ NW COR SEC
7. USED RUGER'S STONE @ CENTER OF SEC 7

1976 BARNES VOL 5 PG 142 FD CUT STONE 0.3' ABOVE
GROUND. 2.5 SOUTH OF E/W FENCE & ON N/S FENCE. REF.
SAME.

1982 BARNES VOL 6 PG 273 FD CUT LS

1982 BARNES VOL 6 PG 274 FD CUT LS. N89-56-18W 2031.01
TO FD PIPE; THENCE N89-56-18W 698.11 TO SET R/R SPIKE
@ AMENDED MON.; THENCE S89-56E 8.06 TO FD ALUM MON.
FD ALUM MON IS 0.07 SOUTH OF A LINE BETWEEN THE FD
PIPE & THE R/R SPIKE

1982 COMBS GSM VOL 11 PG 26 ALUM MON. USED STONE @
CENTER OF SEC 7 FOR LINE.

1998 COMBS #8112 STONE MON. S0-13-52W 2639.06 TO STONE
MON @ CEN OF SEC 4.

FD CUT LIMESTONE 0.4' ABOVE GRADE. LEANING TO THE NW.
PLUMB LINE FROM L.S. IS 0.15' TO THE EAST & 0.06' TO THE SOUTH.
SET CARSONITE POST @ SE COR OF L.S.

Donald Barnes

SEAL
NOV 3, 2011
Emboss

SHEET 1 OF 3

CORNER CODE E-3

UN522 S1/4CORSEC6

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIMESTONE.


D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.


Donald Barnes

Nov 3, 2011

SHEET 2 OF 3

CORNER CODE E-3

A.E. 7.08 REQUIREMENT

