

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2N., R. 12E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
B	6																									
C	5																									
D																										
E																										
F	1	8	9	10	11	12																				
G																										
H																										
I	18	17	16	15	14	13																				
J																										
K																										
L																										
M																										
N																										
O	19	20	21	22	23	24																				
P																										
Q																										
R																										
S	30	29	28	27	26	25																				
T																										
U																										
V																										
W																										
X	31	32	33	34	35	36																				
Y																										
Z																										

ROCK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 4

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE J-25(2)

RO553

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT ORIGINAL GOVERNMENT SURVEYOR. FIELD NOTES SET POST CORNER SECTIONS 13 & 24 IN MOUND. PIT SOUTH 1.98'
- 1836 LYON ORIGINAL GOVERNMENT SURVEYOR. FIELD NOTES EAST BETWEEN SECTIONS 12 & 13. INTERSECTED RANGE LINE 54.78' NORTH OF POST. MEASURED 2545.62 TO S 1/4 CORNER OF SECTION 12.
- 1865 LOCKE VOL 1 PG 242 FD OLD STAKE - SET STAKE ON N. SIDE SURROUNDED IT BY 3 L.S. VAR 7-45 2641.58 TO W 1/4 COR SEC 7
- 1869 LEE VOL 2 PG 4 FOUND OLD STAKE. SHOWS A DISTANCE OF 2564.10 TO S 1/4 CORNER OF SEC 12 AND 2653.20 TO E 1/4 CORNER OF SECTION 13.
- 1871 RUGER LA PRAIRIE TOWNSHIP REMONUMENTATION FIELD NOTES. SOUTH ALONG THE SW LINE OF SECTION 7. 2647.26' INTERSECTED SOUTH BOUNDARY 1.65' EAST OF CORNER. FOUND STAKE SURROUNDED BY 3 LIMESTONES AT CORNER. MEASURED 2654.52 TO W 1/4 CORNER OF SECTION 18 AND 2443.98' TO THE S 1/4 CORNER OF SECTION 7.
- 1877 RUGER VOL 2 PG 237 STATES NOTHING ABOUT MONUMENT. VAR 4-53 2560.14 TO N 1/4 COR SEC 13 & 2649.08 TO E 1/4 COR SEC 13
- 1936 SUNNY VOL 3 PG 294 FOUND 6X6 HARD HEAD. SET 1 1/2"X14" IRON PIPE WITH CAP ON TOP. SHOWS TIES.
- 1960 BATTERMAN VOL 4 PG 60 SHOWS REFERENCE TIES.
- 1960 DOT #11174 CTH "G" STATES NOTHING ABOUT MON.
- 1968 THOM #02490 PIPE. ANGLE 89-21-22 @ W 1/4 COR SEC 7 FROM NORTH LINE E/W 1/4 LINE TO SW COR SEC 7
- 1968 BATTERMAN JR. VOL 4 PG 387. SHOWS NB9-44-30W 2444.36 TO N1/4 CORNER OF SECTION 18 LA PRAIRIE TOWNSHIP.
- 1976 COMBS CSM VOL 5 PG 348 FD PIPE IN MON. BOX
- 19?? HURD VOL 5 PG 517 N/S 235,653.86; E/W 2,265,953.48
- 1985 BARNES J-1 REPLACED 1X24" PIPE WITH POLY MON. & REFERENCED SAME. SHOWS COORDINATES AS SHOWN IN J-25 1990. ELEVATION NAD29 841.5
- 1985 LA PRAIRIE TWP REMON 2646.28 TO E 1/4 COR SEC 12 & 2653.40 TO E 1/4 COR SEC 13
- 1987 DOT #11107 8TH 351 ALUM. 235,653.20; 2,265,952.30
- 1988 THOM CSM VOL 13 PG 303 FD ALUM
- 1988 THOM CSM VOL 13 PG 306 FD ALUM ANGLE 90-40-20 @ SW COR SEC 7 FROM W 1/4 COR SEC 7 TO S 1/4 COR SEC 7.
- 1988 COMBS CSM VOL 13 PG 398 FD ALUM. 2646.22 TO E 1/4 COR SEC 13
- 1989 THOM CSM VOL 13 PG 460 ALUM MON. ANGLE 89-38-15 ALONG NORTH LINE SEC 18 TO W 1/4 COR SEC 18. FD PIPE SB9-44-30E 40.00 OF SEC COR.
- 1989 BARNES VOL 6 PG 395 COORDINATES N/S 235,652.85; E/W 2,265,952.87; TOWNSHIP PROJECT N/S 235,653.62; E/W 2,265,952.65 DOT N/S 235,653.20; E/W 2,265,952.30. SHOWS THE FOLLOWING DISTANCES:
- | | |
|---------------------|---------|
| TO E 1/4 COR SEC 13 | |
| RUGER 1871 | 2654.52 |
| BARNES 1986 | 2653.41 |
| HURD | 2653.36 |
| NO-46-29W | 2653.37 |
- 1990 BARNES J-25 FOUND POLY MONUMENT IN MONUMENT BOX. REFERENCED SAME. SHOWS AT CENTER OF PVMT. NAD27 235,652.96; 2,265,952.66,

SHEET 1 OF 34
J-25(2)

Dwight Barnes
May 27 2004

RD553

- HURD 235,653.86; 2,65,953.48,
STH 235,653.20; 2,265,952.30,
LA PRAIRIE TWP PROJ. 235,653.62; 2,265,952.65
- 1991 BARNES E-23 & ROCK TWP REMON N88-49-54W 2564.85 TO S
¼ COR SEC 12, NO-26-30W 2646.28 TO E ¼ COR SEC 12, &
S00-08-03E 2653.40 TO E ¼ COR SEC 13
- 1992 LEE #11243 & 1242 SET PIN NO-24-25W TO W ¼ COR SEC 7 &
S0-06-15W TO W ¼ COR SEC 18
- 1994 THOM CSM VOL 17 PG 243 ALUM MON
- 1994 THOM #09613 ALUM MON
- 1994 BARNES J-1(1) FD POLY MONUMENT 0.3' DEEP AT CENTER OF
PVMT. MONUMENT WILL BE DESTROYED BY ROAD
CONSTRUCTION. REFERENCED SAME. ACCEPTED FOUND
MONUMENT.
- 1997 LATHROP BOOK 32 PG 368 "SUNDOWN REPLAT". PK
- 1997 LATHROP CSM VOL 20 PG 137 FD PK 2646.13 TO E ¼ COR
SEC 12
- 1997 HOEL #08591 ALUM MON 2653.34 TO W ¼ COR SEC 18
- 1997 LATHROP CSM VOL 20 PG 329 PK. 2653.35 TO W ¼ COR SEC
18
- 1998 ZHRINGER #08262 ALUM ANGLE 89-38-40 FROM N ¼ COR
SEC 18 TO W ¼ COR SEC 18 & 2653.34 TO W ¼ COR SEC 18
- 1998 COMBS CSM VOL 21 PG 461 ALUM 2653.34 TO W ¼ COR SEC
18 & ANGLE 89-38-40 FROM NORTH LINE SEC 18 TO W ¼ COR
SEC 18
- 1999 LATHROP #07546 PK NAIL
- 1999 KNUDSON CSM VOL 22 PG 147 FD POLY S00-06-15E 2653.45
TO W ¼ COR SEC 18 & N00-24-20W 2646.22 TO W ¼ COR SEC
7
- 1999 KNUDSON #7275, 7274, & 7277 SET PK ANGLE 180-18-35
FROM W ¼ COR SEC 7 TO W ¼ COR SEC 18, 2653.45 TO W ¼
COR SEC 18 & 2646.22 TO W ¼ COR SEC 7
- 1999 LATHROP CSM VOL 23 PG 73 PK 2653.31 TO W ¼ COR SEC 18
- 1999 LATHROP CSM VOL 23 PG 254 PK 2653.31 TO W ¼ COR SEC
18
- 1999 STROBEL #7442 FD PK OF REC
- 1999 KNUDSON J-1(2) POLY MON. WAS NOT FOUND. I RE-
ESTABLISHED THE SECTION CORNER POSITION USING THE
TIES FROM A U.S PUBLIC LAND SURVEY MONUMENT RECORD
BY DONALD BARNES DATED JUL 5, 1994 AND SET A PK NAIL AT
THE SECTION CORNER
- 2001 COMBS #14218 N88-47-35W ALONG SEC LINE TO PIPE & S0-
05-50E ALONG EAST LINE OF SECTION. LEGEND CALLS FOR
PK.
- 2002 KUBIZEK #14359 & 14360 BRASS CAP 2649.35 TO W ¼ COR
SEC 7
- 2003 BARNES J-25(1) INFORMATION PROVIDED BY WIDOT PROJECT
#1704-06-21 SHEET #4.6 DATED 5-22-2001. PK NAIL
Y=71,829.385M; X=681,051.214M. NOTE: COORDINATES
AND BEARINGS ON THIS PLAT ARE ORIENTED TO THE WI.
COORDINATE SYSTEM SOUTH ZONE NAD83. COORDINATES
ARE IN METERS. I DON BARNES CONVERTED THE ABOVE
COORDINATES TO THE FOLLOWING ROCK COUNTY
COORDINATES: N/S 254,317.32; E/W 496,280.72

SHEET 2 OF 34
J-25(2)

Donald Barnes
May 27, 2004

R0553

FOUND PK @ CENTER OF PVMT. & REFERENCE MONUMENTS. SOUTH BOUND PVMT WAS REMOVED. SEARCHED AND DID NOT FIND REMAINS OF POLY. MONUMENT. INTERSECTION OF 1994 RECORD DISTANCE (BARNES J-1(1)) ARE IN HARMONY BUT DO NOT AGREE WITH FD PK.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD RECORD TIES & INTERSECTION OF RECORD DISTANCES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

FD PK IS S41-29-48W 0.07' FROM INTERSECTION OF RECORD TIES.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Donald Barnes
Seal

May 27, 2004
Emboss

SHEET 3 OF 5

CORNER CODE J-25(2)

A.E. 7.08 REQUIREMENT

