

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

UNION TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B			6			5				4				3					2						1	B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE N-23(1)

UN572 N1/4CORSEC24

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 (NOV) HARRISON T4N R10E 4TH MER. EAST ON RAND.

BET. SECS 13 & 24

2640.0 TEMPY 1/4 SEC COR.

5188.92 INT. EAST BDY 66' NORTH OF POST LAND &
SAME

WEST COR. WEST BET 13 & 24

2594.46 QUARTER SEC COR. BURR OAK 18 N62W 36.96';
HICKORY 13 S20E 58.74' BURR OAK 18;
HICKORY 13} MARKED

5188.92 SEC COR

1870 RUGER AUG REMON-73 WEST ON NORTH LINE OF NE 1/4
SEC 24 ON A VAR 6-30 AT

2621.19 INTERSECTED QUARTER LINE 3.63' NORTH OF
QUARTER CORNER. FOUND REMAINS OF OLD
STAKE AND STUMP OF NORTH BEARING TREE
AND REMAINS OF STUMP OF SOUTH BEARING
TREE. COR. VAR 6-35

WEST ON NORTH LINE OF NW 1/4 SEC 24 ON A
VAR 6-30 OFFSET NORTH 3.63' AT

2614.92 INTERSECTED WEST BOUNDARY LINE 19.8' NORTH
OF CORNER FOUND REMAINS OF OLD STAKE AT
CORNER. ALSO FOUND STUMPS OF BOTH
BEARING TREES. COR VAR 6-51

1940 SUNNY VOL 3 PG 464 DUG 6X6 HOLE 2' DEEP. FD
NOTHING, ROAD IS IN CUT STONE GRADED OUT & CENTER
OF N/S FENCE LINE.

1968 BATTERMAN FB#142 PG 46 & 47 DUG & FD CUT STONE TOP
BROKEN OFF AND GONE. BOTTOM 14" REMAINING. SOUTH
EDGE OF ROADWAY. 1 1/2' DEEP. PK'S 12' EAST & 12'
NORTH. CORNER SHOWN AS 38' SOUTH OF E/W FENCE LINE
ON NORTH SIDE OF ROAD. [50.00 DISTANCES BETWEEN
PIPES & CORNER ARE CORRECT]

1970 BATTERMAN VOL 4 PG 449 DUG & FD CUT STONE. SET IRON
PIPE OVER STONE. REFERENCED SAME.

1970 DOT CTH M #13063

1972 DOT CTH M #7430 PROJ E0624(16) SHEET 4.5 STATES
NOTHING ABOUT MON.

1973 THOUSAND VOL 3 PG 70 PLACED PK

1985 BARNES N-23 FD 1970 TIES. THE PIPE WAS PROBABLY
DESTROYED BY RD CONSTRUCTION AND A T-BAR LIKE THE
ONE USED BY SAGE WAS. SEE VOL 4 PG 533 THE FD T-
BAR DOES NOT AGREE WITH THE OLD TIES. FD REFERENCE
PIPES. AUG 20, 1985 PLACED POLY. TIES PREPARED FOR
CONSTRUCTION PROJECT.

1996 COMBS GSM VOL 19 PG 312 PK

1998 COMBS #8122 FD ALUM. MON. S87-20-40E 2614.0X TO
STONE MON @ NE COR SEC 24

2001 COMBS GSM VOL 24 PG 326-327 #14124 FD POLYSTRENE
MON @ N 1/4 COR SEC 24 2619.64 TO FD IRON PIPE @ NW
COR SEC 24

2001 COMBS #14215 & #14512 FD POLY 2615.90 TO CUT STONE
@ NE COR SEC 24

2006 LATHROP #15421 FD ALUM. MON. S82-20-40E 2614.06 TO
CUT STONE @ NW COR SEC 19 T4N R11E

Donald Barnes

SEAL
June 20, 2011
Emboss

SHEET 1 OF 3

CORNER CODE N-23(1)

UN572 N1/4CORSEC24

FD REFERENCE TIES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED CUT LIMESTONE POSITION PER TIES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SEAL
Donald Barnes
Emboss
JUNE 20, 2011

SHEET 2 OF 3

CORNER CODE N-23(1)
A.E. 7.08 REQUIREMENT

FD 1' PIPE

XXXXXXXXXX

WOODS

1970 BATTERMAN VOL 4 PG 449
1985 BARNES N-23 & FB#2 PG 11
2011 OBSERVATION SHEET #130

FD 1' PIPE

N 1/4 COR
SEC 24
UNION TWP
T4N R10E

NO-46-08E 50.00
1970 50.00
XXXXXXXXXXXXXXXXXXXXXXXXXXXX

N7-38-49E 166.10

E4-11-18
4/0

XXXXXXXXXX

FD 1' PIPE

N89-26-44E 3022.79

SO-46-31W 50.00
1970 50.00

N88-29-55E 3024.37

FD 3/4
REROD

TANK
N42-43-40W 55.687

N88-13-54E 3044.86

CTH M

1985 41.40
1985 3 +/-

1985 BARNES
FD T ROD WITH
FLAGGED NAIL
0.5' DEEP

1985
REC BOTTOM 14' CUT
L.S. 1 1/2' DEEP
SET POLY MON
2011 DID NOT UNCOVER POLY
SHEET 3 OF 3

SET 3/4X24
REROD
FROM REF PIPE TO
FD PIPE @
NW COR SEC 24
N89-18-32W 2,599.86

EMBOSSSED
SEAL

Daryl Barnes

June 20, 2011

N-23(1)

S14-52-30E 28.034'
S72-01-01E 14,542'
ANT