

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:  
T. 4 N. R. 10 E. 4th P.M.  
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT  
REV 10/23/2004 USMONREC.DWG

UNION TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3			2				1					B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR 2010 \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL: \_\_\_\_\_

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT       WITNESS MONUMENT

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_  
OR OBSERVATION SHEET \_\_\_\_\_

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE R-13(2)

UN587 NECORSEC28

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON T4N R10E 4TH MER. NORTH BETWEEN SECS 27 & 28

1089.00 ENTER SMALL PRAIRIE  
2409.0 LEAVE IT E & W  
2640.00 QUARTER SEC COR. [RED O 12 N64W 22.44'; W.O. 8 N36E 16.5' W.O 12 & WO 8}MARKED  
5280.00 COR TO SECS 21,22,27,28 {W.O 18 N52W 5.94'; W.O 18 N8E 15.18' {RED O 12 S30E 42.24'; W.O 18 S53W 50.16'  
LAND LEVEL 2ND RATE TIMBERED WITH W. RED & BURR ASPEN. UNDERGROWTH SCRUBS GRASS & WEEDS.

1833 HARRISON T4N R10E 4TH MER NORTH BET. SECS 21 & 22

1279.0 RED O. 24  
1789.0 CREEK 13.0' CRS SE  
2640 QUARTER SEC COR. [BURR O 24 N45E 283.8' NO OTHER NEAR BURR O 24 & BURR O 24}MARKED  
5280.00 SET COR TO SECS 15,16,21,22 {BURR O 12 N81E 12.54'; BURR O 10 N31E 45.54'; BURR O 12 S8W 26.4'; BURR O 24 N59Q 129.36' LAND ROLLING 2ND RATE TIMBER SAME MOSTLY WEEDS, GRASS.

1833 HARRISON T4N R10E 4TH MER EAST BET. SECS 22 & 27

828.96 C? CREEK CRS SE  
2640.00 TEMPY 1/4 SEC COR  
5214.00 INT. E BDY 33.0 N OF P LAND & SAME WEST COR WEST BET 22 & 27  
2607.00 QUARTER SEC COR {WO 36 S19E 29.04'; WO 29 N45W 50.16' WO 36 & WO 29}MARKED  
5214.00 SEC COR

1833 HARRISON T4N R10E 4TH MER EAST BET. SECS 21 & 28

2640.00 TEMPY 1/4 SEC COR  
5272.08 INT. E BDY 4.62' S OF P LAND ROLLING 2ND RATE TIMBER ?? RED O ???  
WEST COR WEST BET 21 & 28  
2636.04 QUARTER SEC COR {RED O 10 S64E 33.66'; RED O 12 N53E 13.20' RED O 10 & RED O 12}MARKED  
5272.08 SEC COR

1870 RUGER AUG REMON-71 NORTH ON WEST LINE OF SW 1/4 SEC 27 ON A VAR 7-20 OFFSET EAST 3.96' AT

2659.47 INTERSECTED QUARTER LINE 9.9' EAST OF QUARTER CORNER. FOUND STONE ON CORNER. ALSO FOUND REMAINS OF BOTH BEARING STUMPS. COR. VAR 7-28'  
REMON-75 AUGUST 22, 1870 NORTH ON WEST LINE OF NW 1/4 SEC 27 ON A VAR 7-50 OFFSET EAST 2.64' AT

2670.69 INTERSECTED NORTH BOUNDARY LINE 22.44' EAST OF CORNER. FOUND REMAINS OF OLD STAKE. ALSO FOUND STUMPS OF BOTH BEARING TREES. COR VAR 8-15

1870 RUGER AUG REMON-98 AUGUST 30, 1870 WEST ON NORTH LINE OF NE 1/4 SEC 27 ON A VAR 7-00'; OFFSET NORTH 14.52' AT

2616.90 INTERSECTED QUARTER LINE 19.14' NORTH OF QUARTER CORNER. FOUND STAKE SURROUNDED BY HARD HEAD STONES SET BY LOCKE AT

DEAL  
Barboss  
Baines

OCT 27, 2011

UN587 NECORSEC28

UN587 NECORSEC28 CORNER. ALSO FOUND STUMPS OF BEARING TREES. TESTED STAKE AND FOUND IT CORRECT. COR VAR 7-06'

WEST ON NORTH LINE OF NW 1/4 SEC 27 ON A VAR 7-00 AT

2632.08 INTERSECTED WEST BOUNDARY LINE 6.6' NORTH CORNER. COR VAR 7-09

1870 RUGER AUG REMON-76 WEST ON NORTH LINE OF NE 1/4 SEC 28 ON A VAR 7-00 COULD FIND NO TRACE OF QUARTER CORNER. IT HAVING BEEN PLACED CONSIDERABLY TOO FAR EAST BY THE U.S. SURVEYORS AND SUBSEQUENTLY DESTROYED IN CONSEQUENCE BY PARTIES INTERESTED AS I WAS CREDIBLY INFORMED. CONTINUED WEST ON NORTH LINE OF NW 1/4 ON VAR AS ABOVE GIVEN AT

5277.36 INTERSECTED WEST BOUNDARY LINE AT CORNER. ESTABLISHED NORTH QUARTER CORNER AT A POINT IN A TRUE LINE BETWEEN AND EQUI-DISTANT FROM THE NE & NW CORNERS OF SAID SECTION. IT BEING 2638.68 DISTANT FROM EACH.

1870 RUGER AUG REMON-96 NORTH ON EAST LINE OF SE 1/4 SEC 21 ON A VAR 7-00; OFFSET EAST 6.93' AT

2665.74 INTERSECTED QUARTER LINE 6.60' WEST OF QUARTER CORNER. FOUND BOTH BEARING STUMPS AND ESTABLISHED QUARTER CORNER FROM THEM.

NORTH ON EAST LINE OF NE 1/4 SEC 21 ON A VAR 7-00; AT

2658.64 INTERSECTED NORTH BOUNDARY LINE 1.98' EAST OF CORNER. COR VAR 7-02

1893 BLEEDORN VOL 2 PG 431 CALLS FOR A MON & 2640.00 TO E 1/4 COR SEC 21 & 2642.64 TO S 1/4 COR SEC 21

1899 BROWN VOL 2 PG 512 CALLS FOR A MON. & 2643.80 TO S 1/4 COR SEC 21.

1926 PARSONS BK-10 PG 48 ASSESSORS PLAT SHEET 4 OF 7 STATES NOTHING. SOUTH 1306

1965 DOYLE BK-23 PG 10 "EVERY ADD." STATES NOTHING ABOUT MON. SOUTH 1337.18 TO 1" PIPE WHICH IS 66.00 EAST OF PIPE IN CENTER OF ST.

1966 BATTERMAN VOL 4 PG 289 FD STONE. 2642.78 TO S 1/4 COR SEC 21 & 5285.56 TO SW COR SEC 21

1966 BATTERMAN VOL 4 PG 325 FD CUT STONE MON. WEST 1321.39 TO FD PIPE.

1966 LEE #5218 FD CUT STONE MON. 2642.76 TO CUT STONE MON @ N 1/4 COR SEC 28.

1967 BATTERMAN VOL 4 PG 325 FD CUT STONE & 1321.38 TO N 1/16TH COR OF THE NE 1/4 OF SEC 28

1969 JENSEN SUB #2183 ASSESSORS PLAT SHEET 6 S1-06E 2672.40 TO STONE @ E 1/4 COR SEC 28 & WESTERLY 1321.12 TO FD PIPE(2.08 W & 0.27 N); THENCE WESTERLY 1321.00 TO STONE @ N 1/4 COR SEC 28

1982 BARNES VOL 6 PG 288 SHOWS RECORD DISTANCES; RUGER 2665.74 & BLEEDORN 2666.40 TO W 1/4 COR SEC 22 & BROWN 2643.79 & ORIG 2636.04 TO S 1/4 COR SEC 21

1984 GENSKE ASSESSORS PLAT SHEET 4. #14063 CUT STONE.

1984 GENSKE ASSESSORS PLAT SHEET 4. #14054 CUT STONE.

1984 GENSKE R-13 THE COUNTY SURVEYOR MENTIONED THAT

*Donald Barnes*  
D. Barnes

OCT 27, 2011

UN587 NECORSEC28

THE MOST RECENT REFERENCE TO THE CORNER WAS FROM A SURVEY OF RECORD MENTIONING A CUT LIMESTONE MONUMENT, SOME 20 YEARS AGO. FD CUT LIMESTONE & REFERENCED SAME.

1985 BARNES VOL 6 PG 337 SHOWS RECORD DISTANCES.  
1989 COMBS CSM13-521 FD STONE.  
1990 BARNES P-13 2672.10 TO E 1/4 COR SEC 21  
1990 WOODMAN P32-70 "EAGER ESTATES" FD STONE 2642.68 TO ALUM @ N 1/4 COR SEC 27  
1999 UNK SUB #3283

2000 BARNES R-13(1) FD CUT LIMESTONE  
2000 BARNES VOL 6 PG 456 307,406.13; 416,449.24 S89-40-49E 2642.94 TO S 1/4 COR SEC 22 & NO-11-08W 2672.07 TO W 1/4 COR SEC 22. FD LS.  
2005 JENKINS FD CUT LS. 2642.68 TO FD ROCK COUNTY MON @ S 1/4 COR SEC 22  
2008 COMBS CSM VOL 32 PG 158 FD STONE 2673.13 TO ALUM @ E 1/4 COR SEC 28

#### FD CUT LIMESTONE & REFERENCE MONUMENTS

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIMESTONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location. NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.



Emboss

OCT 27, 2011

SHEET 3 OF 3

CORNER CODE R-13(2)

A.E. 7.08 REQUIREMENT