

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 2N. R. 12E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A	
B		6				5				4					3					2						1	B
C																											C
D																											D
E																											E
F																											F
G																											G
H																											H
J																											J
K																											K
L																											L
M																											M
N																											N
O																											O
P																											P
Q																											Q
R																											R
S																											S
T																											T
U																											U
V																											V
W																											W
X																											X
Y																											Y
Z																											Z

Rock TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE R-25(1)

RO593 SECORSEC24

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1836 LYON. ORIGINAL GOVERNMENT SURVEYOR. FIELD NOTES © SET POST CORNER TO SECTIONS 24 & 25 IN MOUND. PIT BEARING SOUTH 3.3'

1866 LOCKE VOL 1 PG 253 FOUND REMAINS OF STAKE. SET STAKE. SHOWS 2632.74 TO W 1/4 COR SEC 19 LA PRAIRIE TOWNSHIP

1920 BATTERMAN VOL 3 PG 95 IRON ROD? SHOWS A DISTANCE OF 2582.2(?) TO THE S 1/4 COR SEC 24.

1936 SUNNY VOL 3 PG 295 FOUND 6X6 CUT STONE MONUMENT 12" LOW. SET 1 1/2" IRON PIPE MONUMENT, CAPPED. REFERENCED SAME.

1960 BATTERMAN VOL 4 PG 59 REFERENCED SAME.

1985 BARNES R-1 DUG & FD 0.3' DEEP A MONUMENT BOX WITH A 1" IRON PIPE. BROKE PIPE AT 18". ALSO FD A CAPPED PIPE AT 18". PLACED POLY MON ON TOP OF CAPPED PIPE. TOP OF 1" IRON PIPE WAS BENT SO IT WAS OVER THE CAPPED PIPE. ELEV 819.8; NAD27 N/S 225,090.30; 2,266,093.12

1989 BARNES VOL 6 PG 394. N/S 225,089.08; E/W 2,266,093.19; TOWNSHIP PROJECT N/S 225,090.30 E/W 2,266,093.12 SHOWS THE FOLLOWING DISTANCE

TO E 1/4 COR SEC 24	SO-36-41E	2639.06
	RUGER 1871	2640
	BARNES 1985	2639.02
S 1/4 COR SEC 24	S89-35-44E	2516.24
E 1/4 COR SEC 25	SO-40-03E	2663.15
	RUGER 1871	2653.20
	BARNES 1985	2663.17

1990 BARNES R-25 FOUND POLY MONUMENT. ACCEPTED FOUND MONUMENT. REFERENCED POLY. ELEV 819.8

2012 BARNES COUNTY NET READJUSTED N/S 243,752.91'; E/W 496,303.49'

2012 COMBS R-25() PRELIM 246,392.00; 496,304.70

FD MAG NAIL @ PVMT SURFACE & 0.4' DEEP FD POLY WITH TOP BROKE OFF INSIDE MON BOX. 2' EAST OF N/S PVMT CENTER. FD 4 REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD POLY.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

DID NOT ACCEPT THE MAG NAIL. IT IS S88-47-45W 0.23' OF THE POLY.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SHEET 1 OF 2

Donald Barnes

Sep 19, 2012

CORNER CODE R-25

A.E. 7.08 REQUIREMENT

