

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

UNION TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B			6				5					4				3				2				1		B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010 _____

GPS (X) _____ TRAVERSE (X)

BASED ON THE FOLLOWING CONTROL:

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE 2-11(1)

UN626 S1/4CORSECC33

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 BRINK & MULLETT (SEP 12) T4N R10E
WEST ON SOUTH SIDE OF SECTION 33 (PG109)
241.56 B. OAK 5
2640.00 SET QUARTER SECTION POST B. OAK 18 N53W
81.84'; B. OAK 6 N66 1/2E 128.7'
3234. STREAM 2.64' CROSS SOUTH
4620 ENTER PRAIRIE
5280.00 SET POST FOR CORNER TO SECTION 32 & 33 IN
PRAIRIE MADE A SQUARE MOUN OF EARTH AND
SODS 3 FEET HIGH & 3 FEET DIAMETER AT THE
BASE. LAND EAST OF PRAIRIE ROLLING SECOND
RATE TO TIMBER BURR AND B. OAK HAZLE RED
ROOT CROSSES PRAIRIE LEVEL & RICH FIRST
RATE COVERED WITH GRASS
- 1846 BENSON MAGNOLIA BK 1 PG 1 COMMENCING IN THE CENTER
OF THE HIGHWAY RUNNING FROM MADISON TO БЕЛОIT UPON
THE CENTER LINE OF SEC 4 T3N R10E & RUN THENCE NORTH
ALONG THE CENTER OF SECTION 4441.8' TO QUARTER POST
UPON THE NORTH LINE OF SAID SEC 4 THE CORNER AND
DISTANCES ARE THE CENTER OF THE ROAD. VARIATION OF
THE MAGNETIC NEEDLE IS 8 EAST.
- 1863 LOCKE VOL 1 PG 196 @ N 1/4 COR SEC 4 PLACED RED HH
14X11X6 WEST OF SOUTH QUARTER SEC 33. SHOWS
2663.74 TO THE NW COR & NE COR OF SEC 4 & EAST 129.36
TO THE SOUTH QUARTER COR OF SEC 33. N 1/4 COR SEC 4
USED TO SUBDIVIDE SEC 4
- 1870 RUGER AUG REMON-81 EAST ON SOUTH LINE OF SW 1/4
SEC 33 ON A VAR 6-57 OFFSET SOUTH 14.02'
AT
2623.00 INTERSECTED QUARTER LINE 15.84' SOUTH OF
QUARTER CORNER. FOUND STUMP OF SOUTH
BEARING TREE AND REMAINS OF STUMP OF
NORTH BEARING TREE. COR VAR 7-00'
EAST ON SOUTH LINE OF SE 1/4 SEC 33
ON A VAR 7-456 AT
2626.80 INTERSECTED EAST BOUNDARY LINE AT CORNER.
- 1891 BLEEDORN VOL 2 PG 457 SHOWS SOUTH QUARTER COR
OF SEC 33 AND AN IRON ROD 990 WEST OF IT & ON THE
SOUTH LINE OF THE SW 1/3 OF SEC 33.
- 1906 KERCH VOL 3 PG 36 FD MON. USED TO SUBDIVIDE SEC 33
- 1963 BATTERMAN (COMBS) VOL 4 PG 150 & #6982 FD CUT STONE
SHOW ON E/W FENCE LINE
- 1973 LEE CSM VOL 3 PG 208 LS 2628.06 TO LS @ SE COR SEC
33
- 19?? UNK LETTER ON BACK OF QUAD SHEET. CUT LIMESTONE
898.86
- 1975 COMBS CSM VOL 4 PG 338 CUT STONE. EAST 2629.24 FD
REF TIES.
- 1975 COMBS #2721 FD CUT LIMESTONE @ S 1/4 COR SEC 33
WHICH IS 126.39 EAST OF N 1/4 COR SEC 4.
- 1990 COMBS CSM VOL 15 PG 30 N 1/4 COR SEC 4 FD 1" PIPE.
USED ALUM @ S 1/4 COR SEC 4 FOR LINE. SHOWS A PK 6.38
WEST OF R/R SPIKE @ CENTER OF SEC 4.
- 1991 BARNES VOL 6 PG 421 FD LS. N89-15-31W 128.55 TO FD
RED HH @ N 1/4 COR SEC 4 & N0-16-06E 2659.46 TO
PLACED PK FROM TIES @ CENTER OF SEC 33
- 1991 BARNES Z-11 @ S 1/4 COR SEC 33 FD CUT LIMESTONE.
PLACED CARSONITE AT SW CORNER OF L.S. & PLACED
TWO MAGNETS ON SOUTH SIDE OF STONE. REFERENCED
SAME. ON SOUTH SIDE OF E/W FENCE LINE. N89-14-51W
SHEET 1 OF 2

SEAL
Emboss
Donald Barnes
Oct 20, 2011

CORNER CODE Z-11(1)

UN626 S1/4CORSECC33

- 130.26 TO FD RED 14X6X10 HH @ N 1/4 COR SEC 4.
REPLACED HH WITH ALUM. MON & PLACED CARSONITE ON
NORTH SIDE OF ALUM. MON.
- 1991 BARNES A-11 @ S 1/4 COR SEC 33 FD CUT LIMESTONE.
PLACED CARSONITE AT SW CORNER OF L.S. & PLACED
TWO MAGNETS ON SOUTH SIDE OF STONE. REFERENCED
SAME. ON SOUTH SIDE OF E/W FENCE LINE. NB9-14-51W
130.26 TO 14X6X10 HH @ N 1/4 COR SEC 4. REPLACED
HH WITH ALUM. MON & PLACED CARSONITE ON NORTH
SIDE OF ALUM. MON.
- 1992 COMBS CSM VOL 16 PG 86 LS SB9-43-40E 2629.24 TO
ALUM @ SE COR SEC 33. . @ S 1/6TH COR OF SE 1/4 FD
PIPE 3.2 WEST.
- 1993 COMBS CSM VOL 17 PG 1 LS 2629.24 TO ALUM @ SE COR
SEC 33
- 1995 COMBS CSM VOL 18 PG 191 COMBS CSM VOL 17 PG 1 LS
2629.24 TO ALUM @ SE COR SEC 33

FD CUT LIMESTONE & REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD CUT LIMESTONE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

A circular seal with the name "Donald Barnes" and the word "Embloss" below it. The seal is partially obscured by a signature.

SHEET 2 OF 2

Barnes

OCT 20, 2011

CORNER CODE Z-11(1)

A.E. 7.08 REQUIREMENT