

Paper weight-110# (minimum) Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 10 E. 4th P.M.
 CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
 REV 10/23/2004 USMONREC.DWG

UNION TWP
 ROCK COUNTY WI

IF AVAILABLE
 ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4				3				2				1				B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
 PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____
 East _____
 Hor. Datum _____ Vert. Datum _____
 LATITUDE _____ ELLIPS. HT. _____
 LONGITUDE _____
 NAD83(91) _____ NETWORK ADJ. YR 2010
 GPS (X) _____ TRAVERSE (X) X
 BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT ○ WITNESS MONUMENT

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
 OR OBSERVATION SHEET _____

SHEET 1 OF 4

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE A-9(4)

UN505 NECORSEC5

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 BRINK SOUTH BOUNDARY OF T5N R10E WEST ON SOUTH SIDE SECTION 33

- 208.56 BURR OAK 14
- 2408.34 BURR OAK 12
- 2640.00 SET QUARTER SECTION POST BURR OAK 9 N1E 29.70'; BUR OAK 10 N59 1/2E 58.74'
- 5280.00 SET POST CORNER TO SECTIONS 32 & 33 BURR OAK 12 N2? 4E 84.48'; BURR OAK 12 N63 1/2W 112.70' LAND & C SAME

1833 BRINK SOUTH BOUNDARY OF T5N R10E WEST ON SOUTH SIDE SECTION 32

- 2304.72 W. OAK 16
- 2640.00 SET QUARTER SECTION POST BURR OAK 10 N60E 38.28'; BURR OAK 10 N87W 21.78'
- 2929.74 W. OAK 14
- 5280.00 SET POST CORNER TO SECTIONS 31 & 32 BURR OAK 16 N62E 59.40'; BUR OAK 14 N48W 42.90' LAND & C SAME

1833 HARRISON (OCT 6) T5N R10E NORTH BETWEEN SECTIONS 32 & 33

- 1014.42 B. OAK 14 IN
- 1333.86 B OAK 16 IN
- 2640.00 SET 1/4 SEC POST B.B. O 15IN N30E 231.0'; B.B. O 18 IN N37W 171.60'
- 3202.98 B. OAK 15 IN
- 4626.60 B. OAK 22 IN
- 5280.00 SET POST COR SECT 28,29,32,33 B.B. O 12 IN S71W 627'; B.B. O 8 IN N59 1/2E 450.12' LAND LEVEL 2 RATE B.W. & YELLO OAK OAK & HAZEL UNDERBRUSH INDIGO, RED ROOT ????? OCT 6, 1833

1833 HARRISON (NOV 9) T4N R10E 4TH MER. NORTH BETWEEN 4 & 5

- 2640.00 QUARTER SEC COR {BURR O 18 S16W 38.94'; BURR O 12 N78E 27.72' BURR O 18 & BURR O 12} MARKED
- 5181.00 INT. NORTHERN BOUNDARY 92.4' WEST OF P {W.O. 12 S48E 110.22'; BURR O 18 S79W 108.9' W.O. 12 & BURR O 18} MARKED LAND SAME NOV 9TH 1833

1856 CHURCH VOL 1 PG 61 STATES NOTHING ABOUT MON. VAR 8 2779.26 TO N 1/4 COR SEC 5

1870 RUGER AUG REMON-117 NORTH ON WEST LINE OF SW 1/4 SEC 4 ON A VAR 7-30; OFFSET WEST 7.92' OFFSET EAST 15.84' AT

- 2654.52 INTERSECTED QUARTER LINE 42.24' WEST OF QUARTER CORNER. FOUND LARGE STONE SURROUNDED BY SEVERAL STONES AT CORNER. ALSO FOUND STUMP OF EAST BEARING TREE. COR VAR 6-25

NORTH ON WEST LINE OF NW 1/4 SEC 4 ON A VAR 6-50; OFFSET EAST 11.22' OFFSET WEST 15.84' AT

- 2561.46 INTERSECTED NORTH BOUNDARY LINE 1.98' EAST OF CORNER. COR VAR 6-58

1870 RUGER AUG REMON-115 WEST ON NORTH LINE OF NE 1/4 SEC 4 ON A VAR 7-13; OFFSET SOUTH 12.54' INTERSECTED QUARTER LINE OF SECTION 33, T5N R10 13.86' SOUTH OF QUARTER CORNER. COR

Donald Barnes
Nov 9, 2011

UN505 NECORSEC5

- VAR 7-11 CONTINUED WEST ON NORTH LINE OF NW QUARTER ON A VAR 7-13; OFFSET SOUTH 14.52' OFFSET NORTH 37.62' AT
- 5324.22 INTERSECTED WEST BOUNDARY LINE 3.96' SOUTH OF CORNER. FOUND CORNER ESTABLISHED BY CHURCH FROM BEARING TREES. ALSO FOUND STUMP OF WEST BEARING TREE AND REMAINS OF STUMP OF EAST BEARING TREE. CORNER ESTABLISHED BY CHURCH CORRECT. COR VAR 6-37' ESTABLISHED NORTH QUARTER CORNER OF SECTION 4 ON THE TOWN LINE AND EQUI-DISTANT FROM THE NE AND NW CORNERS OF SAID SECTION. IT BEING 2662.11 DISTANT FROM EACH AND 63.52' WEST OF THE SOUTH QUARTER CORNER OF SECTION 33 T5 R10
- 1870 RUGER AUG REMON-118 SEPTEMBER 7, 1870 WEST ON NORTH LINE OF NE 1/4 SEC 5 ON A VAR 7-30; OFFSET NORTH 15.18' INTERSECTED QUARTER LINE OF SECTION 32 T5 R10 19.8' NORTH OF QUARTER CORNER. COR VAR 7-36 CONTINUED WEST ON NORTH LINE OF NW QUARTER SECTION 5 ON A VARIATION 7-30; OFFSET NORTH 19.8' OFFSET NORTH 10.56' OFFSET SOUTH 8.58' OFFSET NORTH 5.28 AT
- 5560.50 INTERSECTED WEST BOUNDARY LINE 7.92' NORTH OF CORNER. FOUND OLD STAKE AT CORNER. ALSO FOUND REMAINS OF THE STUMPS OF THE BEARING TREES. COR. VAR 7-05 ESTABLISHED NORTH QUARTER CORNER OF SECTION 5 ON THE TOWN LINE AND AT A POINT EQUI-DISTANT FROM THE NE AND NW CORNERS OF SAID SECTION. IT BEING 2780.25 DISTANT FROM EACH.
- 1892 MARCY VOL 6 PG 351 COPIED FROM DANE COUNTY SURVEYOR'S RECORDS-BK6 PG 206 & 207 2/17/1886. DISTANCES IN FEET. COURSES TRUE BEARINGS VAR 4-3-15 & ??-42E FROM DUE NORTH SEE FB F P1-15. @ NE COR SEC 5 STATES "ROCK COUNTY STONE" & 92.4 WEST OF SE COR SEC 32. 2621.5 FROM SE COR SEC 32 TO S 1/4 COR SEC 32. SHOWS N88-55E 5243 ALONG SOUTH SECTION LINE. VAR7-4 2649 TO SET STAKE @ E 1/4 COR SEC 32. CALLS FOR THE EAST LINE OF SEC 32 AS N2-58W 5298. SW COR SEC 32 RUN N88-55E TO THE SE COR SEC 32 FOUND BY MEASURING 92.4 FROM THE ROCK COUNTY CORNER STONE, ACCORDING TO THE US FIELD NOTES, NO WITNESS TREES REMAINING; THENCE N2-58W 5298 TO THE NE CORNER OF SEC 32. SHOWS NE COR SEC 5 AS WEST OF SE COR SEC 32.
- 1904 KERCH VOL 3 PG 22 MON 2787.5 TO MON @ N 1/4 COR SEC 5, 2569.4 TO MON @ E 1/4 COR SEC 5
- 1978 BARNES VOL 5 PG 386 FD CUT LIMESTONE 0.7' DEEP ON LINE WITH FENCE TO THE WEST. SET 1X24 IRON BAR (SQUARE) HORIZONTALLY & 18" DEEP ON WEST SIDE OF STONE. REF SAME. 171' EAST OF CENTER OF STH 14 & 104' NW OF NE BLDG COR.
- 1978 LEE #5073 CUT STONE. EAST 2673.18 TO CUT STONE @ N 1/4 COR SEC 4, & S0-27-44E 2569.61 TO IP @ W 1/4 COR SEC 4, & S89-16-46W 2787.27 TO CUT STONE @ N 1/4 COR SEC 5
- 1978 LEE CSM VOL 7 PG 248 FD CONG. MON. POB S89-16-46W 126.49 TO PIPE ON EAST R/W LINE WHICH IS 42.09 FROM CENTER OF USH 14; THENCE S37-37-20E 410.95 TO PIPE.

SEAL

Arnold Barnes
Nov 9, 2011

SHEET 2 OF 4

CORNER CODE A-9(2)

UN505 NECORSECS

- 1979 WILHELM #40034 & #5074 FD 6X6 LIMESTONE MON. 92.40 WESTERLY OF IP @ SE COR SEC 32. FROM SE COR SEC 32 TO S 1/4 COR SEC 32 IS S89-22-13W 2613.48, FROM SE COR SEC 32 TO IRON PIPE @ S 1/4 COR SEC 33 IS S89-51-47E 2645.60, & FROM SE COR SEC 32 TO PIPE @ E 1/4 COR SEC 32 IS N2-53-16W 2647.94
- 1980 FED #5075 6X6 LIMESTONE MON. N89-22-13E 92.40 TO 1" PIPE @ SW COR SEC 33. SO-23-37E 2569.69 TO 1" PIPE @ W 1/4 COR SEC 4. 2672.76 TO 6X6 LIMESTONE @ N 1/4 COR SEC 4.
- 1983 COMBS #13056 (MORTGAGE INSPECTION) STATES NOTHING ABOUT MON. CALLS FOR PIPE @ SW COR SEC 33-5-10; THENCE S89-18-40W 219.11 ALONG SEC LINE TO PIPE ON EAST R/W OF STH 14; THENCE N40-39-38W 242.38 TO PIPE.
- 1986 KARNS #13305 & 13304 SEC COR. EASTERLY OF USH 14. N89-54-21W TO NW COR SEC 5, SO-19-49W TO E 1/4 COR SEC 5.
- 1987 WILLIAMSON CSM VOL 13 PG 137 FD CUT LS SO-22-36W TO FD PK @ E 1/4 COR SEC 5
- 1987 RADEL A-9 FD 0.7X.7 CUT LIMESTONE BURIED 0.7' +/- DEEP AT THE NE COR OF SEC 5, TOWN OF UNION, AS PER ROCK COUNTY TIE SHEET DATED FEB 3, 1978. ABOUT 126.6 EAST OF THE EAST PVMT EDGE OF USH 14 & 104.40' NW OF NE HSE COR.
- 2006 LATHROP CSM VOL 30 PG 307 FD CUT LS. SO-03-37W 2569.52 TO FD PK @ W 1/4 COR SEC 4

FD CUT LIMESTONE 0.7' DEEP. PLACED 2 MAGNETS ON TOP. ALSO FD REFERENCE PIPES & PIPE @ SE COR SEC 32.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?


ACCEPTED FD CUT LIMESTONE @ NE COR SEC 5 & PIPE @ SE COR SEC 32 T5N R10E.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.


 Donald Barnes
 Nov 9, 2011

SHEET 3 OF 4

CORNER CODE **A-9(1)**
 A.E. 7.08 REQUIREMENT 2

