

COUNTY SURVEYOR  
RECORD 2 1869-1900



Found old stone - Drove  
New stone in place of  
old one 7 feet out of  
it - line alone 10x6 1/4  
The corner is 10 1/2 feet  
south of 24 60 fence  
& 4 1/2 feet south of  
corner of 9th. Corner  
of Sec. 34 Rock

Found old stone and where  
shanks of B. T. had been dug up.  
Drove new stone deep in place of  
old one 7 feet out of it - line alone  
20 x 6 x 1 1/2 - 4 1/2 feet  
head head alone in the  
ground where the B. T.  
shanks had been dug  
up.

Found old stone - Drove  
New stone deep in place  
of old one 7 feet out of  
it - line alone 20 x 6 x 1 1/2  
4 1/2 feet head head alone  
The corner is at  
intersection  
of fences

Found old stone in highway  
Drove new stone deep in place  
of old one 7 feet out of it -  
line alone 16 x 6 x 8 - The corner  
is 4 1/2 feet south of 24 60 fence  
from base of road 24 57 feet  
from base of road 24 57 feet  
side of road

Established corner from  
Drove new stone deep in place  
of old one 7 feet out of it -  
line alone 13 x 7 x 5 - The corner  
is 9 inches west of corner  
established by Church

3 1/2 lines alone 15 x 6 x 2 1/2  
The corner is 5 1/2 feet south of  
road 24 60 fence 24 34 feet  
west of fence running north

Found old stone - Drove new stone deep  
in place of old one 7 feet out of it - line alone  
16 x 11 x 1 1/2 - laid flat one top of stone - Also  
set line alone 50 feet west for west  
line of road - From the corner it is 39 feet  
to fence on east side of road 7 68 1/2 feet to  
fence on west side of road - The corner is  
in line of 29 W. fence

Found fence post on corner. Also found  
shanks of B. T. B. T. should read  
39 instead of 29 feet - set line alone  
18 x 10 x 2 1/2 close to post on east side  
The corner is in line fence running west

Found line alone at corner -  
The corner is 50 feet from fence on  
west side of road and in line with  
fence running west

Found stone set by Church correct

Found old stone and line alone at corner  
Drove new stone in place of old one 7 feet out of it -  
line alone 23 x 7 x 6 - The corner is 48 feet south  
of nose of east side of road on north side of road running  
East 4 1/2 feet north of fence on north side of road  
measuring East 7 41 1/2 feet west of fence on east side  
of N.T.S. toward 7 61 feet East of nose of post on  
base on west side of N.T.S. road

Found line & old stone - Drove new stone in  
place of old one 7 feet out of it - line alone  
17 x 8 x 2 1/2 - Also set line alone 50 feet west  
From the corner it is 48 1/2 feet to fence on  
east side of road 7 66 1/2 feet to fence on west  
side of the road - The corner is nearly in  
line of fence running west

Set line alone 15 x 6 x 2 1/2 at corner. Also  
set line alone 50 feet west - From the  
corner it is 47 1/2 feet to fence on east of  
road 7 60 feet to fence on west of road  
The corner is in line of fence running east

Found old stone - Drove new stone deep in  
place of old one 7 feet out of it - line alone  
16 x 11 x 1 1/2 - laid flat one top of stone - Also  
set line alone 50 feet west for west  
line of road - From the corner it is 39 feet  
to fence on east side of road 7 68 1/2 feet to  
fence on west side of road - The corner is  
in line of 29 W. fence

Found fence post on corner. Also found  
shanks of B. T. B. T. should read  
39 instead of 29 feet - set line alone  
18 x 10 x 2 1/2 close to post on east side  
The corner is in line fence running west

The above is a plat and record of a survey made by me on sections  
34 10 Belvid & section 34 Rock June 18 & 19 - 1924

Edward Raper  
County Surveyor