

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 3 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C	6																								C
D																									D
E																									E
F																									F
G	7																								G
H																									H
J																									J
K	18																								K
L																									L
M																									M
N																									N
O																									O
P	19																								P
Q																									Q
R																									R
S																									S
T	30																								T
U																									U
V																									V
W																									W
X	31																								X
Y																									Y
Z																									Z

JANESVILLE TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE A-23(1)

JA 512
EU632^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1835 (JAN 7) MULLETT & BRINK WEST ON SOUTH SIDE SECTION 36
T4N R12 VAR 8 20 EAST

- 1828.86 BUR OAK 10
2640 SET 1/4 SECTION POST W. OAK 22 N37W 112.2'
BUR OAK 10 N35E 19.14'?
- 4486.02 BUR OAK 10
5280 SET POST COR SECTIONS 35 & 36 B. OAK 10
N49W 135.3' B. OAK 12 N86E 9.24' LAND
GENTLY ROLLING 2ND RATE W. B. & BUR OAK
- 1866 JANESVILLE TWP RD REC BK 2 PG 32 COMMENCING AT THE
NORTHEAST COR OF SEC 1 IN SAID TOWN OF JANESVILLE &
IN THE CENTER OF THE HIGHWAY RUNNING BETWEEN THE
TOWNS OF JANESVILLE AND HARMONY, RUNNING THENCE
WEST ON NORTH LINE OF SAID SECTION 1 AND 2 IN SAID
TOWN OF JANESVILLE.
- 1866 FULTON TWP RD REC BK 1 PG 44 COMMENCING AT THE
NORTH EAST CORNER OF SECTION ONE OF THE TOWN OF
JANESVILLE AND IN THE CENTER OF THE HIGHWAY RUNNING
BETWEEN THE TOWNS OF JANESVILLE & HARMONY RUNNING
THENCE WEST ON THE NORTH LINE OF SAID SECTION 1 ONE
MILE TO THE CENTER OF THE HIGHWAY RUNNING BETWEEN
SECTIONS 1 & 2 IN SAID TOWN OF JANESVILLE. THE LINE OF
SAID SURVEY TO BE THE CENTER OF SAID HIGHWAY WHICH
LINE IS THE TOWN LINE BETWEEN THE TOWNS OF FULTON &
JANESVILLE AND THE SAME IS ESTABLISHED 66' IN WIDTH;
33' ON EACH SIDE OF SAID LINE.
- 1866 JANESVILLE TWP RD REC. BK 1 PG 408 COMMENCING AT THE
NORTHEAST CORNER OF SECTION IN SAID TOWN OF
JANESVILLE AND IN THE CENTER OF THE HIGHWAY RUNNING
BETWEEN THE TOWNS OF JANESVILLE AND HARMONY
RUNNING THENCE WEST ON THE NORTH LINE OF SAID
SECTION 1 5280' TO THE CENTER OF THE HIGHWAY RUNNING
BETWEEN SECTIONS 1 AND 2 IN SAID TOWN OF JANESVILLE.
THE LINE OF THE SAID SURVEY TO THE CENTER OF THE
HIGHWAY WHICH LINE IS THE TOWN LINE OF SAID TOWNS OF
JANESVILLE AND FULTON; AND THE SAME IS ESTABLISHED
66' IN WIDTH, 33' ON EACH SIDE OF SAID LINE.
- 1867 LOCKE VOL 1 PG 297 & #1482 FD W.B.T. & STAKE SET STAKE
WITH HARDHEAD ON N.S.E. & W VAR 7-15 ALONG N/S 1/4 LINE
SEC 36.
- 1872 LEE VOL 2 PG 93 CALLS FOR BUT STATES NOTHING ABOUT
MON. 10.23' WEST OF N 1/4 COR SEC 1 JANESVILLE TWP. VAR
6-50 2623.50' FROM N 1/4 COR TO NE COR SEC 1, 2623.50
FROM N 1/4 COR TO NW COR SEC 1.
- 1875 RUGER VOL 2 PG 190 STAKE SURROUNDED BY 4 HH STONES
SEE BK 1 PAGE 2650.56 TO CEN SEC 36
- 1947 SUNNY #1478 STATES SET PIPE AT S 1/4 COR SEC 36, 2632.X
TO SE COR SEC 36, 2638.7X TO SW COR SEC 36, 2648.9 TO
SET PIPE AT CEN OF SEC 36, & 5304.7 TO N 1/4 COR SEC 36.
- 1961 BATTERMAN VOL 4 PG 96 DUG & FD NOTHING.
- 1965 LEE CSM VOL 1 PG 120 STATES NOTHING ABOUT MON.
- 1965 LEE CSM VOL 1 PG 118 STATES NOTHING ABOUT
MONUMENTS. PIPE 33.00 SOUTH OF N 1/4 COR SEC 1. S 1/4
COR SEC 36 IS 10.23 WEST OF N 1/4 COR SEC 1
- 1965 LEE #2170 STATES NOTHING ABOUT MON. PIPE 33.0 SOUTH
OF N 1/4 COR SEC 1, S 1/4 COR SEC 36 IS 10.23' WEST OF N 1/4
COR SEC 1
- 1970 LEE VOL 1 PG 310 SET PIPE
- 1977 SCHROEDER CSM VOL 6 PG 244 STATES NOTHING ABOUT
MON.

Donald Barnes
Dec 13, 2007

SHEET 1 OF 2

A-23(1)

JA 512

~~RU632~~

- * 1978 COMBS #2167 PIPE @ N 1/4 COR SEC 1
- 1982 SCHROEDER #2184 STATES NOTHING ABOUT MON. PIPE @ PROPERTY COR IS 217.03 SOUTH OF N 1/4 COR SEC 1
- 1987 BARNES A-23 FD TIES. DUG 1.6X1.6 2' DEEP HOLE 10.2' WEST OF S 1/4 COR SEC 36 & FD NOTHING. POLY MON AT N 1/4 COR SEC 1 & S 1/4 COR SEC 36. N 1/4 COR SEC 1 10.23 EAST OF S 1/4 COR. S 1/4 COR 278,587.09; 2,262,294.68 N 1/4 COR SEC 1 278,587.29; 2,262,304.93
- 1987 BARNES VOL 6 PG 365 N89-03-39E 2636.10 FROM SW TO S 1/4 COR SEC 36.
- 1991 COMBS #11761 ALUM AT N 1/4 COR SEC 1 2619.46 TO NE COR SEC 1
- 1992 COMBS CSM VOL 15 PG 361 ALUM @ N 1/4 COR SEC 1. 2619.46 FROM N 1/4 TO NE COR SEC 1
- 1995 LATHROP CSM VOL 18 PG 174 ALUM @ N 1/4 COR SEC 1 & S 1/4 COR SEC 36. S 1/4 COR SEC 36 IS WEST 10.08 OF N 1/4 COR SEC 1. 2609.72 FROM S 1/4 COR SEC 36 TO NW COR SEC 1. THERE IS A PROPERTY PIN 35.0 SOUTH OF N 1/4 COR SEC 1
- 2000 LATHROP CSM VOL 23 PG 310 ALUM @ N 1/4 COR SEC 1.
- 2002 COMBS CSM VOL 25 PG 276 ALUM. MON. @ S 1/4 COR SEC 36 & N 1/4 COR SEC 1. PIN 40.00 SOUTH OF N 1/4 COR SEC 1. 2619.36 FROM N 1/4 COR SEC 1 TO NE COR SEC 1.
- 2002 COMBS CSM 26 PG 116 ALUM @ N 1/4 COR SEC 1 & S 1/4 COR SEC 36. S 1/4 COR SEC 36 IS 10.23 WEST OF N 1/4 COR SEC 1.
- 2005 COMBS CSM VOL 28 PG 293 5306.33 TO N 1/4 COR SEC 36 & ANGLE 90-59-03 @ N 1/4 COR SEC 36 FROM NE TO S 1/4 COR SEC 36.

FD MONUMENTS & REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD MONUMENTS.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes

Emboss
Barnes

Dec 13, 2007

SHEET 2 OF 2

CORNER CODE **A-23(1)**

A.E. 7.08 REQUIREMENT