

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	7																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R		20																							
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARIC TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 579

FIELD BOOK _____ PAGE # _____

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE P21(1)

NE579

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 10 NORTH BETWEEN 23 & 24
1610.4 BUR OAK 6 IN DIA
2640 SET 1/4 SEC POST BUR OAK 10 IN N79W 26.4'; BUR OAK 14 IN N40E 22.44'
4745.4 BUR OAK 12
5280 SET POST COR SECS 13,14,23,24 BUR OAK 16 IN N79E 44.22'; BUR OAK 14 IN S33W 21.12' LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY. OAK & HAZEL UNDERGROWTH
- 1863 LOCKE VOL 1 PG 185 FD OLD BT STUMPS SET HH 13X10X7 SURROUNDED BY 4 SMALL LIMESTONES ON N,S,E,W SIDE OF IT. 2667.72 TO CENTER OF SEC 24, 5335.44 TO E 1/4 COR SEC 24, VAR 5-10 2682.9 TO SW COR SEC 24
- 1871 COLLINS REMONUMENTATION NOTES
PG 137 NORTH BETWEEN 23 & 24 VARIATION 4-35
2694.78 INTERSECT 1/4 LINE 3.3' WEST OF CORNER SET 1/4 STONE BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 4-39
CONTINUED NORTH VARIATION 4-30
5384.94 INTERSECT SECTION LINE 7.26' WEST OF CORNER. SET STONE FOR CORNER SECTIONS 13,14,23,25 IN PLACE OF STONE AGREEING WITH ROOTS OF WITNESS TREES. CORRECTED VARIATION 4-40
- 1961 BATTERMAN VOL 4 PG 90 DUG & FD 6X8 CUT STONE BROKEN BY PREVIOUS EXCAVATION. SET MON. BOX OVER 1" PIPE & REFERENCED SAME.
- 1988 LEE #12358 2685.54 TO NE COR SEC 23
- 1995 BARNES P-21 COORDINATES WERE SUPPLIED BY WPL. THE SURVEY WAS BY GPS & CONNECTED TO THREE ROCK COUNTY GPS CONTROL MONUMENTS; BRODHEAD (305S), AVON (312S), & NEWARK EAST (313S) NAD83(91) 195,622.611; 2,197,733.925. I CONVERTED THEM TO COUNTY & USED AS CONTROL POINT IN TWP ADJUSTMENT. N/S 459,155.969; E/W 214,690.166

FD 1" PIPE IN MON. BOX.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal



emboss

7-02-01

Number of included sheets **D**

CORNER CODE **P-21(1)**

A-E 7.08 REQUIREMENT