

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																										
B	6																									
C		5																								
D			4																							
E				3																						
F					2																					
G	1																									
H		8																								
I			9																							
J				10																						
K					11																					
L						12																				
M	18	◆	17			16																				
N							15																			
O								14																		
P									13																	
Q	19									20																
R											21															
S												22														
T													23													
U														24												
V															25											
W																26										
X																	27									
Y																		28								
Z																			29							
																				30						
																					31					
																						32				
																							33			
																								34		
																									35	
																										36

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL ◆ AT PROPER LOCATION ON ABOVE INDEX

◆ CORNER MONUMENT

○ WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

Fd TIES IN L5

FIELD BOOK 2 PAGE # 5

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE L-5(1)

HE555

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 35 NORTH BETWEEN SECS 17 & 18
1136.52 YELLOW OAK 24 IN DIAMETER
2640 SET 1/4 SEC POST. YELLOW OAK 6 IN S57W 54.12', YELLOW OAK 6 INCH
N70E 113.52'
3036 YELLOW OAK 24 IN DIAMETER
3924.36 YELLOW OAK 8 IN DIA.
5280 SET POST COR SEC 7,8,7,18 LAND ROLLING 2RD RATE TIMBER OAK &
HICKORY *BEARINGS TO COR 7,8,17,18 YELLOW OAK 8 S12-30W 71.28',
BUR OAK 14 N36E 62.04' MARCH 12, 1834
- 1871 COLLINS REMONUMENTATION NOTES
PG 193 NORTH BETWEEN 17 & 18 VARIATION 5-45
2663.76 SET 1/4 STONE BY STUMP OF WITNESS TREES
CONTINUED NORTH VAR 5-30
5324.88 INTERSECT SECTION LINE 5.28' EAST OF CORNER SET STONE FOR
CORNER OF 7,8,17,18 BY STUMPS OF WITNESS TREES.
CORRECTED VARIATION 5-23
- 1937 SUNNY VOL 3 PG 358 FD 6X6 CUT STONE MON. SET 1 1/2X10: CAPPED PIPE ON
TOP & REFERENCED SAME. NOTE: 7/18/69 SET MON OVER SCRIBED STONE.
1970 BATTERMAN VOL 4 PG 438 STONE IN MON BOX. REFERENCED COR.
1989 BARNES VOL 6 PG 401 2660.44 TO NW COR SEC 17, 2666.32 TO SW COR SEC 17, &
ANGLE OF 180-00-06 @ W 1/4 COR SEC 17 FROM NW COR SEC 17 TO SW COR SEC
17. FD C.I.
1989 BARNES L-5 FD C.I. & REFERENCED SAME. @ CENTER OF PVMT.
1993 COMBS CSM 16 PG 182 2666.33 TO SE COR SEC 18

FD C.I.

(C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal



Number of included sheets 1

emboss

6-29-01

CORNER CODE L-5(1)

A-E 7.08 REQUIREMENT