

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE N-5(1)

NE563

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER

PG 35 NORTH BETWEEN SECS 17 & 18

1136.52 YELLOW OAK 24 IN DIAMETER

2640 SET 1/4 SEC POST. YELLOW OAK 6 IN S57W 54.12', YELLOW OAK 6 INC N70E 113.52'

3036 YELLOW OAK 24 IN DIAMETER

3924.36 YELLOW OAK 8 IN DIA.

5280 SET POST COR SEC 7, 8, 7, 18 LAND ROLLING 2RD RATE TIMBER OAK & HICKORY *BEARINGS TO COR 7,8,17,18 YELLOW OAK 8 S12-30W 71.28', BUR OAK 14 N36E 62.04' MARCH 12, 1834

PG 34 WEST RANDOM BETWEEN SEC 18 & 19

5320.26 INTERSECT RANGE LINE 33' SOUTH POST

LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY SCATTERING

EAST CORRECTION

SET POST COR 18 & 19

BUR OAK 18 S65E 35.64'; BURR OAK 22 N75E 29.04'

2680.26 SET 1/4 SEC POST BUR OAK 16 S13W 73.92', BUR OAK 16 N18W 34.98'

4696.56 YELLOW OAK 24 IN DIA

5320.26 SEC COR

PG 33 NORTH BETWEEN SECS 19 & 20

706.2 BUR OAK 14 IN

2425.5 WHITE OAK 22 IN

2640 SET 1/4 SEC POST YELLOW OAK 15 S43W 34.32'; WHITE OAK 24 N43E 69.3'

3689.4 BUR OAK 18 IN DIA

5103.12 YELLOW OAK 22 IN DIA

5280 SET POST COR SECS 17,18,19,20 YELLOW OAK 10 N78E 100.32'; BUR OAK 20 S44W 69.3' LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY OAK & HAZEL U.G. PRAIRIE GRASS TOO

PG 34 EAST RANDOM BETWEEN SECS 17 & 20

330 ENTER MARSH C S.E.

2112 LEAVE SAME

5272.74 SEC LINE 13.2' NORTH OF POST LAND 2ND RATE

WEST CORRECTED BETWEEN SECS 17 & 20

2636.04 SET 1/4 SEC POST YELLOW OAK 5 IN N20E 30.36'; BUR OAK 22 S30W 9.24'

5272.74 SEC COR

1870 RUGER VOL 2 PG 42. FOUND OLD STAKE, ALSO FOUND STUMPS OF S.W. BEARING TREE & WHERE STUMPS OF NE BEARING TREE HAD BEEN DUG UP. SET LIMESTONE 19X10X4 AND SURROUNDED IT WITH 3 LIMESTONES. VAR 5-05 2647.04 TO N 1/4 COR SEC 19 & VAR 5-35 2653.2 TO E 1/4 COR SEC 19

1871 COLLINS REMONUMENTATION NOTES

PG 193 NORTH BETWEEN 17 & 18 VARIATION 5-45

2663.76 SET 1/4 STONE BY STUMP OF WITNESS TREES

CONTINUED NORTH VAR 5-30

5324.88 INTERSECT SECTION LINE 5.28' EAST OF CORNER SET STONE FOR CORNER OF 7,8,17,18 BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 5-23

PG 192 WEST BETWEEN 18 & 19 VARIATION 3-50

2652.54 SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING WITH ROOTS OF WITNESS TREES.

EAST BETWEEN 18 & 19 (NOV 4) VARIATION 3

2750.88 1/4 STONE SET NOV 2

Donald Barnes
6-29-01

SHEET 1 OF 2

N-5(1)

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6				5					4				3						2				1
C																								
D																								
E																								
F																								
G	1					8				9				10					11				12	
H																								
I																								
J																								
K																								
L	18					11				16				15					14				13	
M																								
N																								
O																								
P	19					20				21				22					23				24	
Q																								
R																								
S																								
T	30					29				28				27					26				25	
U																								
V																								
W																								
X	31					32				33				34					35				36	
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT WITNESS MONUMENT

BEARINGS ARE BASED ON:

Fd TIES IN NS

OBSERVATION sheets 460
A14, 22B,

FIELD BOOK _____ PAGE # _____

SHEET 2 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE N-5(1)

2657.82 INTERSECT 1/4 LINE 3.3' WEST OF CORNER. SET 1/4 STONE IN PLACE OF STAKE SET BY RUGER AGREEING WITH STUMP OF WITNESS TREES. CORRECTED VARIATION 5-25

CONTINUED NORTH VARIATION 5-30

5315.64 INTERSECT SECTION LINE 9.24' WEST OF CORNER SET STONE FOR CORNER OF 17,18,19,20 IN PLACE OF STONE SET BY RUGER AGREEING WITH ROOTS OF WITNESS TREES CORRECTED VARIATION 5-42

2651.88 SET 1/4 STONE IN LINE WITH FENCES NORTH & SOUTH BY ROOTS OF WITNESS TREES.

CONTINUED EAST VARIATION 8-15

5305.74 SECTION CORNER. NOV 1, 1871

- 1937 SUNNY VOL 3 PG 358. FOUND 6X6" STONE MONUMENT. SET 1 1/2"X12" CAPPED PIPE ON TOP. PLACED REFERENCE TIES. 7/18/69 SET MON BOX OVER CAPPED PIPE WITH PUNCH MARK
- 1958 SHIMEALL #3178 ANGLE OF 88-50 @ SW COR SEC 17 FROM W 1/4 COR TO S 1/4 COR SEC 17
- 1969 BATTERMAN VOL 3 PG 358 SET MON BOX OVER CAPPED PIPE WITH PUNCH MARK.
- 1970 BATTERMAN JR. VOL 4 PG 437. SHOWS 4 REFERENCE TIES AND NOTES THAT STATES "C.T.H. K UNDER CONSTRUCTION. CORNERS TO BE RESET.
- 1989 BARNES VOL 6 PG 401 FOUND CAST IRON MONUMENT. N0-06-56E 2666.32 TO W 1/4 COR SEC 17, S1-15-42W 2659.05 TO W 1/4 COR SEC 20, N89-07-18E (SOLAR OBSERVATION) 2651.09 TO S 1/4 COR SEC 17, & ANGLE OF 89-00-23 (1958 SHIMEALL 88-50) @ SW COR SEC 17 FROM W 1/4 TO S 1/4 CORNERS OF SEC 17.
- 1992 BARNES N-5 FD CL. 1' NORTH OF E/W CENTER PVMT & 3' EAST OF N/S CENTER PVMT. FD NW & SW REFERENCE PIPES. REFERENCED SAME

FD C.I.


C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

 emboss
 6-29-01

SHEET 2 OF 2

CORNER CODE N-5(1)