

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. ___ N., R. ___ E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6					9									3										1
C																									
D																									
E																									
F																									
G	7																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 11A of 563

FIELD BOOK _____ PAGE # _____

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE P-5(1)

NE575

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 33 NORTH BETWEEN SECS 19 & 20
706.2 BUR OAK 14 IN
2425.5 WHITE OAK 22 IN
2640 SET 1/4 SEC POST YELLOW OAK 15 S43W 34.32'; WHITE OAK 24
N43E 69.3'
3689.4 BUR OAK 18 IN DIA
5103.12 YELLOW OAK 22 IN DIA
5280 SET POST COR SECS 17,18,19,20 YELLOW OAK 10 N78E 100.32';
BUR OAK 20 S44W 69.3' LAND GENTLY ROLLING 2ND RATE TIMBER
OAK & HICKORY OAK & HAZEL (UNDER GROWTH) PRAIRIE GRASS
TOO
- 1851 MC VEAN VOL 1 PG 6 STATES NOTHING ABOUT MON. 2645.28 TO CENTER OF
SEC 20 & 2640 TO SW COR SEC 20
- 1870 RUGER VOL 2 PG 42. FOUND OLD STAKE AND STUMPS OF NORTHWEST
BEARING TREE AND WHERE STUMPS OF SOUTHWEST BEARING TREE HAD
BEEN DUG UP. SET POINTED HARD HEAD 18X14X8 AND SURROUNDED IT WITH
4 HARD HEADS. SHOWS A DISTANCE OF 2653.20 VAR 5-35 THE NORTHWEST AND
2653.86 VAR 5-42 TO CORNERS OF SECTION 20, 2643.3 VAR 5-38 TO CENTER SEC
19, & VAR 5-38 5321.58 TO W 1/4 COR SEC 19.
- 1871 COLLINS REMONUMENTATION NOTES
PG 190 NORTH BETWEEN 19 & 20 VARIATION 5-20
2657.82 INTERSECT 1/4 LINE 3.3' WEST OF CORNER SET 1/4 STONE IN
PLACE OF STAKE SET BY RUGER AGREEING WITH STUMP OF
WITNESS TREES. CORRECTED VARIATION 5-25
CONTINUED NORTH VARIATION 5-30
5315.64 INTERSECT SECTION LINE 9.24' WEST OF CORNER SET STONE
FOR CORNER OF 17, 18,19,20 IN PLACE OF STONE SET BY RUGER
AGREEING WITH ROOTS OF WITNESS TREES CORRECTED VAR. 5-42
- 1937 SUNNY VOL 3 PG 358 FOUND 6X6" CUT STONE MONUMENT & REFERENCED
SAME. SET 1 1/2"X12" CAPPED PIPE ON TOP.
- 1969 BATTERMAN JR. VOL 3 PG 358 SET MONUMENT BOX OVER SCRIBED STONE.
- 1970 BATTERMAN JR. VOL 4 PG 437 SHOWS TIES TO 4 REFERENCE PIPES AND
NOTES THAT CTH "K" IS UNDER CONSTRUCTION AND CORNERS WILL BE
RESET.
- 1989 BARNES VOL 6 PG 401 FOUND CAST IRON MONUMENT, N1-15-42E (SOLAR
OBSERVATION) 2659.05 TO NW COR SEC 20, & ANGLE OF 92-08-24 @ NW COR
SEC 20 FROM N 1/4 COR TO W 1/4 COR SEC 20.
- 1997 BARNES P-5 COORDINATES WERE SUPPLIED BY WP&L. THE SURVEY WAS BY
& CONNECTED TO THREE ROCK COUNTY GPS CONTROL MONUMENTS;
BRODHEAD (305S), AVON (312S), & NEWARK EAST (313S). NAD83(91) WI STATE
PLANE COORDINATES N/S 195,742.883; E/W 2,176,545.487. I CONVERTED THEM
TO COUNTY PROJECTION - N/S 437,970.413; E/W 215,045.686

FD C.I MON 2' WEST OF CENTER OF PVMT. I USED WP&L COORDINATES AS A
CONTROL POINT IN THE NEWARK TWP ADJUSTMENT.

(C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found
perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was
determined by me under my direction and control and that this U.S. Public Land Survey Monument Record
is correct and complete to the best of my knowledge and belief.

Seal
Donald
Barnes
6-29-01

Number of included sheets 1

CORNER CODE P-5(1)

A-E 7.08 REQUIREMENT