

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			4																					
E				3																				
F					2																			
G	1																							
H		8																						
I			9																					
J				10																				
K					11																			
L						12																		
M	18						11																	
N								10																
O									9															
P										8														
Q											7													
R												6												
S													5											
T														4										
U															3									
V																2								
W																	1							
X																								
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

REFERENCED IN 1996

OBSERVATION Sheet 331

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE N3(1)

NE562

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER

PG 34 WEST RANDOM BETWEEN SEC 18 & 19

5320.26 INTERSECT RANGE LINE 33' SOUTH POST

LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY
SCATTERING

EAST CORRECTION

SET POST COR 18 & 19

BUR OAK 18 S65E 35.64'; BURR OAK 22 N75E 29.04'

2680.26 SET 1/4 SEC POST BUR OAK 16 S13W 73.92', BUR OAK 16 N18W 34.98'

4696.56 YELLOW OAK 24 IN DIA

5320.26 SEC COR

1834 ORIG GOV PLAT SHOWS NO JOG AT TWP LINE.

1870 RUGER VOL 2 PG 42 FD OLD STAKE ALSO FD WHERE STUMPS OF BEARING
TREES HAD BEEN DUG UP. SET RED SANDSTONE 18X12X6 IT WITH SEVERAL
STONES. VAR 4-56 2748.08 TO NW COR SEC 19, VAR 5-05 2647.04 TO NE COR SEC
19, VAR 5-15 2666.73 TO CENTER SEC 19 & 5321.25 TO S 1/4 COR SEC 19

1871 COLLINS REMONUMENTATION NOTES

WEST BETWEEN 18 & 19 VARIATION 3-50

2652.54 SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING WITH
ROOTS OF WITNESS TREES.

EAST BETWEEN 18 & 19 (NOV 4) VARIATION 3

2750.88 1/4 STONE SET NOV 2

1974 LEE VOL 5 PG 21 FD PIPE OVER CUT STONE MON. REFERENCED SAME

1996 TODD N-3 I FD & ACCEPTED (3) 1": IRON PIPE WITNESS MONUMENTS THAT
WERE PLACED BY HUGH LEE ON OCT 4 1974. I PLACED A R.R. SPIKE AT THE
SECTION CORNER LOCATION. REFERENCED SAME

FD R/R SPIKE. DRILLED HOLE IN CENTER.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal
Donald Barnes

6-29-01

emboss

Number of included sheets 1

CORNER CODE N-3(1)

A-E 7.08 REQUIREMENT