

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 1 E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																								
C		5																							
D			A																						
E																									
F																									
G	7																								
H		8																							
I			9																						
J																									
K																									
L	18																								
M		11																							
N			16																						
O																									
P																									
Q	19																								
R		20																							
S			21																						
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 865

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R3(1)

NE582

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1834 MILLER (MARCH) PG 33 WEST RANDOM BETWEEN SECS 19 & 30

5243.7 INTERSECT RANGE LINE 36.96' SOUTH POST

LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY  
OAK & HAZEL U.G. (UNDER GROWTH)

EAST CORRECTED BETWEEN SEC 19 & 30

SET POST COR OF 19 & 30 BUR OAK 14 IN S27E 32.34'; BUR OAK 14  
IN N37E 79.86

87.12 BUR OAK 15 IN DIA

792 WHITE OAK 15 IN DIA

2593.8 BUR OAK 12 IN DIA

2603.7 SET 1/4 SEC POST BUR OAK N73E 9.9'; BUR OAK 16 S29W 15.18'

2947.56 BUR OAK 18 IN

4979.7 BUR OAK 10 IN

5243.7 SEC COR

1870 RUGER VOL 2 PG 42 FD OLD STAKE & EAST BEARING TREE & WHERE  
STUMP OF S.W. BEARING TREE HAD BEEN DUG UP. SET LIMESTONE  
17X13X14 SURROUNDED IT WITH 6 LIMESTONES. VAR 5-26 2609.31 TO SW  
COR SEC 19, VAR 5-15 2646.6 TO SE COR SEC 19, VAR 5-15 2654.52 TO  
CENTER OF SEC 19 & 5321.25 TO N 1/4 COR SEC 19

1871 COLLIN'S REMONUMENTATION NOTES

EAST BETWEEN 19 & 30 VARIATION 5-20

2608.98 SET 1/4 STONE IN PLACE OF STONE SET BY RUGER AGREEING  
WITH WITNESS TREE.

CONTINUED EAST VARIATION 4-30

5254.26 SECTION CORNER

1953 BATTERMAN B16 PG 2 1329.29 NORTH TO 1/16TH COR & 2652.0 TO NE  
COR SEC 30

1962 BATTERMAN VOL 4 PG 128 FD STONE MON. AT S 1/4 COR &  
REFERENCED SAME.

1977 COMBS CSM 7 PG 100 ANGLE OF 92-48-20 @ NE COR SEC 30 FROM E 1/4  
COR SEC 30 TO N 1/4 COR SEC 30

1993 KREBS CSM 16 PG 234 ANGLE OF 88-59-41 @ NW COR SEC 30 FROM  
NORTH LINE TO WEST LINE SEC 30

1996 HASSE R-3 I FOUND & ACCEPTED (3) 1" IRON PIPE WITNESS  
MONUMENTS THAT WERE PLACED BY R.H. BATTERMAN JR. ON SEP 17,  
1962 I PLACED A R/R SPIKE AT THE SEC COR LOCATION &  
REFERENCED SAME.

FD 1" PIPE IN MON. BOX 0.7' DEEP, 3.5' NORTH CENTER OF PVMT, & ON LINE  
CENTER OF PVMT TO THE NORTH. FD REFERENCE TIES IN R-3

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found  
perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index  
was determined by me under my direction and control and that this U.S. Public Land Survey  
Monument Record is correct and complete to the best of my knowledge and belief.

sdul

SHEET 1 OF 1

Emboss  
Donald Barnes  
7-05-01

CORNER CODE **R-3(1)**

A-E 7.08 REQUIREMENT