

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in the
T. N., R. 13 E

 TURTLE TWP
 ROCK COUNTY WI

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
A																																							
B																																							
C																																							
D																																							
E																																							
F																																							
G																																							
H																																							
I																																							
J																																							
K																																							
L																																							
M																																							
N																																							
O																																							
P																																							
Q																																							
R																																							
S																																							
T																																							
U																																							
V																																							
W																																							
X																																							
Y																																							
Z																																							

IF AVAILABLE
ROCK COUNTY COORDINATES REFERRED


North 210,950.63 Elev.

East 527,932.20

Hor. Datum COUNTY Vert. Datum

GPS (x) TRAVERSE (x) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

(a) CORNER MONUMENT Fd ALUM MON. WITNESS MONUMENT

 Fd TIES IN VOL 5 pg 221

SEARINGS ARE BASED ON:

FIELD BOOK PAGE #

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. THE CORNER MONUMENT SHALL HAVE THE FOLLOWING CHARACTERISTICS: 1) HAVE A LEAST TWO PREDETERMINED BREAK-OFF POINTS. 2) IF BROKEN, LEAVE A PERMANENTLY MAGNETIZED REMNANT AT THE ORIGINAL POINT. 3) MUST BE EXTENDABLE. 4) THE CAP IS INSCRIBED "ROCK COUNTY SURVEY MONUMENT" - PENALTY FOR DISTURBING MARKER. 5) OR AN EXISTING OUT LINES TOLE. AN IRON PIPE (1 1/2" DIA) 4' DEEP MAY BE USED IN AREAS WHERE GROUND WATER IS WITHIN ONE FOOT OF THE SURFACE. IF THE CORNER IS OCCUPIED BY AN IMPROVEMENT (SHAWL/BURIED CABLE, ETC) AND DURABLE, DISTINCT EQUIPMENT MAY BE USED. CORNERS SHALL BE REFERENCED WITH AT LEAST 4 DURABLE WITNESS INSTRUMENTS. WITNESS MONUMENTS SHALL BE MADE OF CONCRETE, BRICK, STONE, IRON OR OTHER EQUALLY DURABLE MATERIAL EXCEPT WOOD. DESCRIBE THE CORNER AND THE WITNESS MONUMENTS.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1992
WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

SHEET OF

CORNER CODE

 P25

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1867 LOCKE VOL 1 PG 283 FOUND STUMPS OF BT SET STAKE 2644.12 VAR 7-08 TO E 1/4 COR SEC 24
- 1867 LOCKE VOL 1 PG 324 FOUND CORNER AS SET BY SELF . SEE SEC 24 2578.62 VAR 6-15 TO S 1/4 COR SEC 19.
- 1869 LEE VOL 1 PG 349 FOUND STAKE & STUMPS OF BT 2657.82 VAR 4-42 TO N 1/4 COR SEC 25 & 2647.92 TO E 1/4 COR SEC 25.
- 1971 LEE VOL 4 PG 516 DUG & FOUND NOTHING.
- 1976 BARNES VOL 5 PG 220 2658.63 TO S 1/4 COR SEC 24.
- 1976 BARNES VOL 5 PG 221 SET THE SW CORNER ON LINE WITH W 1/16TH COR OF SEC 19. THE SW COR WAS SET AT SINGLE PROPORTIONATE FROM THE W 1/16TH COR SEC 19. REFERENCED THE CORNER.
- 1977 BARNES VOL 5 PG 335 2650.09 TO E 1/4 COR SEC 25.
- 1977 BARNES VOL 5 PG 334 FOUND PK & REFERENCE TIES. SET ALUM. MON.
- 1980 BARNES VOL 6 PG 78 FOUND ALUM. MON. ANGLE OF 92-04-48 FROM THE E 1/4 COR TO N 1/4 COR OF SEC 25.

FOUND ALUM MON & TIES IN VOL 5 PG 221. AN ANGLE OF 92-04-22 (REC 92-04-48)

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?
ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, 1994 established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

seal
Donald Barnes
7/10/95

COUNTY SURVEYOR FILING DATA

Date of computer entry _____

Date microfilmed _____

Number of included sheets R25
CORNER CODE

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT