

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2N. R. 14E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

BRADFORD TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											A
B																											B
C																											C
D																											D
E																											E
F																											F
G																											G
H																											H
J																											J
K																											K
L																											L
M																											M
N																											N
O																											O
P																											P
Q																											Q
R																											R
S																											S
T																											T
U																											U
V																											V
W																											W
X																											X
Y																											Y
Z																											Z

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON: -----

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-11(3)

BR526 S1/4CORSEC4

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1874 RUGER VOL 2 PG 142 & MAP #562 VAR 7-25 TO S 1/4 COR SEC 9. FD OLD STAKE. DROVE NEW STAKE IN PLACE OF OLD ONE & PUT ON TOPOF IT HH STONE 18X11X8 SURROUNDED WITH 2 LIME 7 2 HH STONES.
- 1878 RUGER VOL2 PG 246 & MAP #6504 SEE SEC 9 PG 99 2647.92 TO CENTER OF SEC 4 & 5307.06 TO N 1/4 COR SEC 4.
- 1971 COMBS CSM VOL 2 PG 123 THE S 1/4 COR SEC 4 WAS IN CUT AREA OF HIGHWAY. COUNTY SURVEYOR DID NOT DIG FOR IT, THW SW CORNER & SE CORNERS WERE LOCATED BY COUNTY SURVEYOR.
- 1980 BARNES VOL 6 PG 32 FD STAKE. N88-17-06W 2650.13 TO SW COR SEC 4, S88-22-25E 2649.03 TO SE COR SEC 4, 5315.5X TO N 1/4 COR SEC 4.
- 1980 BARNES VOL 6 PG 37 DUG 2.5' DEEP & FOUND WOOD STAKE. TERRAIN AND SOILS INDICATE ROAD WAS CUT & HARD HEAD RUGER SET ON TOP OF STAKE WAS DESTROYED. CALLS FOR CORNER @ CENTER OF PVMT. & ON LINE WITH N/S FENCE TO THE NORTH.
- 1981 WIDOT E-11 ESTABLISHED REFERENCE MONUMENTS & DISTANCES TO PK.
- 1982 BARNES E-11(1) FB #1 PG 20 FD WIDOT TIES. FD 1" PIPE & DROVE DEEP. SET POLY ON TOP OF PIPE.
- 1982 BARNES BRADFORD TWP PROJ. N89-19W 2650.2X TO SW COR SEC 4 & S89-25E 2648.9X TO SE COR SEC 4
- 1990 SCHROEDER CSM VOL 14 PG 453 STATES NOTHING ABOUT MON. WESTERLY 983.00 ALONG SEC LINE TO POB OF CSM.
- 1994 WIDOT E-11(2) NAD83(91) 240,589.72; 2,279,076.88 CONVERT 258,748.60; 540,995.04 CALLS FOR ALUM.

CONTACTED AFTER PVMT WAS MILLED. FD POLY WITH TOP MILLED OFF. PLACED 2 MAGNETS ON TOP OF POLY, WHICH WAS PAVED OVER. INSTALLED STEEL SURVEY MONUMENT SPIKE AFTER FINAL MATT WAS INSTALLED. STEEL SURVEY SPIKE IS 3" LONG, 3/8" DIAMETER, & TOP IS 1" IN DIAMETER AND STAMPED "SURVEY MARKER". SUB-BASE MONUMENT IS STILL IN. RECORD TIES CHECKED VERY WELL.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

THE INTERSECTION OF THE RECORD TIE DISTANCES WAS USED TO ESTABLISH THE POSITION. THE POLY MON. WAS PROBABLY DISTURBED BY THE MILLING OPERATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

SHEET 1 OF 2

Emboss  
*Donald Barnes*  
9/22/08

CORNER CODE **E-11(3)**

A.E. 7.08 REQUIREMENT

EMBOSSED SEAL

SHEET 2 OF 2

E-11(3)

*Donald Barnes*  
8/22/08

N 1/4 COR  
SEC 9  
BRADFORD TWP  
T2N R14E

