

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N., R. 11 E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6																							
C		5																						
D			A																					
E				3																				
F					2																			
G	1																							
H		8																						
J			9																					
K				10																				
L	18																							
M		11																						
N			16																					
O				15																				
P					14																			
Q	19																							
R		20																						
S			21																					
T				22																				
U					23																			
V						24																		
W							25																	
X								26																
Y									27															
Z										28														
											29													
												30												
													31											
														32										
															33									
																34								
																	35							
																		36						

PLYMOUTH TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A-21 (2)

PL511

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT WEST ON SOUTH SIDE SECTIONS 34 & 35 {35}
- 1518 LEAVE PRAIRIE TO ENTER MARSH
 - 2442 STREAM 6.6' C SOUTH
 - 2508 LEAVE MARSH AND ENTER PRAIRIE
- SET QUARTER SECTION POST IN PRAIRIE AND MADE MOUND
- 5280 SET POST CORNERS SECTIONS 34 & 35 IN PRAIRIE AND MADE MOUND. LAND ROLLING PRAIRIE SECOND RATE. BY OBSERVATION VAR 7-45E
NORTH BETWEEN SECS 1 & 2
- 2640 QUARTER SEC COR {BURR O 12 N71E 148.5' BURR O 24 S47W 48.84' BURR O 12 BURR O 24} MARKED
- 5240.4 INT. N BDG 3.3' W OF P {BURR O. 24 S41E 316.8' BURR O. 14 S45W 293.7 LAND HIGH & ROLLING 2ND RATE BUR & BLACK O. TIMBER FRIDAY DEC 20TH 1833
- 1833 MULLETT VAR 7-55 WEST ON SOUTH SIDE OF SECTION 36 T3N R11E
- 2640 SET QUARTER SECTION POST IN PRAIRIE AND MADE MOUND
 - 5280 SET POST CORNER SECTIONS 35 & 36 BUR OAK 10 N70E 411.84' BUR OAK 8 N64 1/2 W 557.7' LAND ROLLING SECOND RATE PRAIRIE.
- 1833 HARRISON NORTH BETWEEN SECS 1 & 2
- 2640 QUARTER SEC COR {BURR O 12 N71E 148.5' BURR O 24 S47W 48.84' BURR O 12 BURR O 24} MARKED
 - 5240.4 INT. N BDG 3.3' W OF P {BURR O. 24 S41E 316.8' BURR O. 14 S45W 293.7 LAND HIGH & ? 2ND RATE BUR & BLACK O. TIMBER FRIDAY DEC 20TH 1833
- 1845 TWP RD RECORDS BK 1 PG 5 BEGINNING AT THE NW COR OF SEC 1 AND RUNNING SOUTH ON THE LINE BETWEEN SEC 1 & 2 IN SAID TWP 2602.38' TO THE QUARTER POST ON THE WEST SIDE OF SEC 1 AFORESAID; THENCE SOUTH ON THE LINE AFOREMENTIONED TO THE SW COR OF SAID SEC 1 IN ALL 5242.38'? ((7) 49 CH & 43 LKS)
- 1846 TWP RD REC BK 1 PG 14 BEGINNING AT THE 1/4 POST ON WESTSIDE OF SEC 12 T2N R11E AND RUNNING NORTH 2640 ON THE WEST SIDE OF SAID SEC 12; THENCE NORTH 5240.4' ON THE WEST SIDE OF SEC 1 IN SAME TOWN AND RANGE; THENCE NORTH 5280 ON THE WEST SIDE OF SEC 36, T3N OF RANGE 11 EAST. SAID RD IS 66' IN WIDTH. VARIATION OF NEEDLE 8 E.
- 1868 LOCKE REMONUMENTATION NOTES.
- PG 35 SOUTH BETWEEN SECS 1 & 2 VAR 7-10
- 2621.52 INTERSECTED 1/4 LINE AT COR. FOUND SOUTH BT AND STAKE & STONE SET ON CORNER. COR IN CENTER OF HIGHWAY AND IN LINE OF E & W FENCE.
CONTINUED SOUTH WITH VAR 7-25
 - 5285.28 INTERSECTED SOUTH BOUNDARY 2.97' EAST OF COR. VAR CORRECTED 7-21 AUG 27 1868
PG 34 WEST ON NORTH LINE SECTION 1.
 - 2668.38 INTERSECTED 1/4 LINE FOR TOWN 3 (CENTER) 1.98' SOUTH OF COR. FOUND LARGE LIMESTONE IN CENTER OF HIGHWAY AND IN LINE OF N AND S FENCES.
 - 5334.12 INTERSECTED WEST BOUNDARY 14.52' SOUTH OF COR. FOUND BT IN SEC 2

SHEET 1 OF 3 CORNER CODE A-21(2)

David Barnes
6-17-03

- PL511
- 5330.82 INTERSECTED COR FOR TOWN 3 FOUND BT IN SEC 35 AND STUMP OF BT IN SEC 36. COR IN CENTER OF HIGHWAY.
- 2667.06 SET $\frac{1}{4}$ COR 1.32' EAST OF $\frac{1}{4}$ COR FOR TOWN 3 FOR FIRST HALF MILE VAR CORRECTED 6-58, FOR LAST HALF MILE VAR CORRECTED 7-11 $\frac{1}{4}$ MONUMENT MARKED WITH FIGURE 1 ON SOUTH FACE AUG 27, 1868
- PG 38 EAST ON NORTH LINE SEC 2 VAR 5-45
- 505.56 CENTER SLUICE BRIDGE
- 2657.49 INTERSECTED $\frac{1}{4}$ LINE FOR TOWN 3 7.26' NORTH OF COR. FOUND STONE WITH STAKE SET BY ANDREW CODDINGTON IN OLD MOUND. COR. IN CENTER OF HIGHWAY AND IN LINE OF FENCE RUNNING N. VAR CORRECTED 5-36
CONTINUED EAST FROM $\frac{1}{4}$ COR OF T3 WITH VAR 7-12
- 3034.02 CENTER OF BRIDGE 33' WIDE OVER CREEK.
- 5313.66 INTERSECTED EAST BOUNDARY AT COR.
- 5316.96 INTERSECTED EAST BOUNDARY OF SEC 35 T3N AT COR.
- 2656.83 SET $\frac{1}{4}$ COR 0.66' WEST OF $\frac{1}{4}$ COR FOR T3N $\frac{1}{4}$ MONUMENT MARKED WITH FIG 2 ON SOUTH FACE. AUG 28, 1868
- 1877 RUGER VOL 2 PG 234 FOUND STONE MONUMENT. CALLS FOR 2652.54' TO N $\frac{1}{4}$ CORNER OF SECTION 2 AND 2616.89' TO EAST QUARTER CORNER OF SECTION 2.
- 1933 SUNNY VOL 3 PG 234 & 235 SET 1X30" LONG PIPE IN CONCRETE PAVEMENT, 2.4' NORTH OF CENTER OF SAME. CALLS FOR 2667.2' TO N $\frac{1}{4}$ CORNER OF SECTION 1 AND 2621.6 TO W $\frac{1}{4}$ CORNER OF SECTION 1.
- 1962 BATTERMAN JR. VOL 4 PG 142 FOUND 1" PIPE UNDER BLACKTOP AND REFERENCED SAME.
- 1975 COMBS CSM 5-169 FD PIPE
- 1977 BARNES VOL 5 PG 362 FOUND A PK AS RECORDED AS THE NE CORNER OF SECTION 2 T2N R11E PLYMOUTH IN VOL 4 PG 142 & VOL 5 PG 140. IT IS ERRONEOUS. DUG AND FOUND 1" PIPE 0.3' DEEP. IT AGREED WITH THE DISTANCE TO THE N $\frac{1}{4}$ CORNER OF SECTION 2 AS RECORDED IN VOL 3 PG 235. SET ALUMINUM MONUMENT. DUG AND FOUND NOTHING AT SE CORNER OF SECTION 35. SET ALUM MONUMENT AT RECORD DISTANCE FROM NE CORNER OF SEC 2 AS RECORDED IN VOL 3 PG 235. CALLS FOR 2656.86 TO N $\frac{1}{4}$ CORNER OF SECTION 2.
- 1979 NORTHROP MAP #809 BERNTSEN ALUM. MON. OF REC. WEST OF SE COR SEC 35. 2660.25 FROM SE COR SEC 35 TO E $\frac{1}{4}$ COR SEC 35.
- 1988 BARNES VOL 6 PG 388 & 389 CALLS FOR RECORD DISTANCES AND CALLS FOR N89-14-40E 2654.68 TO N $\frac{1}{4}$ COR SEC 2, S0-41-45E 2621.72 TO E $\frac{1}{4}$ COR SEC 2, S89-56-08E 2667.20 TO N $\frac{1}{4}$ COR SEC 1, AND N1-01-11W 2660.68 TO THE E $\frac{1}{4}$ CORNER OF SECTION 35. FOUND DOT DISK.
- 1988 BARNES Z-21(CENTER TWP) SE COR SEC 35 USING DOT CONTROL N/S 246,046.57; E/W 2,228,589.77 ALUM. MON SEE OLD TIE SHEET.
- 1989 WIDOT PROJ. MAP #16692 #1704-03-22 ALUM 246,128.43; N88-48-56E 3.29 TO SE COR SEC 35 CENTER TWP. ALUM AT SE COR SEC 35 CENTER TWP (246,128.50; 2,228,589.06). CI AT E $\frac{1}{4}$ COR SEC 33 (248,788-70; 2,228,541.64)
- 1992 BARNES A-21 MONUMENT WILL BE DESTROYED BY ROAD CONSTRUCTION. DISTANCE & BEARINGS TO OLD REFERENCE MONUMENTS & NEW DOT REFERENCE MONUMENTS. N88-04-47E 3.28' TO SE COR SEC 35 CENTER TWP.

SHEET 2 OF 3 CORNER CODE A-21(2)

Donald Barnes
6-17-03

PL511

1992 BARNES A-21(1) Z-21(1) FOUND DOT DISK & ACCEPTED IT. REFERENCED SAME. 3.34' (REC 3.28') BETWEEN NE COR SEC 2 & SE COR SEC 35.

1993 COMBS MAP #10329 ALUM. MON

2000 COMBS A-19(4) FD DOT DISK NB3-58-10W 13.25 FROM SET PK NAIL. THIS DISK DID NOT CHECK D.O.T. RIGHT OF WAY MAP DISTANCES EAST-WEST FOR SECTION CORNER LOCATION. DISK DID NOT CHECK D. BARNES PREVIOUSLY MEASURED DISTANCES EAST-WEST. NB9-14-40E 2657.74 TO DOT DISK @ SE COR SEC 35, SB9-20-22E 2659.14 TO DOT DISK @ SW COR SEC 35, 0.66' EAST OF N 1/4 COR SEC 3, AND STATEMENT "PRORATED DISTANCES USING DON BARNES ANGLE. D. BARNES ANGLE @ S 1/4 COR SEC 35 FROM SW TO SE COR SEC 34 IS 178-35-02. REFERENCED SAME. FD DOT DISK NB3-58-10W 13.25 & SET IRON REBAR FOR REF. MONUMENTS. SET PK MASONRY NAIL AT S 1/4 COR SEC 35.

2000 COMBS CSM 24-55 FD DOT DISK. 2658.48 TO S 1/4 COR SEC 35 CENTER TWP

2001 COMBS CSM VOL 24 PG 186 DOT MON. 2654.36 TO PK AT S 1/4 COR SEC 35

2001 LATHROP CSM VOL 25 PG 164 DISK. 2621.95 TO W 1/4 COR SEC 1.

USED MY 1992 OBSERVATIONS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED DOT DISK & REFERENCE MONUMENTS

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal


Emboss

6-17-03

SHEET 3 OF 3

CORNER CODE **A-21(2)**
A-E 7.08 REQUIREMENT