

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2N., R. 11E

### CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6					5					4			3							2			1
C																								
D																								
E																								
F																								
G	1					8					9			10						11			12	
H																								
I																								
J																								
K																								
L	18					17					16			15						14			13	
M																								
N																								
O																								
P	19					20					21			22						23			24	
Q																								
R																								
S																								
T	30					29					28			27						26			25	
U																								
V																								
W																								
X	31					32					33			34						35			36	
Y																								
Z																								

PLYMOUTH TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEETS 185, 425, 426, 493, 627, 4507

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE Z-13(1)

PL627

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLET WEST ON SOUTH SIDE SECTION 33  
2640 SET QUARTER SECTION POST IN PRAIRIE AND MOUND OF EARTH AND SODS  
3102 INDIAN PATH CS S.E.  
5280 SET POST CORNER SECTIONS 32 & 33 MADE A MOUND OF EARTH AND SODS LAND ROLLING SECOND RATE DRY PRAIRIE  
WEST ON SOUTH SIDE SECTION 34  
2640 SET QUARTER SECTION POST WHITE OAK 16 N29E 155.76'  
BUR OAK ; BUR OAK 12 N60 1/2W 167.64';  
3960 ENTER PRAIRIE  
5280 SET POST CORNER SECTIONS 33 & 34 MADE A MOUND OF STONES 3 FEET IN DIAMETER AT BASE & 3 FEET HIGH FIRST 3/4 THINLY TIMBERED WITH BLACK WHITE AND BUR OAK THICK UNDERGROWTH HAZEL BRIERS GRAPE VINES & LAST 1/4 RICH DRY PRAIRIE.
- 1833 HARRISON NORTH BETWEEN SECS 33 & 34 T2N R11E  
1188 LEFT PRAIRIE & ENTER TIMBER  
1683 WHITE OAK 26  
2268.42 WHITE OAK 18  
2640 QUARTER SEC COR. BLK O 24 N35E 48.18'; WHITE OAK 16 S21E 31.02  
4066.26 BLK O 36  
5181.66 BLK O 28  
5280 COR TO SEC 27,28,33,34 WHITE OAK 24 S35E 114.18'; LYM? 24 N78E 86.46'; RED O 30 N46W 45.54'; W.O. 34 S31W 75.9'; LAND ? 1ST RATE TO TIMB. BLK & W.O. ASPEN  
HICKORY. ? & LITTLE OR NO UNDERGROWTH
- 1834 MILLER MARCH 10  
NORTH BETWEEN SECS 3 & 4 T1N R11E  
2319.9 TRAIL CRS N.W.  
2640 SET 1/4 SECS POST IN MOUND OF EARTH AND SOD  
5283.3 INTERSECT N. BOUNDARY. 33.66' EAST OF POST. SET POST IN MOUND OF STONE. COR OF SEC 3 & 4. LAND ROLLING 2ND RATE.
- 1853 LOCK TWP ROAD RECORDS BK 1 PG 30 THIS DAY SURVEYED BY THE DIRECTION OF THE SUPERVISORS OF THE TOWN OF PLYMOUTH THE FOLLOWING DESCRIBED RD TO WIT: BEGINNING AT THE NE COR OF SEC 33 THENCE RUNNING SOUTH ONE MILE ON SEC LINE BETWEEN SECTIONS 33 & 34 TO THE TERMINATION OF SAID RD ON TOWN LINE. THE SAID COURSES AND DISTANCES ARE THE CENTER OF THE RD. VARIATION OF THE MAGNETIC NEEDLE 7 1/2 EAST
- 1868 LOCKE PLYMOUTH TWP REMONUMENTATION AUG 21 1868  
PG 16 WEST ON SOUTH LINE SEC 34 VAR 6  
264 SET OFF 3.3' SOUTH  
528 SET OFF 6.6' SOUTH  
1122 SET OFF 1.32' SOUTH  
1518 SET OFF 1.65' SOUTH  
2673 INTERSECTED 1/4 LINE 14.52' SOUTH OF COR. FOUND BTS AND OLD STAKE. VAR CORRECTED 5-58  
CONTINUED WEST FROM 1/4 COR WITH VAR 6-22  
3762 ENTER PRAIRIE  
5339.4 INTERSECTED WEST BOUNDARY 30.36' SOUTH OF COR. FOUND LARGE LIMESTONE SET FOR CORNER. COR IN CENTER HIGHWAYS RUNNING N.E. & W SET MONUMENT IN MOUND OF STONES COVERED WITH EARTH. VAR CORRECTED 5-43 1/4 MONUMENT MARKED 34 ON NORTH FACE.  
PG 17 NORTH BETWEEN SEC 33 & 34 VAR 7 AUG 21 1868  
2655.18 INTERSECTED 1/4 LINE .66' EAST OF COR. FOUND STUMPS OF BTS AND STAKE UNDER STONE ON CORNER. THE DISTANCE & COURSE OF EACH BT GIVEN FOR THE
- SHEET 1 OF 3 CORNER CODE Z-13(1)

2/14/03  
Donald Barnes

PL627

OTHER RIGHT WHEN EXCHANGED. COR IN CENTER OF HIGHWAY & IN LINE OF E & W FENCE. VAR CORRECTED 7-01.

*CONTINUED NORTH FROM 1/4 COR WITH VAR 7*

3118.5 BROOK 3.96' WIDE COURSE SW  
5318.28 INTERSECTED NORTH BOUNDARY 3.3' E OF COR.  
VAR CORRECTED 7-04.  
PG 69 WEST ON SOUTH LINE SEC 33 VAR 6-20 SEPT 11 1868  
1214.4 CENTER SLUICE BRIDGE 4.62' WIDE  
1712.04 CENTER SLUICE BRIDGE 3.96'  
2668.71 INTERSECTED 1/4 LINE AT COR. FOUND OLD STAKE IN CENTER OF HIGHWAY AND IN LINE WITH FENCE RUNNING NORTH. SURROUNDED MONUMENT BY HEAP OF LIMESTONES.

*CONTINUED WEST WITH VAR 6-20*

2705.34 CENTER OF SOUTH END OF BRIDGE  
5340.39 INTERSECTED WEST BOUNDARY 12.87' SOUTH OF OCR.  
VAR. CORRECTED 6-04' 1/4 MONUMENT MARKED 33 ON ITS NORTH FACE.

1871 COLLINS REMONUMENTATION NEWARK TWP T1N R11E

PG 172 *NORTH BETWEEN 3 & 4 VARIATION 6-30*

2682.9 SET 1/4 STONE IN LINE WITH FENCES EAST & WEST.  
CONTINUED NORTH VARIATION 6-25

5134.8 SET STONE FOR CORNER OF 3 & 4 33.66' EAST OF PLYMOUTH CORNER.

PG 173 *EAST ON NORTH LINE OF SEC 3. VARIATION 5-50*

5280 SECTION CORNER

*BACK TO*

2640 SET 1/4 STONE 1.98' EAST OF PLYMOUTH CORNER.  
OCT 26, 1871

PG 212 *EAST ON NORTH LINE OF 4 VARIATION 5-40*

5334.12 SECTION CORNER

*BACK TO*

2667.06 SET 1/4 STONE 31.02' EAST OF PLYMOUTH 1/4 CORNER. NOV 6TH 1871

1871 RUGER VOL 2 PG 75 FD STONE MON. SE COR SEC 33 TO E 1/4 COR SEC 33 2650.06' VAR 6-15 & 2667.89 VAR 5-25 SE COR SEC 33 TO S 1/4 COR SEC 33.

1873 RUGER VOL 2 PG 117 STONE MON. AT NW COR SEC 3 & SE COR SEC 33.66' EAST OF PLYMOUTH COR.

1882 RUGER VOL 2 PG 403 2632.74 NW TO N 1/4 COR SEC 3, 2488.86 NW TO W 1/4 COR SEC 3.

1882 HOLMES VOL 2 PG 349 CALLS FOR MON. 2487.21 TO W 1/4 COR SEC 3

1957 BATTERMAN VOL 3 PG 520 33.66 BETWEEN CORNERS. NEWARK IS EAST OF PLYMOUTH. 2640.72 SE 33 TO N 1/4 COR 4.

1967 BATTERMAN VOL 4 PG 317 FD CUT L.S. AT SE COR SEC 33 & NE COR SEC 4. 33.45 BETWEEN CORNERS. REFERENCED SAME

1976 BARNES VOL 5 PG 203 33.46 BETWEEN CORNERS. REFERENCED SAME.

1978 BARNES VOL 5 PG 473 33.45 BETWEEN CORNERS. FROM SE COR SEC 33 N89-02-54W 2640.64 SE 33 TO N 1/4 COR SEC 4, NO-00-02W 2655.96 SEC 33 TO E 1/4 COR SEC 33, & 2670.88 SE 33 TO S 1/4 COR SEC 33.

1978 BARNES VOL 5 PG 481 SE COR SEC 33 FD PK & 6" DEEP FOUND CUT L.S. SET 6" ALUM. MON. AT NE COR SEC 4 FD PK & 18" DEEP FD CUT L.S. SET 18" ALUM. MON.

1989 COMBS #12293 FD ALUM

2001 BARNES Z-13 FD ALUM. MON @ CENTER OF E/W PAVEMENT CENTER LINE.

SHEET 2 OF 3 CORNER CODE Z-13(1)

2/14/03

Donald Barnes

PL627

FD ALUM. MON., WHICH THE TOP WAS LOOSE. ALSO FD THE REF. MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND ALUM. MON., WHICH PERPETUATES THE CUT L.S. LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal  
Donald Barnes  
Emboss  
2/14/03

SHEET 3 OF 3

CORNER CODE Z-13(1)

A-E 7.08 REQUIREMENT