

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N., R. 11 E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	7	8	9	10	11	12																			
H																									
J																									
K	18	17	16	15	14	13																			
L																									
M																									
N																									
O	19	20	21	22	23	24																			
P																									
Q																									
R																									
S	30	29	28	27	26	25																			
T																									
U																									
V																									
W																									
X	31	32	33	34	35	36																			
Y																									
Z																									

PLYMOUTH TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  $\blacklozenge$  AT PROPER LOCATION ON ABOVE INDEX

$\blacklozenge$  CORNER MONUMENT

$\circ$  WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

W<sup>1</sup>/<sub>4</sub> 19 TIES

N 0-49-31 W  
2634.11

N 63-11-33 E  
5293.83

PIN  
E 1/4  
19

NW 30

EAST 2660.34 30

LS  
N<sup>1</sup>/<sub>4</sub>

S 0-44-15 E  
2636.56

W<sup>1</sup>/<sub>4</sub>  
30

1 1/2" capped  
PIPE

OBSERVATION SHEET 123

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R-1(1)

PL581

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT. NORTH ON EAST SIDE SECTION 25 T2N R10E  
2508 ENTER PRAIRIE

2640 SET QUARTER SECTION POST MADE A MOUND OF  
EARTH & SOD & C

5280 SET POST CORNER SECTIONS 24 & 25 IN PRAIRIE  
MADE A MOUND OF EARTH & SOD. LAND  
ROLLING. SECOND RATE B W & BUR OAK. LAST HALF  
DRY PRAIRIE RED ROOT ROSE WILLOW GRASS.

NORTH ON EAST SIDE SECTION 24 T2N R10E

2640 SET QUARTER SECTION POST MADE MOUND OF EARTH  
& SOD & C(?)

5280 SET POST CORNER SECTIONS 13 & 24 IN PRAIRIE &  
MADE MOUND & C(?) LAND ROLLING SECOND RATE  
DRY PRAIRIE

1833 HARRISON WEST ON RAND BET 19 & 30

1650 BROOK CRS 5.28' N.W.

2640 TEMPY 1/4 SEC COR.

5276.7 INT. W. BDG AT POST & ESTABLISHED COR TO SEC  
19 & 30. BEARINGS {'BLANK' LAND & SAME  
COR EAST

2636.7 QUARTER SEC COR ON GROUND DESCENDING N.W.  
SET POST & RAISED MOUND

5276.7 SEC

1833 HARRISON ORIG PLAT SW TO SE SEC 24 5285.28

1834 MILLER EAST RANDOM BETWEEN SECS 24 & 25 T2N R10E

4197.6 ENTER PRAIRIE [MAYBE 4210.8']

5285.28 INTERSECT RANGE LINE 10.05' N OR P. LAND 2<sup>ND</sup>  
RATE ROLLING TIMBER OAK

WEST CORRECTION BETWEEN SECS 24-25

2642.64 SET 1/4 SC POST W.O. 24 S9W 86.46' W.O. 25 N53E  
155.1'

5285.28 SEC COR.

1854 McVEAN VOL 1 PG 22 CALLS FOR 2626.14 TO THE WEST  
QUARTER CORNER OF SECTION 19 AND 2647.92 TO THE  
SOUTH QUARTER CORNER OF SECTION 19. STATES  
NOTHING ABOUT THE CORNER.

1868 LOCKE PG 64 NORTH ON WEST LINE SEC 30 VAR 7-30

0 SET OFF 3.63' EAST

1987.26 CENTER OF BRIDGE 6.6' WIDE

2517.24 CENTER OF BRIDGE 5.28' WIDE

2617.56 INTERSECTED 1/4 LINE 2.97' EAST OF COR. FOUND  
LARGE LIMESTONE AND UNDERNEATH AN OLD  
STAKE. SET IN HIGHWAY IN LINE OF E & W FENCES  
AND 27.72' EAST OF COR. POST TO WEST FENCE.  
VAR CORRECTED 7-29

CONTINUED NORTH FROM 1/4 COR WITH VAR 7-30

3366 SET OFF 14.52' EAST

5251.95 INTERSECTED NORTH BOUNDARY 4.95' EAST FOUND  
WHERE OLD STAKE WAS PULLED OUT AND  
STRONGLY MARKED INDICATIONS OF PIT 4 FT S.E.  
COR IN CENTER OF HIGHWAY & IN LINE WITH FENCE  
FUNNING WEST AND NEARLY IN LINE WITH FENCE  
RUNNING EAST. VAR CORRECTED 7-17 SEPT 10  
1868

PG 65 NORTH ON WEST LINE SEC 19 VAR 7-05

2632.08 INTERSECTED 1/4 LINE 3.3' EAST OF COR. FOUND  
COR. AS SET BY SELF. (SEE CO SURVEYOR RECORD  
SEC 24 SPRING VALLEY) IN CENTER OF HIGHWAY  
AND IN LINE OF E & W FENCES. VAR. CORRECTED 7-  
09 SEPT 10, 1868

Donald E. Curran  
12-27-02

PL5B1

PG 65  
CONTINUED NORTH FROM 1/4 COR WITH VAR 7-05  
5252.61 INTERSECTED NORTH BOUNDARY 13.86' EAST OF  
COR. FOUND OLD STAKE IN COR OF RAIL FENCE  
RUNNING N & S. VAR CORRECTED 7-23 SEPT  
PG 75 WEST BETWEEN SECS 19 AND 30 VAR 6-22  
1651.98 BOTTOM OF RAVINE  
2655.18 INTERSECTED 1/4 LINE 5.61' NORTH OF COR.  
FOUND OLD STAKE 1 FT NORTH OF FENCE POST IN  
E & W FENCE VAR CORRECTED 6-29  
CONTINUED WEST FROM 1/4 COR WITH VAR 6-22  
5316.3 INTERSECTED WEST BOUNDARY 3.96' NORTH OF  
COR. VAR CORRECTED 6-27 SEPT 15 1868  
1937 SUNNY VOL 3 PG 356 FOUND BUT LIMESTONE 10" LOW. SET  
1 1/2 PIPE WITH CAP ON TOP FLUSH WITH BLACKTOP.  
1992 BARNES R-1 FOUND CAPPED PIPE. 1.7 WEST OF CENTER OF  
PAVEMENT. REFERENCED SAME. 22' SOUTH OF E/W CENTER  
OF PVMT.  
1992 BARNES VOL 6 PG 430 CAPPED PIPE 2660.30 TO S 1/4 COR  
SEC 19.

FD CAPPED PIPE 1.7' WEST OF CENTER OF GTH K PVMT & 22' SOUTH  
OF CENTER OF RINGEN RD PVMT.

*C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?*

ACCEPTED FD CAPPED PIPE, WHICH PERPETUATES THE CUT  
LIMESTONE. 1992 TIES STILL EXIST.

*D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.*

*(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.*

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

*Donald Barnes*

SHEET 2 OF 2

Emboss

*12-27-02*

CORNER CODE

**R-1(1)**

A-E 7.08 REQUIREMENT