

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 12 E. 4th P.M.
CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|
| A | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | A |
| B | | | | | | | | | | | | | | | | | | | | | | | | | | B |
| C | | | | | | | | | | | | | | | | | | | | | | | | | | C |
| D | | | | | | | | | | | | | | | | | | | | | | | | | | D |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | E |
| F | | | | | | | | | | | | | | | | | | | | | | | | | | F |
| G | | | | | | | | | | | | | | | | | | | | | | | | | | G |
| H | | | | | | | | | | | | | | | | | | | | | | | | | | H |
| J | | | | | | | | | | | | | | | | | | | | | | | | | | J |
| K | | | | | | | | | | | | | | | | | | | | | | | | | | K |
| L | | | | | | | | | | | | | | | | | | | | | | | | | | L |
| M | | | | | | | | | | | | | | | | | | | | | | | | | | M |
| N | | | | | | | | | | | | | | | | | | | | | | | | | | N |
| O | | | | | | | | | | | | | | | | | | | | | | | | | | O |
| P | | | | | | | | | | | | | | | | | | | | | | | | | | P |
| Q | | | | | | | | | | | | | | | | | | | | | | | | | | Q |
| R | | | | | | | | | | | | | | | | | | | | | | | | | | R |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | S |
| T | | | | | | | | | | | | | | | | | | | | | | | | | | T |
| U | | | | | | | | | | | | | | | | | | | | | | | | | | U |
| V | | | | | | | | | | | | | | | | | | | | | | | | | | V |
| W | | | | | | | | | | | | | | | | | | | | | | | | | | W |
| X | | | | | | | | | | | | | | | | | | | | | | | | | | X |
| Y | | | | | | | | | | | | | | | | | | | | | | | | | | Y |
| Z | | | | | | | | | | | | | | | | | | | | | | | | | | Z |

FULTON TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT ○ WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____ SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-3 (3)

FU522

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 (APR 4) HARRISON WEST ON RAND. BET SECS 6 & 7
2640 TEMPY 1/4 SEC COR.
5316.3 INT. W. BDY 29.7' N OF P LAND ROLLING 2ND RATE TIMBER
ALL BURR O. UNDERGROWTH ? GRASS & WEEDS
COR. EAST
2676.3 QUARTER SEC COR. {BURR O 12 S80W 26.4' RED O. 10'
N54E 76.56' BURR O 12, RED O 20} MARKED
4579.74 BURR O 12 IN DIAMETER
5316.3 SEC COR.
- 1847 TWP RD REC BK 1 PG 10 ALSO A RD, THE CENTER LINE OF WHICH IS DESCRIBED AS FOLLOWS TO WIT: PLACE OF BEGINNING IS THE QUARTER SECTION POST BETWEEN SECTION 5 & 8 IN T4N R12E FROM SAID POST RUN ON SECTION LINE S81-15W 957' THENCE S54W 858', THENCE N83-45W 1130.58' TO SEC COR (NW COR SEC 8) THEN ON SECTION LINE BETWEEN 6 & 7 S81-15W 5315.64' TO THE TOWN LINE, MAKING 8261.22'. IN WITNESS WHEREOF WE HAVE HEREUNTO SET OUR HANDS AT FULTON ON THE 12 DAY OF OCT. 1847 GOODRICH, PHILIP & DAVOLT MARK COMMISSIONER OF HIGHWAYS.
- 1847 PIERCE TWP RD BK 1 PG 10 SURVEYED JUNE 2ND 1847 A RD THE CENTER LINE OF WHICH IS DESCRIBED AS FOLLOWS TO WIT; PLACE OF BEGINNING IS THE 1/4 SEC POST BETWEEN SEC 5 & 8 IN T4 OF R12 FROM SAID POST, RUN ON SEC. LINE S81-15W 957.00' THEN S54W 858' THEN N83-45W 1130.58' TO SEC COR (NW COR SEC 8), THE ON SEC LINE BETWEEN 6 & 7 S81-15W 5315.64 TO THE TOWN LINE MAKING 8,261.22'.
- 1865 LOCKE VOL 1 PG 226 & 1065 FOUND STUMPS OF B.T. & OLD STAKE. 2660.12 TO CENTER OF SEC 6 & 5315.8 TO N 1/4 COR SEC 6.
- 1871 RUGER VOL 2 PG 79 & 1069 FOUND OLD STAKE & WHERE STUMPS OF B.T. HAD BEEN DUG UP. DROVE STAKE DEEP & PUT ON TOP OF IT LIMESTONE 22X6X4 SURROUNDED IT WITH 4 HH. VAR 7-25 2672.34 TO SW COR SEC 6, VAR 6-35 2671.68 TO SE COR SEC 6, & VAR 7-28 ALONG N/S CENTER LINE OF SEC 7.
- 1876 RUGER #1069 VAR 7-27 TO NW COR SEC 7, VAR 6-37 TO SE COR SEC 6. OTHER INFORMATION IN VOL 2 PG 79 IS THE SAME
- 1968 BATTERMAN VOL 4 PG 357 SET 1" PIPE IN BLACK TOP. REFERENCED SAME. CALLS WPL 1974 COORDINATES
- 1974 WPL #1063 COORDINATES OF 304,668.74 ~~384,669.27;~~
~~2,235,576.36~~ 2,235,576.69 N88-51-20E 2678.02 N88-52-02E
~~2678.34~~ TO SE COR SEC 6
- 1978 BARNES VOL 5 PG 483 FD PK & 0.1' DEEP FD 1" PIPE 0.11' NORTH OF PK. REPLACED 1" PIPE WITH ALUM. MON. REFERENCED SAME.
- 1983 BARNES VOL 6 PG 303 CALLS FOR WPL COORDINATES OF 304,669.27; 2,235,576.36 & WPL N88-52-02E 2678.34 TO SE COR SEC 6.
- 1991 BARNES E-3 FD ALUM. MON. 3' NORTH OF CENTER OF PVMT REFERENCED SAME. INT. OF STH 59 & BUBLITZ RD.
- 1992 NORTHROP CSM VOL 15 PG 475 2679.03 TO NW COR SEC 7 & ANGLE 89-50-36 @ N 1/4 COR SEC 7 FROM S 1/4 COR SEC 7 TO NW COR SEC 7
- 1993 LEUNBERGER CSM VOL 16 PG 356 FD SMALL SQ PIN. 5300.41 TO N 1/4 COR SEC 6
- 1994 NORTHROP #9491 5300.54' FROM S 1/4 COR SEC 6 TO N 1/4 COR SEC 6, 2679.03 TO SW COR SEC 6, ANGLE OF 91-10-35 @ S 1/4 COR SEC 6 FROM SW TO N 1/4 COR SEC 6. ALUM MON IS GONE POSITION OF CORNER IS A 1/4" SQ. IRON PIN 12" BELOW SURFACE AGREEING WITH TIES.

SHEET 1 OF 3
CORNER CODE E-3(3)

Donald Barnes
May 15 2006

FU522

1998 SCHROEDER CSM VOL 21 PG 464 STATES NOTHING ABOUT THE TYPE OF MON. 1339.17 TO S 1/16TH COR OF SE 1/4 SEC 6

1999 BARNES E-3(1) FD ALUM. MON. 0.7' DEEP WITH TOP BROKE OF 0.03' NORTH OF E/W CENTER PVMT, 6' WEST OF N/S CENTER OF PVMT. SHOWS WPL GPS CONTROL WITH COUNTY SYSTEM & ANGLE/DISTANCE TO COR. FROM GPS CONTROL.

1999 BARNES E-3(2) SAME AS ABOVE BUT SET MORE TIES.

2000 NORTHROP CSM VOL 24 PG 45&87 ALUM. 2679.02 TO NW COR SEC 7 & ANGLE 89-50-36 @ N 1/4 COR SEC 7 FROM S 1/4 COR SEC 7 TO NW COR SEC 7, 5325.47 TO S 1/4 COR SEC 7

FD ALUM. MON & REFERENCE TIES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

IN 1978, 1 FD A PK & 0.1' DEEP FD A 1" PIPE 0.11' NORTH OF THE PK & REFERENCED SAME.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald Barnes

May 15 2006

Emboss

SHEET 2 OF 3

CORNER CODE **E-3(3)**

A-E 7.08 REQUIREMENT

