

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N., R. 11 E

CORNER CODE INDEX

PLYMOUTH TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

| | | | | | | | | | | | | | | | | | | | | | | | | |
|---|----|----|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| A | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 |
| B | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 6 | | | | | | | | | | | | | | | | | | | | | | | |
| D | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | |
| F | 1 | | | | | | | | | | | | | | | | | | | | | | | |
| G | | | | | | | | | | | | | | | | | | | | | | | | |
| H | | | | | | | | | | | | | | | | | | | | | | | | |
| I | | | | | | | | | | | | | | | | | | | | | | | | |
| J | | | | | | | | | | | | | | | | | | | | | | | | |
| K | | | | | | | | | | | | | | | | | | | | | | | | |
| L | 18 | | | | | | | | | | | | | | | | | | | | | | | |
| M | | | | | | | | | | | | | | | | | | | | | | | | |
| N | | | | | | | | | | | | | | | | | | | | | | | | |
| O | | | | | | | | | | | | | | | | | | | | | | | | |
| P | 19 | | | | | | | | | | | | | | | | | | | | | | | |
| Q | | | | | | | | | | | | | | | | | | | | | | | | |
| R | | 20 | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | |
| T | | | | | | | | | | | | | | | | | | | | | | | | |
| U | 30 | | | | | | | | | | | | | | | | | | | | | | | |
| V | | | | | | | | | | | | | | | | | | | | | | | | |
| W | | | | | | | | | | | | | | | | | | | | | | | | |
| X | | | | | | | | | | | | | | | | | | | | | | | | |
| Y | 31 | | | | | | | | | | | | | | | | | | | | | | | |
| Z | | | | | | | | | | | | | | | | | | | | | | | | |

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 2247, 2245, 2246, 4627, 7070

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE A-13(3)

PL507

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT WEST ON SOUTH SIDE SECTION 33 T3N R1E
2640 SET QUARTER SECTION POST IN PRAIRIES AND MADE MOUND
5280 SET POST CORNERS SECTIONS 32 & 33 IN PRAIRIE AND MADE MOUND. LAND & C SAME.
- 1833 MULLETT WEST ON SOUTH SIDE SECTION 34
2640 SET QUARTER SECTION POST IN PRAIRIE AND MADE MOUND
5280 SET POST CORNER SECTIONS 33 & 34 IN PRAIRIE AND MADE MOUND LAND ROLLING PRAIRIE SECOND RATE.
- 1833 HARRISON NORTH BET 3 & 4
2574 LEFT MARSH 7 ENTER PRAIRIE
2640 QUARTER SEC COR. SET A POST & RAISED MOUND
5214 INT. N. BDY 26.4' E OF P. SET POST & RAISED MOUND FOR COR TO SECS 3 & 4. LAND 1ST 1/2 LEVEL & WET 3RD RATE- MARSH- NORTH 1/2 ROLLING 1ST RATE PRAIRIE DEC 26TH 1833
- 1847 TWP RD RECORDS BK 1 PG 21 BEGINNING AT THE NORWEST CORNER OF SEC 3 AND 4, 9 AND 10, 15 AND 16, 21 AND 22 TO THE SOUTHWEST CORNER OF SEC 22. SAID RD IS FOUR RODS IN WIDTH.
- 1847 TWP RD REC BK 1 PG 21 BEGINNING AT THE NW COR OF SEC 3 AND 4, 9 AND 10, 15 AND 16, 21 AND 22 TO THE SW COR OF SEC 22. SAID RD IS 66' IN WIDTH
- 1866 LOCKE REMONUMENTATION FIELD NOTES.
PG 49 WEST ON NORTH LINE SEC 4 VAR 7
503.58 STONE CULVERT
1256.64 CENTER SLUICE BRIDGE 3.3' WIDE
2684.88 INTERSECTED 1/4 LINE FOR TOWN 3 2.11' SOUTH OF COR FOUND OLD STAKE IN CENTER OF HIGHWAY AND NEARLY IN LINE WITH FENCES RUNNING N AND S.
2651.88 SET 1/4 COR FOR SEC 4 33' EAST OF COR. FOR TOWN 3 33' BEING 1/2 OF THE SUM OF THE MEAN BETWEEN THE "JOGS" AT THE SEC. COR. VAR CORRECTED 6-44
CONTINUED WEST FROM 1/4 COR WITH VAR 7
5311.18 INTERSECTED WEST BOUNDARY 26.90' SOUTH OF COR. FOUND STONE SET BY SELF. (SEE CO. SURVEYORS RECORD SEC 4) VAR CORRECTED 6-25 MARKED 1/4 MONUMENT WITH FIGURE 4 ON SOUTH FACE. SEPT 3, 1868
PG 48 WEST ON NORTH LINE SEC 3 VAR 7
2668.05 INTERSECTED 1/4 LINE FOR SEC 34 TOWN 3 N AT COR. FOUND OLD STAKE IN CENTER OF HIGHWAY AND IN LINE OF FENCES RUNNING NORTH AND SOUTH.
2654.85 SET 1/4 COR 13.2' EAST OF 1/4 COR. FOR TOWN 3 THE SEC. COR. WEST BEING LOST.
2979.9 CENTER SLUICE BRIDGE 5.28' WIDE
4068.9 CENTER SLUICE BRIDGE 5.28' WIDE
5300.13 INTERSECTED WEST BOUNDARY 12.62' SOUTH OF COR. SET AS PREVIOUSLY STATED (PAGE 47) VAR CORRECTED 6-44 MARKED 1/4 MONUMENT WITH FIGURE 3 ON SOUTH FACE. SEPT 3 1868
PG 47 NORTH BETWEEN SECS 3 AND 4 VAR 7-25
2655.84 INTERSECTED 1/4 LINE 3.96' WEST OF COR. FOUND POST IN MOUND 6 INCHES SOUTH TO COR POST TO FENCES VAR CORRECTED 7-20
CONTINUED NORTH FROM 1/4 COR WITH VAR 7-20

Donald Barnes

SHEET 1 OF 3

CORNER CODE A-13(3)

703-03

PL507

- 5243.04 INTERSECTED NORTH BOUNDARY 11.88' EAST OF COR. CORNERS FOR TOWN 2 AND 3 BOTH LOST. SET COR FOR TOWN 3 MIDWAY AND ON A RIGHT LINE BETWEEN THE ¼ COR ½ MILE EAST AND WEST AND SET THE COR. FOR TOWN 2 2.64'? 26.4'? EAST OF COR. FOR TOWN 3 COR IN CENTER OF HIGHWAY VAR CORRECTED 7-35 SEPT. 3 1868
- 1933 SUNNY VOL 3 PG 235 SET 1" X 36" IRON PIPE IN CONCRETE PAVEMENT 1.76' NORTH OF CENTER OF SAME.
- 1934 SUNNY VOL 3 PG 236 FOR THIS COR. SEE PG 235. 26.4' OFFSET. SE COR SEC 33 IS WEST.
- 1958 BATTERMAN VOL 3 PG 235 FD 1" PIPE 1' FROM NORTH EDGE PVMT. REF. SAME.
- 1970 BATTERMAN JR. VOL 4 PG 484 REFERENCED AND MAPPED CORNER.
- 1974 LEE MAP #4316 PIPE. ANGLE 89-54-12 @ N ¼ COR SEC 4 FROM NE COR SEC 4 TO CENTER OF SEC 4.
- 1988 LEE CSM13-216 2625.14 TO N ¼ COR SEC 4 & 26.46 EAST OF SE COR SEC 33 CENTER TWP
- 1988 BARNES A-13 & Z-13 (CENTER TWP) LARGE CUT ON NORTH SIDE OF ROAD AND SMALL CUT ON SOUTH SIDE. FOUND 1" PIPE, REFERENCE TIES, & EXCAVATION HOLE @ SE COR SEC 33. USING DOT CONTROL 246,015.82; E/W 2,217,948.38' FOR SE COR SEC 33 CENTER TWP. @ SE COR SEC 33 CENTER TWP DUG 4X10 HOLE & FD NOTHING. SUBSOIL INDICATES AREA WAS CUT. LARGE BANK CUT ON NORTH SIDE AND POSSIBLY SMALL CUT ON SOUTH SIDE. PLACED SE COR SEC 33 ON LINE WITH NE COR OF SEC 3 PLYMOUTH TWP NORTH 1/4 COR OF SEC 4 PLY AT RECORD DISTANCE.
- 1988 BATTERMAN VOL 6 PG 386 & 388 N88-56-44E 2645.99 TO N ¼ COR SEC 3, S89-03-54W 2651.06 TO N ¼ COR SEC 4, S1-27-23E 2587.09 TO E ¼ COR SEC 4, 26.40 EAST OF SE COR SEC 33.
- 1989 WIDOT STH 11 MAP #16698 PROJECT 1704-03-22 REINFORCING ROD 246,016.25; 2,217,974.77 S89-04-00W 26.40 TO SE COR SEC 33 CENTER TWP MON TO BE SET (246,015.82; 2,217,948.38)
- 1992 BARNES A-13(1) & Z-13(1) FOUND DOT DISK IN CONCRETE MON @ REFERENCE MONUMENTS. N86-47-19W 26.42' TO SE COR SEC 33 CENTER TWP. MONUMENT WILL BE DESTROYED BY CONSTRUCTION.
- 1992 BARNES A-13(2) FD DOT DISK @ NE COR SEC 4 & DOT REFERENCE MONUMENTS. N86-47-19W 26.42 (REC 26.40) TO SE COR SEC 33 CENTER TWP. DOT STATIONING: 299+44 @ SE COR SEC 33 & 299+71 @ NE COR SEC 4. DID NOT ACCEPT DISK. ACCEPTED POSITION AS ESTABLISHED BY TIES OF RECOR. THE DISK IS 0.44' SOUTH AND 0.08' EAST OF THE CORRECT LOCATION. RECORD TIE DISTANCES DO NOT AGREE WITH DISK.
- 1995 LUENBERGER CSM VOL 18 PG 425 FD DOT BRASS CAP AT NE COR SEC 4 & SE COR SEC 33. S88-48-39W TO N ¼ COR SEC 4, S1-27-25E TO E ¼ COR SEC 4. 2624.65 FROM SE COR SEC 33 TO N ¼ COR SEC 4.
- 2002 REIGEL MAP #14302 FD 1" PIPE IN MON BOX & FD 1" PIPE IN MON BOX AT SE COR SEC 33. 26.52 EAST OF SE COR SEC 33. 2651.14 TO N ¼ COR SEC 4

Donald Barnes

SHEET 2 OF 3 CORNER CODE A-13(³/₂)

7-03-03

PL507

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

USED MY OLD OBSERVATIONS. FD TIES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

THE WIDOT DISK IS NOT AT THE CORRECT LOCATION. SEE U.S. PUBLIC LAND SURVEY MONUMENT RECORD A-13(1).

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes
Emboss 7-03-03

SHEET 3 OF 3

CORNER CODE A-13(~~2~~³)

7.08 REQUIREMENT