

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 3 N., R. 10 E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6						5																		
D																									
E																									
F																									
G	1						8																		
H																									
J																									
K																									
L	18						17																		
M																									
N																									
O																									
P	19						20																		
Q																									
R																									
S	30						29																		
T																									
U																									
V																									
W																									
X	31						32																		
Y																									
Z																									

MAGNOLIA TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 2-23

MA632

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT VAR 7-40E

WEST ON SOUTH SIDE SEC 36

2640 SET QUARTER SEC POST

BUR OAK 9 N29W 70.62'

RUB OAK 6 N42E 163.02'

2970 ENTER PRAIRIE

5280 SET POST CORNER SECTIONS 35 & 36

IN PRAIRIE AND MADE A MOUND

1868 LOCKE VOL 1 PG 322 FOUND BTs DIST TO N B.T. 1.57 SET W.O. STAKE SURROUNDED BY 3 SANDSTONES. CALLS FOR 2616.90 TO NW COR SEC 1 & 2480.94 TO CENTER OF SEC 1.

1870 RUGER VOL 2 PG 36 FOUND COR EST. BY LOCKE. CALLS FOR 1320.66 TO 1/16TH COR TO NORTH, 2641.32 TO CENTER OF SEC 36, 659.92 TO COR TO EAST, 2639.68 TO NE COR SEC 1.

1874 RUGER VOL 2 PG 130 FOUND COR SET BY LOCKE. CALLS FOR DISTANCE OF 1242.45 TO 1/16TH COR TO SOUTH & 2476.65 TO CENTER OF SEC 1 AND 2610.96 NW COR SEC 1.

1877 RUGER VOL 2 PG 232 FOUND COR EST. BY LOCKE.

1880 LEE VOL 2 PG 313 FOUND COR SET BY LOCKE, CALLS FOR 1861.20 TO PROPERTY CORNER TO SOUTH AND 2481.60 TO LOCKE'S CORNER AT CENTER OF SEC 1.

DUG & FOUND NOTHING. PLACED CORNER ON LINE WITH N/S FENCE AND CENTER OF PAVEMENT. THIS IS IN HARMONY WITH RECORD DISTANCES. SINCE THE NW COR OF SEC 1 & THE SW COR OF SEC 36 ARE COMMON THE N1/4 COR OF SEC 1 & THE S 1/4 COR SEC 36 ARE COMMON.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

RESTORED CORNER THROUGH ACCEPTANCE OF OBLITERATED

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Donald Barnes
Seal
April 22, 1998

emboss

Number of included sheets _____

S89-16-10E 2631.46
1833 ORIG 2610.3
1870 RUGER 2620.2

S89-15-55E 2630.32
1833 ORIG 2610.3
1870 RUGER 2625.8

28.45
28.38

1310.10 RUGER 655.05 655.05 656.45 656.45 RUGER 1312.90

NW COR

NE COR

MAGNOLIA TWP

SEC 36

CENTER TWP T3N R1E

T2N R1E

PLYMOUTH TWP

SEC 35

SEC 35

SEC 2

SEC 1

SEC 1

SEC 1

SEC 12

SEC 12

ROCK COUNTY PROJECTION

Z-23

NO-17-23W 1330.95 NO-30-30W 1327.14
1322.64 LEE 1322.64

1833 ORIG 2640
1881 LEE 2658.48
1988 BARNES 2658.09
1330.95 BARNES 1327.14
1881 LEE 2645.28

1870 RUGER 2656.16
1328.08 RUGER 1328.08
655.71 RUGER 655.71

1326.60 RUGER 1326.60
1870 RUGER 2653.20 VAR 5-53
NO-15-39E 2649.95
01/17/01 DAB

1870 RUGER 2623.83
655.96 655.96 RUGER 1311.92
NO-21-00W 2641.79
1833 ORIG 2640
1870 RUGER 2625.8
1312.90 RUGER 1312.90

NO-21-00W 2656.25

1/17/01
DAB

RUGER 5243.21
S89-26-39E 5259.23
W 1/4 COR

1870 RUGER 2618.55 VAR 6-30
1315.88 RUGER 1315.88
S89-26-39E 2624.85
1/10/01 DAB

INTERSECTION OF
1/4 LINES, NOT MONUMENTED
CENTER OF SEC.

NO-15-39E 2641.99
1870 RUGER 2641.32
1320.66 RUGER 1320.66
01/17/01 DAB

1870 RUGER 2632.16
328.84 329.02 329.02 658.04
1316.08 RUGER 1316.08

NO-27-56W 2647.96
1870 RUGER 2644.95 VAR 7-25
1833 ORIG 2640
1322.48 RUGER 1322.48

E 1/4 COR

SET 3/4" PERIOD NW COR

NO-25-45W 2648.64
1833 ORIG 2640
1881 LEE 2644.62
1322.31 LEE 1322.31

LEE 495.88

1833 ORIG 2640 N 1/4 COR

S89-19-00E 2644.01
1833 ORIG 2640
1870 RUGER 2639.68 VAR 6-22
659.92 659.92 RUGER 1319.84

NE COR

1833 ORIG 2600.4

NO-13-02E 2303.10
1834 ORIG 2364.78
1874 RUGER 2332.78 VAR 5-15
1112.26 RUGER 1120.52
1880 LEE 2306.04
1868 LOCKE 2302.74 VAR 6-10

1880 LEE 1729.53
FENCE 1733.2

1874 RUGER 2610.96 VAR 6-45
1868 LOCKE 2616.90
S89-35-19E 2616.90
RUGER 5250.64
5260.91

SET TIES

1874 RUGER 2629.44 XXXX

1880 LEE 1861.20 FENCE 1876.6
1868 LOCKE 2480.94 VAR 6-45
1880 LEE 2481.60
1874 RUGER 2476.65 VAR 5-35
1234.2 RUGER 1242.45
NO-30-00E 2480.94

SEC 1

4926.98
LOCKE 4925.58
LEE 4928.88

SI-32-53W 2623.88
1869 LEE 2622.84
655.71 655.71 1311.42
1868 LOCKE 2623.50 VAR 5-55
1834 ORIG 2640

FENCE 1309.6
LEE 576.51
569.86 FENCE

1869 LEE 2653.2 VAR 3
1326.60 331.65 331.65 331.65 331.65
1880 LEE 2645.28 VAR 3
1874 RUGER 2647.92
1868 LOCKE 2634.06 VAR 3
S85-44-15E 2651.45
1869 LEE 2673.0
1336.5 334.13 334.13 334.13 334.13

1868 LOCKE VAR 6-45
1272.81 LEE 1272.81
1869 LEE 2545.62
NO-30-00E 2607.80
LEE 5027.22
NO-30-00E 5088.74

INTERSECTION OF
1/4 LINES, NOT MONUMENTED
CENTER OF SEC.

5347.68
RUGER 5338.74
1868 LOCKE VAR 3
1345.41 RUGER 1345.41
1877 RUGER 2690.82
S85-44-15E 2696.22

1833 ORIG 2640

1833 ORIG PLAT 2640
1868 LOCKE 2649.57
1989 BARNES 2649.82
NO-30-13W 2649.82

E 1/4 COR

N89-49-22E 1337.27

1363.3 FENCE 1335

S 1/4 COR 1301.6 FENCE 1396.6

SW COR

1834 ORIG 2655.84
1867 LOCKE 2690.68 VAR 3-24
1345.34 LOCKE 1345.34
1989 BARNES 2698.22
S86-08-09E 2698.29

1887 RUGER 2663.32
1986 BARNES INT. 2649.44

1834 ORIG 2655.84
1867 LOCKE 2690.29 VAR 6-24
1870 RUGER 2697.75
1989 BARNES 2698.22
S86-08-19E 2698.19

SE COR

NO-09-16W 2630.45
1867 LOCKE 2657.82

Donald Haines
April 28, 1998
EMBOSSED SEAL

SOME DISTANCES & BEARINGS
ARE BASED ON OLD OBSERVATIONS

1867 LOCKE 2731.08