

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 11 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

PORTER TWP

ROCK COUNTY WI

IF AVAILABLE

ROCK COUNTY COORDINATES PREFERRED

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B	6					5								4											3
C																									2
D																									1
E																									
F																									
G	7					8								9											10
H																									11
J																									12
K																									
L	18					17								16											15
M																									14
N																									13
O																									
P	19					20								21											22
Q																									23
R																									24
S																									
T	30					29								28											27
U																									26
V																									25
W																									
X	31					32								33											34
Y																									35
Z																									36

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON: -----

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE E-15

PO628 S1/4SEC34

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 (SEP 15) MULLETT & BRINK T4N R11E 4TH MERIDIAN WEST
ON SOUTH SIDE SEC 34
2640.0 SET QUARTER SECTION POST BUR OAK 16
N76E 42.90'; BUR OAK 8 N71W 86.46'
5280.00 SET POST CORNER SECTIONS 33 & 34 BUR
OAK 10 N32W 23.76'; BUR OAK N70E 43.56'
LAND ROLLING SECOND RATE TIMBER WHITE
BLACK & BUR OAK
- 1833 ORIG GOV PLAT NW COR SEC 2 CENTER TWP IS 58.74' WEST
OF SW COR SEC 35 PORTER TWP & NW COR SEC 3 CENTER
TWP IS 44.88' WEST OF SW COR SEC 34 PORTER TWP.
- 1861 RUGER VOL 1 PG 156 SET HH 22X13X9 SURROUNDED BY 4
HH VAR 8-25 1321.82 TO S 1/6TH COR OF SE 1/4 SEC 34 &
2643.63 TO SE COR SEC 34. USED TO SUBDIVIDE SE 1/4
SEC 34. SHOWS VAR8-25 ON SOUTH LINE OF SW 1/4 SEC
34. IT APPEARS THE CENTER OF SEC 34 WAS ESTABLISHED
MID WAY BETWEEN THE EAST & WEST 1/4 CORNERS OF SEC
34.
- 1884 RD REC BK 1 PG 8 BEGINNING AT THE JUNCTION OF THE
SOUTH EAST COR SEC 34 IN SAID TOWN OF PORTER AND
THE NE COR OF SEC 3 IN SAID TOWN OF CENTER AND RUN
THENCE WEST ON THE SE LINES OF SAID SEC 2607';
THENCE ANGLE TO NORTH SIDE OF SAID TOWN LINE;
THENCE WEST 1/4 MILE TO INTERSECTION OF HWY RUNNING
NORTH AND SOUTH THROUGH THE CENTER OF SW 1/4 OF
SAID SEC 34 IN SAID TOWN OF PORTER THE SAME BEING
AN ACCURATE SURVEY THEREOF, AND SAID HWY BEING
UPON THE TOWN LINE BETWEEN SAID TOWNS OR AS NEAR
THERETO AS THE SITUATION OF THEN GROUND WILL ADMIT.
THE LINE OF SAID SURVEY IS CENTER OF SAID HWY AND
THE SAME IS LAID OUT OF THE WIDTH OF 49.5' """"
- 1977 BARNES VOL 5 PG 269 & CENTER TWP FB #1 PG 16 DUG 5'
DEEP & FD NOTHING. @ N 1/16TH COR OF NE 1/4 SEC 3
DUG 5' DEEP & FD NOTHING. MIDWAY ON LINE WITH SE &
SW CORNERS OF SEC 34, N 1/4 COR SEC 3 CENTER TWP ON
LINE WITH NE & NW COR OF SEC 3 CENTER TWP. S 1/4 COR
SEC 34 IS 51.89 EAST OF N 1/4 COR SEC 3. REFERENCED
SAME. 2656.70 TO SW COR SEC 34 & 2656.70 TO SE COR
SEC 34. FROM N 1/4 COR SEC 3 TO NE COR SEC 3 IS
2649.78 & FROM N 1/4 COR SEC 3 TO NW COR SEC 3 IS
2649.78. THE N/S FENCE @ THE S 1/16TH COR OF THE SE
1/4 OF SEC 34 IS 1324.6 TO THE SE COR SEC 34 & 1332.0
TO THE S 1/4 COR SEC 34.
- 1979 SCHNEEBERGER CSM VOL 8 PG 501 STATES NOTHING
ABOUT MON @ N 1/4 COR SEC 3 CENTER TWP. 2649.22
FROM N 1/4 COR TO NW CORNERS OF SEC 3 CENTER TWP
- 1979 SCHNEEBERGER #689 N 1/4 COR SEC 3 CENTER TWP.
2649.22 TO NW COR SEC 3 CENTER TWP. STATES NOTHING
ABOUT MON.
- 1979 BARNES VOL 6 PG 5 SHOWS EAST OF N 1/4 COR SEC 3.
- 1979 SCHNEEBERGER #692 N 1/4 COR SEC 3 CENER TWP FD
ALUM.
- 1980 COMBS #693 CENTER TWP COUNTY SURVEYOR MON @ N
1/4 COR SEC 3
- 1980 THOM #690 COUNTY SURVEY MON @ N 1/4 COR SEC 3
CENTER TWP N88-37-15E 2649.72 TO COUNTY SURVEY
MON @ NE COR SEC 3.
- 1981 COMBS CSM VOL 10 PG 239 FD COUNTY SURVEYOR MON @
N 1/4 COR SEC 3 CENTER TWP & NE COR SEC 3 CENTER
TWP. EASTERLY 1324.85 FROM N 1/4 COR SEC 3 TO PIPE.
- 1984 COMBS CSM VOL 11 PG 646 ALUM.

SHEET 1 OF 3
CORNER CODE Z-15

Donald Barnes

3-26-2009

PD628 S 1/4 SEC 34
 1987 COMBS CSM VOL 12 PG 572 ALUM
 1987 COMBS CSM VOL 13 PG 142 STATES NOTHING ABOUT MON.
 1987 COMBS CSM VOL 13 PG 430 ALUM. NO-13-20E ALONG SEC
 LINE. WEST TO ALUM @ SW COR SEC 34. THERE IS A IP
 PROPERTY COR 35.00 NO-13-20E OF S 1/4 COR.
 1988 COMBS CSM VOL 13 PG 444 ALUM MON 2649.90 TO FD PIN
 @ SW COR SEC 34.
 1991 THOM #11866 CENTER TWP ALUM @ N 1/4 COR SEC 3
 CENTER TWP. EASTERLY 1324.86 TO IP ON SEC LINE,
 2649.72 TO ALUM @ NE COR SEC 3 CENTER TWP
 1992 KARNS CSM VOL 15 PG 420 ROCK COUNTY MON. @ N 1/4
 COR SEC 3 CENTER TWP
 1995 KARNS CSM VOL 20 PG 172 STATES NOTHING ABOUT MON.
 EAST 2652.65 TO SE COR SEC 34.
 1997 JRK CSM VOL 20 PG 172 STATES NOTHING ABOUT MON.
 2652.65 TO SE COR SEC 34.
 1998 COMBS CSM VOL 21 PG 182 ALUM. MON N88-37-15E
 2679.70 TO SET PIN @ NE COR SEC 3 CENTER TWP. S 1/4
 COR SEC 34 IS EAST 51.76 OF ALUM @ N 1/4 COR SEC 3
 CENTER TWP
 1999 COMBS CSM VOL 23 PG 68 ALUM N88-37-40E 2657.01 TO
 ALUM @ SE COR SEC 34
 2001 COMBS CSM VOL 24 PG 290 ALUM @ N 1/4 COR SEC 3
 CENTER TWP. 2605.08 TO ALUM @ SW COR SEC 34.
 2002 LATHROP CSM VOL 25 PG 263 ALUM 2656.80 TO ALUM @
 SW COR SEC 34.
 2006 GARD CSM VOL 30 PG 220 ALUM 2656.96 TO ALUM @ SE
 COR SEC 34

I USED MY 1977 & 1979 OBSERVATIONS. I FOUND THE REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MONUMENTS

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

YES IN 1977

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald Barnes
 DONALD BARNES

SHEET 2 OF 3

Barnes
 3-26-2009

CORNER CODE **Z-15**

A.E. 7.08 REQUIREMENT

