

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N. R. 11 E.

CORNER CODE INDEX

PLYMOUTH TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C																									C
D																									D
E																									E
F																									F
G																									G
H																									H
I																									I
J																									J
K																									K
L																									L
M																									M
N																									N
O																									O
P																									P
Q																									Q
R																									R
S																									S
T																									T
U																									U
V																									V
W																									W
X																									X
Y																									Y
Z																									Z

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25  
PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:  
\_\_\_\_\_

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON: \_\_\_\_\_

OBSERVATION SHEETS 176 & 6702

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE T 9

PL596

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON NORTH BET 28 & 29

2640 QUARTER SEC COR. IN RAVINE DESCENDING?. SET POST & RAISED MOUND

5280 SET COR TO SECS 20 21 28 29 ON GROUND DESCENDING SE SET POST & RAISED MOUND. LAND HIGH ROLLING PRAIRIE 1<sup>ST</sup> RATE GROWTH ?? & ? & PRAIRIE GRASS.

1855 CHURCH VOL 1 PG 38 STONE 18" LONG 4" THICK 8" WIDE. S. CORNER HSE N 15 1/2 W 373.56; LOCUST TREE N58W 27.72'. VAR 7 1/2 2658.98 TO SEC COR SEC 29, VAR 7 1/2 2660.46 TO NE COR SEC 29, 2660.46 TO CENTER SEC 28, & 5315.31 TO E 1/4 COR SEC 28

1868 LOCKE PG 19 NORTH BETWEEN SECS 28 AND 29 VAR 7-30 SET OFF 23.43' EAST

2668.05 INTERSECTED 1/4 LINE 22.77' EAST OF COR. FOUND STONE SET BY CHURCH (SEE PAGE 18) ALSO CO. SURVEYORS RECORD SEC 28) COR IN CENTER OF HIGHWAY RUNNING NORTH & ON WEST LINE OF HIGHWAY RUNNING SOUTH AND IN LINE WITH FENCES RUNNING E & W. VAR CORRECTED 7-29

CONTINUED NORTH WITH VAR 7-15

5297.16 INTERSECTED NORTH BOUNDARY 0.66' WEST OF COR. FOUND STONE SET BY CHURCH. (SEE CO. SURVEYORS RECORD SEC 28 ALSO PAGE 18 HEREOF) VAR CORRECTED 7-14.

1978 BARNES VOL 5 PG 427 DUG & FD NOTHING. ESTABLISHED CORNER AS CALLED FOR IN LOCKE'S REMONUMENTATION NOTES (1868) & CHURCH'S SURVEY (1855). LOCKS NOTES STATES THE CORNER IS IN LINE WITH THE CENTER OF THE ROAD TO THE NORTH & THE WEST EDGE OF THE ROAD TO THE SOUTH. CHURCH'S SURVEY NOTES THE DISTANCE & BEARING TO THE SOUTH CORNER OF THE HOUSE. THERE IS A LARGE DISCREPANCY BETWEEN THE RECORD & ACTUAL DISTANCE TO THE NE CORNER. DISTANCE TO THE SE HSE COR IS N13W 373.6 (REC N15 1/2 W 373.56). REFERENCED SAME. SHOWS FORMER COUNTY SURVEYORS EXCAVATION PATCH & NEW EXCAVATION LOCATION. SHOWS 1978 & 1855 MAGNETIC NORTH. COR @ CENTER OF PVMT & ON LINE WITH E/W FENCE TO THE EAST. SET ALUM. MON. CALLS FOR MAGNETIC VARIATION OF NEEDLE IN 1978 AS 1-25 EAST OF TRUE NORTH & IN 1855 4-56 EAST OF TRUE NORTH.

1978 BARNES VOL 5 PG 430 5,344 TO CENTER OF 6TH 213 & DISTANCES TO E/W FENCES ALONG EAST LINE OF SEC 29.

1978 BARNES VOL 5 PG 473 NO-13-03E 2666.87 TO NE COR SEC 29, SO-09-37W 2672.16 TO SE COR SEC 29, 1333 TO E/W FENCE BETWEEN THE NE COR SEC 29, ANGLE 88-53-12 @ SE COR SEC 29 FROM S 1/4 COR SEC 29 TO E 1/4 COR SEC 29, ANGLE 90-53-32 @ SE COR SEC 29 FROM E 1/4 COR SEC 29 TO S 1/4 COR SEC 28

1978 LEE CSM VOL 7 PG 313 SET NAIL FROM TIES

1981 COMBS CSM 10 PG 285 FD ALUM.

1984 WIDOT VOL 6 PG 314 & MAP #7038 PROJECT 5521-01-21 ALUM MON. 222,185.89; 2,213,090.75 S1-01-03E 2672.16 TO ALUM MON AT SE COR SEC 29

1996 SCHROEDER CSM VOL 19 PG 479 STATES NOTHING ABOUT MON.

LOCKE'S REMONUMENTATION DISTANCE TO THE NE COR SEC 29 APPEARS TO HAVE A BUST. IT IS PROBABLY 1/2 A CHAIN (33"). FD ALUM. MON. 0.5' DEEP & ALSO FD TIES.

*Donald Barnes*

SHEET 1 OF 2 CORNER CODE T-9

12-31-02

PL596

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

*Donald Barnes*

Seal

12-31-02

Emboss

SHEET 2 OF 2

CORNER CODE

**T-9**

A.E. 7.08 REQUIREMENT