

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N., R. 11 E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K	18																								
L																									
M																									
N																									
O																									
P	19																								
Q																									
R		20																							
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

PLYMOUTH TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEETS 232, 602, 778

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE V-3

PL602

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 HARRISON WEST BET 30 & 31

165 LEFT TIM. & ENTER PRAIRIE
2145 LEFT PRAIRIE & ENTER TIM.
2640 TEMPY ¼ P
3234 BROOK 3.3' CRS SW
5297.16 INT. W. BDY AT P & ESTABLISHED COR TO SECS 30
& 31 BEARINGS {W.O. 14 N85W 99' W.O. 24 S73E
119.46'
LAND ROLLING 1ST RATE WITH LYNN ASPEN HICKY,
WALNUT, BURR & W.O.

COR EAST

2657.16 QUARTER SEC COR {RED O 20 N23E 23.1' ASPEN
16 S5E 9.9'

5297.16 SEC COR

1844 PEASE TWP RD RECORDS BK 1 PG 4 COMMENCING AT THE
CORNERS OF SEC 26,27,34 AND 35, IN T2N R11E AND
RUNNING WEST ON THE LINE BETWEEN SECTIONS 27 & 34,
2622.84'. SET POST WHERE OLD ¼ POST ON SAID LINE
STOOD BURNT STUMP OF WHITE OAK BEARS N5W 13.86' AND
S88E 73.92'; THENCE WEST ON SAID LINE 2622.84' TO THE
CORNER OF SEC 27,28,33, & 34, SET POST WHITE OAK 24
INCHES IN DIA BEARS S35E 114.18', BURNT STUMP OF BASS
WOOD 24" N78E 86.46'; THENCE WEST ON LINE BETWEEN
SECS 28 AND 33 TO CORNER OF SEC 28,29,32 & 33 5224.5'
SETTING POST IN OLD MOUND; THENCE WEST ON LINE
BETWEEN SECTIONS 29 & 32, 2652.8' SET POST BY BLACK
OAK 24 INCH BEARS N26E 27.06'; THENCE WEST ON THE
LINE BEFORE SAID 2642.64' TO THE COR OF SEC 29,30,31 &
32, BLACK OAK BEARS N41E 78' AND N22W 97.02'; THENCE
WEST OF LINE BETWEEN SEC 30 & 31, 5297.16' TO THE LINE
BETWEEN RANGES 10 & 11 EAST 4 MILES AND 5.94'. SAID
RD EXTENDS 33' ON EACH SIDE OF THE ABOVE LINE.

1868 LOCKE PG 63 WEST BETWEEN SECS 30 AND 31 VAR 7-20

2244 SET OFF 14.52' NORTH

2508 SET OFF 36.96' NORTH

2641.98 INTERSECTED ¼ LINE 3.3' SOUTH OF COR. FOUND
NORTH BT AND WHERE SOUTH B.T. WAS DUG OUT
AND LARGE LIMESTONE ON COR. IN HIGHWAY AND
IN LINE WITH FENCE RUNNING SOUTH. VAR
CORRECTED 6-09

SET OFF 6.6' NORTH OF ¼ COR & CONTINUED
WEST WITH VAR 7-08

3158.1 CENTER OF BRIDGE 9.24' WIDE

3532.32 CENTER OF SLUICE BRIDGE

4422 SET OFF 5.28' NORTH

5311.02 INTERSECTED WEST BOUNDARY 22.77' SOUTH OF
COR. FOUND B.T.S IN SECS 30 AND 31 AND 35
AND 36 AND OLD STAKE VAR CORRECTED IS 6-23
BT IN 31 IS S67E BT IN 25 IS 96.36' & BT IN 36 IS
126.72' SEPT 10, 1868

1869 LEE VOL 2 PG 5 FD MON 2645.28 TO SE COR SEC 30 &
2639.34 VAR 7-15 TO GEN SEC 30,

1958 BATTERMAN VOL 3 PG 528 FD 6X6X36 CUT STONE 2' DEEP.
REF SAME.

1975 COMBS OSM VOL 4 PG 319 SEE PAPER COPY FOR SYMBOL

1978 BARNES VOL 5 PG 428 FD 1 ½X22 IP & 2' DEEP FD CUT
L.S. SET ALUM. & REF SAME. 2' NORTH OF E/W CENTER OF
PVMT.

1996 BARNES VOL 6 PG 446 FD ALUM. 2668.58 TO NW COR SEC,
31.

Donald Barnes

2-12-03

SHEET 1 OF 2 CORNER CODE V-3

PL602

1999 TALARGZYK MAP #08048 FD CAST ALUM. EAST 2642.10 TO
NE COR SEC 31, 60-43-53E 2643.40 TO CEN SEC 31, & 60-
43-53E 5292.46 TO S ¼ COR SECC 31

FD ALUM. MON 0.2' DEEP; ON LINE WITH N/8 FENCE; 2.6' NORTH OF
CENTER PVMT. FD REF. PIPES

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON WHICH PERPETUATED FD CUT L.S.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Donald Barnes

2-12-03

Emboss

SHEET 2 OF 2

CORNER CODE

V-3

A.E. 7.08 REQUIREMENT