

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N. R. 11 E.

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C																									
D																									
E																									
F																									
G																									
H																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

PLYMOUTH TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____ SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE G-5

PL535

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON NORTH BET SECS 7 & 8
858 LEFT MARSH & ENTER TIMBER
1609.74 WD 16
2640 QUARTER SEC COR. {W.O. 19 889E 67.32' W.O 20
888W 58.74'
5280 COR TO SECS 5 6 7 8 {ASPEN 16 863 11.22'
ASPEN 10 833W 13.2' ASPEN 15 N54W 34.98'
WHITE O 13 N52E 8.58' LAND ROLLING 1ST RATE
WITH W.O. ASPEN ELM WALNUT HICKY LYNN
CHERRY HAZEL
- 1858 CHURCH VOL 1 PG 76 STATES NOTHING ABOUT MON.
2649.57 TO CEN SEC 8 & 5298.81 VAR 5 TO E ¼ COR SEC
8.
- 1858 CHURCH VOL 1 PG 66 STATES NOTHING ABOUT MON. 2640
TO NE COR SEC 7
- 1868 LOCKE VOL 1 PG 309 & MAP #4329 FD STUMPS OF BT& &
REMAINS OF STAKE - SET L.S. 10X8X2, VAR 4-55 2657.82 TO
CEN SEC 8, & VAR 7-20 2655.84 TO NW COR SEC 8.
- 1868 LOCKE PG 78 NORTH BETWEEN SECS 7 & 8 VAR 7-05
O SET OFF 13.2' WEST
990 SET OFF 11.55'
2670.36 INTERSECTED ¼ LINE AT COR. FOUND STUMPS OF
B.T.S AND STONE SET ON COR. BY SELF. (SEE CO.
SURVEYORS RECORD SEC 8) VAR CORRECTED 7-07
CONTINUED NORTH FROM ¼ COR WITH VAR 7-15
O SET OFF 7.26' WEST'
5326.2 INTERSECTED NORTH BOUNDARY AT COR VAR
CORRECTED 7-24 SEPT 15 1868
- 1891 TWP RD REC BK 2 PG 15 COMMENCING AT THE
INTERSECTION OF A HWY IN THE CEN OF SEC 8; THENCE
RUNNING WEST ON THE ¼ LINE OF SAID SEC TO THE ¼ POST
ON THE WEST LINE OF SAID SEC 8, THE SAME BEING AN
ACCURATE SURVEY THEREOF CAUSED US TO BE MAKE, THE
LINE OF SAID SURVEY IS THE CENTER OF SAID HWY AND THE
SAME IS LAID OUT OF THE WIDTH OF 49.5'
- 1960 BATTERMAN VOL 4 PG 77 FD OUT STONE & REFER. SAME.
1974 LEE VOL 4 PG 77 REFERENCED STONE.
1976 COMBS OSM VOL 5 PG 213 FD O.I.
1977 SCHROEDER OSM VOL 7 PG 131 SET IP 1327.9 TO 1 1/16TH
COR TO THE EAST.
1978 COMBS OSM VOL 8 PG 01 ALUM
1978 BARNES VOL 5 PG 501 888-32-56E 2655.93 TO CEN SEC 8,
5305.74 TO E ¼ COR SEC 8, 80-21-34E 2668.73 TO SW COR SEC
8, 907.24 TO "NO 574" 1957, AND ANGLE 24-26-15 @ "NO 574"
FROM W ¼ COR SEC 8 TO "NO 574 AZIMUTH MARK"
1979 BARNES VOL 6 PG 1 85-29-02W 2668.73 TO SE COR SEC 7 &
N86-26-24W 5344.17 TO ~~SW~~ SEC 7
1983 COMBS MAP #13238 FD OI.
1985 COMBS OSM 8-01 ALUM.
1989 BARNES VOL 6 PG 402 FD ALUM. MON. 80-59-30E 2668.82 TO
SE COR SEC 7, 887-04-42W 5344.46 TO W ¼ COR SEC 7, N1-09-
06W 2655.07 TO NE COR SEC 7.
1993 KARNS OSM VOL 16 PG 478 "ROCK COUNTY MON." 5305.91 TO E
¼ COR SEC 8 A REBAR?
1995 LATHROP OSM VOL 19 PG 15 POLY MON. 2654.35 TO NE COR
SEC 7 A POLY
1997 SCHROEDER OSM VOL 20 PG 56 STATES NOTHING ABOUT MON.
1999 KREBS MAP #7568 FD ALUM. N1-08-20W 2653.11 TO SW COR
SEC 5, 889-10-39E 2655.86 TO CENTER SEC 8, & 5305.66 TO E
¼ COR SEC 8. BEARINGS BASED ON STATE PLANE
COORDINATES FROM GPS ORFORDVILL GPS & ITS
REFERENCE (N14-14-23E)
2000 BARNES VOL 6 PG 455 888-32-56E 2655.93 TO CEN SEC 8, 80-
21-36E 2668.75 TO SW COR SEC 8, & 907.25 TO "NO 574" 1957
FEDERAL MARK, & ANGLE OF 24-26-15 @ "NO 574" FROM W ¼
COR SEC 8 TO "NO 574 AZIMUTH MARK".

Donald Barnes
2/04/03

PL535

FD ALUM. MON.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED ALUM. MON. & USED MY OLD OBSERVATIONS

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes

Emboss
02/04/03

SHEET 2 OF 3

CORNER CODE

G-5

A.E. 7.08 REQUIREMENT

