

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2N., R. 11E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F	1																								
G		8																							
H																									
I																									
J																									
K	18																								
L		11																							
M																									
N																									
O																									
P	19																								
Q		20																							
R																									
S																									
T	30																								
U		29																							
V																									
W																									
X	31																								
Y		32																							
Z																									

PLYMOUTH TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL \blacklozenge AT PROPER LOCATION ON ABOVE INDEX

\blacklozenge CORNER MONUMENT

\circ WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

SW 21
ALUM

N 89-13-12W
2652.87

CENTER
SEC 21
3/8" PIN

N 0-26-54W
2663.04

S 89-12-56E
2655.37

SE SEC
21
ALUM

S 45-04-32W
3725.34
W 1/4 28
ALUM

OBSERVATION SHEET 262

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R-11

PL586

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON EAST ON RAND. SES 21 & 28
1056 BROOK 3.3' CRS N.E.
1386 THICKET
1782 LEFT THICKET & ENTER PRAIRIE
2640 TEMP 1/4 P
5267.46 INT. E BDY AT POST LAND HIGH ROLLING PRAIRIE
1ST RATE
COR. WEST
2633.73 QUARTER SEC COR ON GROUND DESCENDING NE.
SET POST & RAISED MOUND
5267.46 SEC COR
- 1844 TWP RD REC BK 1 PG 3 COMMENCING AT THE NE COR OF
THE W 1/2 OF THE NW 1/4 OF SEC 26 T2N R11E IN SAID TOWN
NEAR THE HOUSE OF WALTER INMAN AND RUNNING WEST ON
THE LINE BETWEEN SECTIONS 23 & 26, 1325.28 TO THE COR
SECTIONS 22,23,26, AND 27 WHITE OAK 36 INCHES BEARS
N59W 64.03' N29E 1.00'; THENCE WEST ON LINE
BETWEEN SECTIONS 22 AND 27, 5247' TO THE COR OF
SECTION 21,22 AND 27 AND 28 SET POST IN MOUND WHERE
OLD POST STOOD; THENCE WEST ON LAND BETWEEN SECTIONS
21 AND 28, 5267.46' TO COR OF SECTIONS 20,21 AND 28
AND 29, SET POST IN MOUND SIGHT OF OLD POST, THENCE
WEST ON LINE BETWEEN 20 AND 29 UNTIL IT INTERSECTS THE
BELDIT AND MADISON RD. SAID RD IS LAID OUT 66' WIDE OR
33' ON EACH SIDE OF THE LINE.
- 1855 CHURCH VOL 1 PG 38 STONE 24 INCH LONG 3 INCH THICK.
2725.80 TO SE & SW CORNERS SEC 21.
- 1868 LOCKE PG 20 EAST BETWEEN SECS 21 & 28 VAR 6-22
1082.4 CENTER OF SLUICE BRIDGE
1326.6 STONE SET BY CHURCH
2653.2 INTERSECTED 1/4 LINE 17.16' NORTH OF COR AS SET
BY CHURCH (SEE PAGE 18 & ALSO CO. SURVEYORS
RECORD SEC 28) COR IN CENTER OF HIGHWAY &
NEARLY IN LINE WITH FENCE RUNNING SOUTH. VAR
CORRECTED 6
CONTINUED EAST FROM 1/4 COR WITH VAR 5-50
4404.18 CENTER OF BRIDGE IN RAVINE
5308.38 INTERSECTED EAST BOUNDARY AT COR.
- 1978 BARNES VOL 5 PG 496 FORMER COUNTY SURVEYOR DUG &
FD NOTHING. SET ALUM. MON ON LINE WITH SE & SW
CORNERS OF SEC 21 AT SINGLE PROPORTIONATE DISTANCE.
THIS IS IN HARMONY WITH LOCKE'S FIELD NOTES. CORNER IN
OLD PATCH & CENTER OF PVMT.
- 1995 LATHROP CSM VOL18 PG 456 ALUM. MON. 2655.10 TO
ALUM @ NE COR SEC 28.
- 1995 SCROEDER MAP #9234 STATES NOTHING ABOUT MON.
1996 SCROEDER CSM VOL 19 PG 505 STATES NOTHING ABOUT
MON.


FD ALUM. MON @ CENTER OF PVMT. IN FRONT OF HSE #10147

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal


Barnes
6-30-03

SHEET 1 OF 1

CORNER CODE **R-11**

A.E. 7.08 REQUIREMENT