U.S.

LAND SURVEY **PUBLIC** MONUMENT RECORD

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT For Public Land Survey Corners in: 、T. <u>2</u> N., R. <u>//</u>_E CORNER CODE INDEX PLYMOUTH ROCK COUNTY IF AVAILABLE D E ROCK COUNTY COORDINATES PERFERRED North Elev. East Hor. Datum _____ Vert. Datum LATITUDE _ELLIPS. HT. LONGITUTE GPS (X) TRAVERSE (X) BASED ON THE FOLLOWING CONTROL: PLACE MONUMENT SYMBOL & LOCATION ON ABOVE INDEX O WITNESS MONUMENT **CORNER MONUMENT** (a) NW 34 ALUM N89-23-40 W W/4 BEAFINGS ARE BASED ON ALUM SW 34

__ OF __ SHEET _ PAGE # FIELD BOOK. SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

PL617

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

LEFT PRAIRIE & ENTER TIMBER

1833

HARRISON

NORTH BETWEEN SECS 33 & 34 T2N R11E

1188 1683

WHITE DAK 26

2268.42 WHITE DAK 18

2640

QUARTER SEC COR. BLK O 24 N35E 48.18'; WHITE DAK 16 521E 31.02

4066.26 BLK D 36

5181.66 BLK D 28

5280

COR TO SEC 27,28,33,34 WHITE OAK 24 835E 114.18'; LYM? 24 N78E 86.46'; RED 0 30 N46W 45.54'; W.O. 34 531W 75.9'; LAND ? 1ST RATE TIMB. BLK & W.D. ASPEN HICKORY. ? & LITTLE OR NO UNDERGROWTH

1853 LOCKE TWP ROAD RECORDS BK 1 PG 30 THIS DAY SURVEYED BY THE DIRECTION OF THE SUPERVISORS OF THE TOWN OF PLYMOUTH THE FOLLOWING DESCRIBED RD TO WIT: BEGINNING AT THE NE COR OF SEC 33 THENCE RUNNING SOUTH ONE MILE ON SEC LINE BETWEEN SECTIONS 33 & 34 TO THE TERMINATION OF SAID RD ON TOWN LINE. THE SAID COURSES AND DISTANCES ARE THE CENTER OF THE RD.

VARIATION OF THE MAGNETIC NEEDLE 7 1/2 EAST

1868 LOCKE PG 17 NORTH BETWEEN SEC 33 & 34 VAR 7

2655.18 INTERSECTED 1/4 LINE .66' EAST OF COR. STUMPS OF BTS AND STAKE UNDER STONE ON CORNER. THE DISTANCE & COURSE OF EACH BT GIVEN FOR THE OTHER RIGHT WHEN EXCHANGED. COR IN CENTER OF HIGHWAY & IN LINE OF E & W FENCE. VAR CORRECTED 7-01.

CONTINUED NORTH FROM 1/4 COR WITH VAR 7

3118.5 BROOK 3.96' WIDE COURSE SW

INTERSECTED NORTH BOUNDARY 3.3' E OF COR. 5318.28 VAR CORRECTED 7-04. 7 AUG 21 1868

- 1871 RUGER VOL 2 PG 75 FD STONE VAR 6-10 2657.99 TO NE COR SEC 33, VAR 6-15 2650.06 TO SE COR SEC 33, VAR 5-35 2664.75 TO CEN SEC 33, & VAR 5-35 5329.17 TO W 1/4 COR SEC 33.
- 1896 BROWN VOL 2 PG 500 2663.26 TO NW COR SEC 34 & 2650.56 TO CEN SEC 34
- 1947 BATTERMAN VOL 3 PG 525 IRON PIN SET BY BATTERMAN SR. IN 1947. REF. SAME. COR IN CENTER OF PVMT.
- 1978 BARNES VOL 5 PG 481 FD OLD ASPHALT RD & IRON PIN 3' DEEP. SET ALUM. MON.
- 1978 BARNES VOL 5 PG 473 NO-02-26E 2661.65 TO NE COR SEC 33, SO-00-02E 2655.96 TO SE COR SEC 33, N88-51-06W 5342.09 TO W 1/4 COR SEC 33.

1980 COMBS MAP #04417 FD ALUM.

- 1989 COMBS MAP #12293 ALUM MON
- 1994 COMBS MAP #09866 FD CAST IRON PIN. NORTH 2661.79 TO NE COR SEC 33 & N88-53-55W TO W 1/4 COR SEC 33.
- 1996 SCHROEDER MAP #D8962 STATES NOTHING ABOUT MON.

USED MY OLD OBSERVATIONS

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Emboss 6-17-03

SHEET 1 OF 1

CORNER CODE X-13

A-E 7.08 REQUIREMENT