

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2N., R. 11E

### CORNER CODE INDEX

	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									
B																									
C	6																								
D		5																							
E			4																						
F				3																					
G	1																								
H		8																							
I			9																						
J				10																					
K					11																				
L						12																			
M	18																								
N		17																							
O			16																						
P				15																					
Q					14																				
R						13																			
S							12																		
T								11																	
U									10																
V										9															
W											8														
X												7													
Y													6												
Z														5											

PLYMOUTH TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEETS 4506, 4507

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 2-11

PL626

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT WEST ON SOUTH SIDE SECTION 33

2640 SET QUARTER SECTION POST IN PRAIRIE AND MOUND OF EARTH AND SODS

3102 INDIAN PATH CS S.E.

5280 SET POST CORNER SECTIONS 32 & 33 MADE A MOUND OF EARTH AND SODS LAND ROLLING SECOND RATE DRY PRAIRIE

1868 LOCKE PLYMOUTH REMONUMENTATION SEPT 11, 1868

PG 69 WEST ON SOUTH LINE SEC 33 VAR 6-20

1214.4 CENTER SLUICE BRIDGE 4.62' WIDE

1712.04 CENTER SLUICE BRIDGE 3.96' WIDE

2668.71 INTERSECTED 1/4 LINE AT COR. FOUND OLD STAKE IN CENTER OF HIGHWAY AND IN LINE WITH FENCE RUNNING NORTH. SURROUNDED MONUMENT BY HEAP OF LIMESTONE.

CONTINUED WEST WITH VAR 6-20

2705.34 CENTER OF SOUTH END OF BRIDGE

5340.39 INTERSECTED WEST BOUNDARY 12.87' SOUTH OF COR. VAR CORRECTED 6-04. 1/4 MONUMENT MARKED 33 ON ITS NORTH FACE.

1871 COLLINS REMONUMENTATION NEWARK TWP T1N R11E

PG 212 EAST ON NORTH LINE OF 4 VARIATION 5-40

5334.12 SECTION CORNER

BACK TO

2667.06 SET 1/4 STONE 31.02' EAST OF PLYMOUTH 1/4 CORNER. NOV 6, 1871

1871 RUGER VOL 2 PG 75 FD STONE MON. 2665.41' VAR 5-20 TO SW COR SEC 33, 2667.89' VAR 5-25 TO SE COR SEC 33, 2660.66 VAR 6-18 TO CENTER SEC 33, & 5321.78' TO N 1/4 COR SEC 33.

1957 BATTERMAN VOL 3 PG 520 DUG TWO HOLES 5X5X2 1/2 DEEP. FD STONE MON. SET 1 1/2 PIPE ABOVE STONES IN RD. REFERENCED SAME. 30.60 BETWEEN CORNERS. PLYMOUTH WEST OF NEWARK COR. 2640.72 FROM S 1/4 COR SEC 33 TO NW COR SEC 4

1967 BATTERMAN VOL 4 PG 316 FD 6X6 CUT L.S. & REFERENCED SAME. DIAGRAM SHOWS COR EAST OF BRIDGE.

1978 BARNES VOL 5 PG 473 S88-47-39E 2667.29 N 1/4 COR SEC 4 TO NW COR SEC 4, S89-02-54E 2640.64 N 1/4 COR SEC 4 TO SE COR SEC 33, FROM S 1/4 COR SEC 33 TO SW COR SEC 33 2673.85 & 2670.88 TO SE COR SEC 33.

1978 BARNES VOL 5 PG 481 FD CARPENTERS NAIL 0.5' DEEP AT N 1/4 COR SEC 4, FD 1 1/4" PIPE AT S 1/4 COR SEC 33. REPLACED WITH ALUM. MONUMENTS. 30.70' BETWEEN MONUMENTS. NEWARK COR IS TO THE EAST.

FD ALUM. MON. TOP GONE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND MONUMENTS AS PERPETUATED.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal  
emboss

Number of included sheets 1

CORNER CODE Z-11

*Donald Barnes*

A-E 7.08 REQUIREMENT

3-07-03