

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B																								
C	6																							
D																								
E																								
F																								
G	7																							
H																								
J																								
K																								
L	18																							
M																								
N																								
O																								
P	19																							
Q																								
R																								
S																								
T	30																							
U																								
V																								
W																								
X	31																							
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

Fd TIES VOL 4 pg 322

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE J21

NE551

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 17 (EAST) RANDOM BETWEEN 11 & 14
5272.08 INTERSECTED SEC LINE 36.96 SOUTH OF POST
LAND ROLLING 2ND RATE LINE RUNNING BORDER OF PRAIRIE
TIMBER OAK & HICKORY
WEST COR BETWEEN SECS 11 & 14
2636.04 SET 1/4 SEC POST HICKORY 12 N18E 27.06'; BUR OAK 15 S47E 42.9
4158 YELLOW OAK 12 IN DIAMETER
5272.08 SEC COR.
PG 12 NORTH BETWEEN 11 & 12 VAR 6
59.4 BUR OAK 12 INCHES IN DIAMETER
577.5 BUR OAK 14 INCHES IN DIAMETER
1435.5 TRAIL S.E.
2640 SET 1/4 SEC POST ASPEN 16 IN N4W 114.18
YELLOW OAK 4 S33E 19.8'
5280 COR OF SECS 1,2,11,12 A YELLOW OAK 20 IN DIAM. LAND 2ND RATE
ROLLING TIMBER OAK & HICKORY OAK & HAZEL U.G.
PG 12 EAST RANDOM BETWEEN SECS 12 & 13
4290 CREEK BOTTOM (MARSHY)
4818 CREEK 9.9' C. SOUTH
5230.5 INTERSECT RANGE LINE 59.4' NORTH OF POST
LAND SAME
WEST CORRECTED BETWEEN SECS 12 & 13
2614.92 SET 1/4 SEC POST. WHITE OAK 8 IN S20E 25.08'; YELLOW OAK N34W
14.52'
2865.72 WHITE OAK 12 IN DIAMETER
4999.5 HICKORY 12 IN
5230.5 SEC COR
PG 11 NORTH BETWEEN 13 & 14
701.58 BUR OAK 14 IN
1492.26 WHITE OAK 15 IN
2640 SET 1/4 SEC POST BUR OAK 12 S17E 42.9'; BUR OAK 10 S10W 54.78'
3503.28 YELLOW OAK 8 IN
5280 SET POST CORNER OF SEC 11, 12, 13, 14
BUR OAK 18 N21W 18.48'; BUR OAK 14 S64E 112.86'
LAND ROLLING 2ND RATE TIMBER OAK & HICKORY OAK & HAZEL
U.G. (UNDER GROWTH) RED ROOT RASIN ??
1871 COLLINS REMONUMENTATION NOTES
PG 156 EAST BETWEEN 11 & 14 VARIATION 9
2644.62 SET 1/4 STONE BY ROOTS OF WITNESS TREES
CONTINUED EAST VAR 8-30
5282.64 SEC CORNER. OCT 20 1871
PG 144 NORTH BETWEEN 11 & 12
2636.7 SET 1/4 STONE BY ROOTS OF WITNESS TREES.
CONTINUED NORTH SAME VARIATION
5273.4 SET STONE FOR CORNER OF 1,2,11,12 IN PLACE OF CORNER TREE AS
SHOWN BY ROOTS.
PG 141 EAST BETWEEN 12 & 13 VARIATION 5-30
2640.66 SET 1/4 STONE.
CONTINUED EAST SAME VARIATION
5281.32 SEC CORNER.
PG 140 NORTH BETWEEN 13 & 14 VARIATION 5-15
2703.36 INTERSECT 1/4 LINE 7.26' WEST OF CORNER SET 1/4 STONE BY
STUMPS OF WITNESS TREES CORRECTED VARIATION 5-25

Donald Baunes

6-29-01

SHEET 1 OF 2

521

CONTINUED NORTH VARIATION 5

- 5392.2 SET STONE FOR CORNER OF SECS 11,12,13, & 14 IN PLACE OF STAKE SAID BY H. HUSEMAN TO BE IN PLACE OF ORIGINAL STAKE.
- 1881 LEE VOL 2 PG 330 STATES NOTHING ABOUT MON. VAR 5-16 2631.42 TO S 1/4 COR SEC 12 & VAR 5-00 2628.12 TO W 1/4 COR SEC 12
- 1967 BATTERMAN VOL 4 PG 322 FD CUT 6X6 L.S. SET MON BOX OVER R/R SPIKE & REFERENCED SAME.
- 1980 TOWNSEND CSM 10 PG 212 2637.10 TO S 1/4 COR SEC 11
- 1981 BARNES VOL 6 PG 132 FD MON. BOX. 2632.38 TO W 1/4 COR SEC 12, 2635.54 TO S 1/4 COR SEC 12, AN ANGLE OF 90-23-34 AT SW COR SEC 12 FROM W 1/4 COR TO S 1/4 COR SEC 12.
- 1988 COMBS CSM 13 PG 323 2635.46 TO S 1/4 COR SEC 12

FD R/R WITH DRILL HOLE IN MON. BOX. 1.5' NORTH OF CENTER PVMT; 1.5' WEST OF CENTER PVMT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

^{seal}
Donald Barnes

6-29-01

emboss

SHEET 2 OF 2

CORNER CODE **J-21**

A-E 7.08 REQUIREMENT