

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

### CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																							
C		5																						
D																								
E																								
F	1																							
G		8																						
H																								
I																								
J																								
K	18																							
L		17																						
M																								
N																								
O																								
P	19																							
Q		20																						
R																								
S																								
T	30																							
U		29																						
V																								
W																								
X	31																							
Y		32																						
Z																								

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT       WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FD TIES IN VOL 4  
Pg 90

OBSERVATION SHEET 591

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R-21

NE591

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 15 EAST RANDOM BETWEEN SECS 23 & 26  
5270.76 INTERSECT SEC LINE 10.56' NORTH OF POST LAND ROLLING 2ND  
RATE TIMBER OAK & HICKORY OAK & HAZEL UNDERGROWTH  
WEST CORRECTED BETWEEN SECS 23 & 26  
2635.38 1/4 SEC A YELLOW OAK 16 IN DIA  
3217.5 BUR OAK 8 IN DIA  
4676.76 BUR OAK 16 IN DIA  
5270.76 SEC COR  
PG 10 NORTH BETWEEN 23 & 24  
1610.4 BUR OAK 6 IN DIA  
2640 SET 1/4 SEC POST BUR OAK 10 IN N79W 26.4'; BUR OAK 14 IN N40E 22.44'  
4745.4 BUR OAK 12  
5280 SET POST COR SECS 13,14,23,24 BUR OAK 16 IN N79E 44.88'; BUR OAK 14  
IN S33W 21.12'  
LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY. OAK &  
HAZEL UNDERGROWTH  
PG 10 EAST RANDOM BETWEEN SECS 24 & 25  
5296.5 INTERSECTED RANGE LINE 11.88' NORTH OF POST. LAND SAME  
WEST CORRECTED BETWEEN SECS 24 & 25  
1433.52 YELLOW OAK 10 IN  
2647.92 SET 1/4 SEC POST BUR OAK 20 S73W 21.12'; BUR OAK 18 N27E 45.54'  
4522.32 BUR OAK 8 IN DIA  
5296.5 SEC COR  
PG 9 NORTH BETWEEN 25 & 26  
5287.92 BUR OAK 14 IN DIA  
2640 SET 1/4 SEC POST BUR OAK 18 IN S6E 21.12'; BUR OAK 18 N54W 13.86'  
3428.7 BUR OAK 6 IN DIAMETER  
4988.28 BUR OAK 10 IN DIAMETER  
5280 SET POST COR SECS 23,24,25,26 BUR OAK 12 IN N17E 7.92'; YELLOW OAK  
30 S50W 21.78' LAND GENTLY ROLLING 2ND RATE TIMBER OAK &  
HICKORY OAK HAZEL & HICKORY U.G. (UNDER GROWTH) PRAIRIE  
GRASS RED ROOT  
1851 MCVEAN VOL 1 PG 4 STATES NOTHING ABOUT CORNER. 2670.36 TO S 1/4 COR  
SEC 24. BUR OAK 10 S27W 5.28' ; YEL OAK 12 S30 1/2 E 47.52'.  
1863 LOCKE VOL 1 PG 185 FOUND BT & OLD STAKE. 2669.04 TO S 1/4 COR SEC 24,  
VAR 5-10 2682.90 TO W 1/4 COR SEC 24  
1871 COLLINS REMONUMNETATION NOTES  
PG 152 EAST BETWEEN 23 & 26 VARIATION 6-30  
ON OFFSET 13.2' SOUTH  
2628.12 INTERSECT 1/4 LINE 4.62' NORTH OF CORNER WHICH IS A YELLOW  
OAK 28 INCHES IN DIAMETER. SET STONE 2.64' NORTH OF  
CORNER MARKED 1/4 S COR 2.64' S. CORRECTED VARIATION 6-  
54 {1/4 SEC A YELLOW OAK 16 IN DIA-ORIG SURVEY} CHECK HIS  
TWP PLAT TO SEE IF DISTANCE IS TO CORNER OR HIS STONE)  
CONTINUED NORTH(SHOULD BE EAST) VARIATION 6-30  
5248.32 INTERSECT SEC. LINE 23.1' NORTH OF CORNER CORRECTED  
VARIATION 7. OCT 19, 1871  
PG 135 NORTH BETWEEN 25 & 26 VARIATION 7  
2704.68 INTERSECT 1/4 LINE 1.54' WEST OF CORNER SET 1/4 STONE BY  
STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-02  
CONTINUED NORTH VARIATION 7-15  
5377.02 INTERSECT SECTION LINE 17.16' WEST OF CORNER. SET STONE FOR  
CORNER 23,24,25,26 BY STUMPS OF WITNESS TREES.  
CORRECTED VARIATION 7-38  
PG 137 NORTH BETWEEN 23 & 24 VARIATION 4-35

Donald  
Barnes

7-02-01

- 2694.78 INTERSECT 1/4 LINE 3.3' WEST OF CORNER. SET 1/4 STONE BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 4-39  
CONTINUED NORTH VARIATION 4-30
- 5384.94 INTERSECT SECTION LINE 7.26' WEST OF CORNER SET STONE FOR CORNER SECTIONS 13,14,23,25 IN PLACE OF STONE AGREEING WITH ROOTS OF WITNESS TREES. CORRECTED VARIATION 4-40  
PG 136 EAST BETWEEN 24 & 25 ON  
OFFSET LINE 19.8' NORTH VARIATION 7
- 2680.92 INTERSECT 1/4 LINE 23.1' NORTH OF CORNER SET 1/4 STONE BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-04 OCT 11, 1871  
CONTINUED EAST VARIATION 7-15
- 5410.02 INTERSECT RANGE LINE 56.1' NORTH OF CORNER.  
CORRECTED VARIATION 8-29
- 1961 BATTERMAN VOL 4 PG 90 DUG & FD CUT STONE MON 6"X8" AT COR. SET MON. BOX & REFERENCED SAME.
- 1977 COMBS #12933 1312.86 FROM NE COR SEC 26 WEST TO 1/16TH COR.
- 1977 LEE CSM VOL 7 PG 19 ANGLE OF 91-05-10 @ NE COR SEC 26 FROM E 1/4 TO N1/4 COR SEC 26
- 1978 BARNES VOL 5 PG 464 USED TO ESTABLISH S 1/4 COR SEC 24. 2679.82 TO S 1/4 COR SEC 24 & EAST 1342 TO N/S FENCE LINE
- 1992 LEE CSM 16 PG 179 1339.94 FROM S 1/4 COR SEC 24 WEST TO 1/16TH COR

FD 1" PIPE IN MON. BOX 1' EAST OF N/S CENTER OF PVMT. & @ CENTER OF E/W PVMT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

*Donald Barnes*

emboss

7-02-01

2 OF 2

CORNER CODE

**R-21**

A-E 7.08 REQUIREMENT