

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	7																								
H																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEET 469

FIELD BOOK _____ PAGE # _____

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE 6-21

NE559

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 11 NORTH BETWEEN 13 & 14
 701.58 BUR OAK 14 IN
 1492.26 WHITE OAK 15 IN
 2640 SET 1/4 SEC POST BUR OAK 12 S17E 42.9'; BUR OAK 10 S10W 54.78'
 3503.28 YELLOW OAK 8 IN
 5280 SET POST CORNER OF SEC 11,12,13,14
 BUR OAK 18 N21W 18.48'; BUR OAK 14 S64E 112.86'
 LAND ROLLING 2ND RATE TIMBER OAK & HICKORY OAK & HAZEL
- 1863 LOCKE VOL 1 PG 186 FD STAKE & BTS VAR 6-10 2637.36 TO CENTER OF SEC 13
 5274.72 TO E 1/4 COR SEC 13.
- 1871 COLLINS REMONUMENTATION NOTES
 PG 140 NORTH BETWEEN 13 & 14 VARIATION 5-15
 2703.36 INTERSECT 1/4 LINE 7.26' WEST OF CORNER SET 1/4 STONE BY
 STUMPS OF WITNESS TREES CORRECTED VARIATION 5-25
 CONTINUED NORTH VARIATION 5
 5392.2 SET STONE FOR CORNER OF SECS 11,12,13, & 14 IN PLACE OF STAKE
 SAID BY H. HUSEMAN TO BE IN PLACE OF ORIGINAL STAKE.
- 1881 LEE VOL 2 PG 329 FD MON. 2697.09 TO SE COR SEC 14 & VAR 6-30 ALONG E/W
 1/4 LINE OF SEC 14
- 1967 BATTERMAN VOL 4 PG 318 FD CUT STONE. SET MON. BOX OVER R.R. SPIKE.
 REFERENCED SAME. SKETCH SHOWS IN NORTHERN E/W PVMT LINE.
- 1979 LEE CSM 8 PG 349 2700.03 TO SW COR SEC 13

FD R/R IN MON BOX.


C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

 6-29-01

Number of included sheets 1

emboss

CORNER CODE L-21

A-E 7.08 REQUIREMENT