

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																								
B	6					5				A			3			2					1			
C																								
D																								
E																								
F																								
G	1					8			9			10			11					12				
H																								
I																								
J																								
K																								
L	18					11			10			15			14					13				
M																								
N																								
O																								
P	19					20			21			22			23					24				
Q																								
R																								
S																								
T	30					29			28			27			26					25				
U																								
V																								
W																								
X	31					32			33			34			35					36				
Y																								
Z																								

NEWARK TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

*Fd TIES IN Vol 4
PG 470*

OBSERVATION Sheet 336

FIELD BOOK _____ PAGE # _____

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE T-21

NE599

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 9 NORTH BETWEEN 25 & 26
 - 5287.92 BUR OAK 14 IN DIA
 - 2640 SET 1/4 SEC POST BUR OAK 18 IN S6E 21.12'; BUR OAK 18 N54W 13.86'
 - 3428.7 BUR OAK 6 IN DIAMETER
 - 4988.28 BUR OAK 10 IN DIAMETER
 - 5280 SET POST COR SECS 23,24,25,26 BUR OAK 12 IN N17E 7.92'; YELLOW OAK 30 S50W 21.78' LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY OAK HAZEL & HICKORY U.G. PRAIRIE GRASS RED ROOT
- 1851 McVEAN VOL 1 PG 4 USED TO SUBDIVIDE SEC 25. 5326.2 TO E 1/4 COR SEC 25.
- 1871 COLLIN'S REMONUMENTATION NOTES
 - PG 135 NORTH BETWEEN 25 & 26 VARIATION 7
 - 2704.68 INTERSECT 1/4 LINE 1.54' WEST OF CORNER SET 1/4 STONE BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-02
CONTINUED NORTH VARIATION 7-15
 - 5377.02 INTERSECT SECTION LINE 17.16' WEST OF CORNER SET STONE FOR CORNER 23,24,25,26 BY STUMPS OF WITNESS TREES. CORRECTED VARIATION 7-38
- 1911 KERCH VOL 3 PG 68 FD MON. USED TO SUBDIVIDE SEC 25
- 1930 BATTERMAN VOL 3 PG 175 FD STONE MON. 81.15 FROM NW CORNER OF SCHOOL BLDG, 99.03' FROM SW CORNER OF SCHOOL BLDG.
- 1931 SUNNY VOL 3 PG 190 FD STONE MON. REFERENCED IP THAT IS 295.5' NORTH OF STONE. THE IP IS IN THE INT. OF THE ROADS.
- 1969 BATTERMAN VOL 4 PG 470 SET MON. BOX OVER 1" PIPE & REFERENCED SAME. SKETCH SHOWS COR WEST OF CENTER OF PVMT.
- 1970 SHIMEAL #3207 2637.12 TO CENTER SEC 26
- 1977 LEE CSM 7 PG 19 ANGLE OF 91-05-10 @ NE COR SEC 26 FROM E 1/4 TO N 1/4 CORNERS OF SEC 26
- 1978 LEUENBERGER CSM 7 PG 265 2637.51 TO CENTER SEC 26
- 1998 KREBS CSM 21 PG 125 2697.73 TO SW COR SEC 25

FD 1" PIPE IN MON. BOX. WEST OF CENTER OF PVMT. .

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD 1" PIPE IN MON. BOX AS PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Donald Barnes
emboss

7-02-01

Number of included sheets **D**

CORNER CODE **T-21**