

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

NEWARK

TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

USED OBSERVATIONS FROM
FIELD BOOK #2 pg 5
TIES SET IN P9

OBSERVATION SHEET 413
FIELD BOOK _____ PAGE # _____

SHEET _____ OF _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE P9(2)

NE576

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 27 NORTH BETWEEN SECS 20 & 21
 - 462 ENTER MARSH CR E
 - 2244 LEAVE SAME
 - 2640 SET 1/4 SEC POST YELLOW OAK 28 N34W 30.36'; YELLOW OAK 8 S56E 83.16'
 - 2844.6 YELLOW OAK 28 IN DIA.
 - 4260.96 BUR OAK 15 IN DIA
 - 5280 COR OF SECS 16,17, 20, & 21. A BUR OAK 20 IN DIAMETER LAND 2ND RATE WITH MARSHY SPOTS THINLY TIMBERED
- 1871 COLLINS. REMONUMENTATION FIELD NOTES
 - PG 179 NORTH BETWEEN 20 & 21 VAR 5-30
 - 2636.04 SET 1/4 STONE BY STUMPS OF WITNESS TREES
 - CONTINUED NORTH VARIATION 5-45
 - 5270.1 INTERSECT SECTION LINE 11.22' WEST OF CORNER. SET STONE FOR CORNER OF 16,17 20,21 IN PLACE OF STUMP OF CORNER TREE. CORRECTED VARIATION 6-0
- 1978 BARNES VOL 5 PG 491 FD CUT LIMESTONE @ FENCE INT.
- 1989 BARNES VOL 6 PG 401 FD CUT LIMESTONE. N0-18-59E 2633.15 TO NW COR SEC 21; S89-03-13W 2653.28 FROM NE COR SEC 20 TO N 1/4 COR SEC 20, & S88-53-55E 2637.34 TO N 1/4 COR SEC 21.
- 1989 BARNES P-9 FD CUT LIMESTONE. PLACED YELLOW CARSONITE POST 1.5' EAST OF STONE. REFERENCED SAME.
- 1995 BARNES P-9(1) COORDINATES WERE SUPPLIED BY WPL. THE SURVEY WS BY GPS AND CONNECTED TO THREE ROCK COUNTY GPS CONTROL MONUMENTS: BROADHEAD (305S), AVON (312S), AND NEWARK EAST (313S). N/S 195,852.501; E/W 2,181,893.306. I CONVERTED THOSE COORDINATES TO COUNTY (N/S 443,319.062; E/W 215,095.950) & USED AS A CONTROL POINT IN THE TWP ADJUSTMENT.

FD CUT LIMESTONE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

Donald Barnes
emboss

6-29-01

Number of included sheets **1**

CORNER CODE **P-9(2)**