

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 1E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	1																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S																									
T	30																								
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PERFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION Sheet 549

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE J17(1)

NE549

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 23 EAST RANDOM BETWEEN SECS 10 & 15
4950 ENTER PRAIRIE
5303.1 INTERSECT SEC LINE 4.62' NORTH POST
2651.22 SET 1/4 SEC POST BUR OAK 12 S9W 72.6'; WHITE OAK 14 N56W 86.46'
3290.76 WHITE OAK 18 IN DIAMETER
5303.1 SEC CORNER LAND GENTLY ROLLING 2ND RATE, TIMBER OAK & HICKORY
PG 18 NORTH BETWEEN SECS 10 & 11
2640 SET 1/4 SEC POST YELLOW OAK 18 S57-30E 124.74; ASPEN 10 N70-30E 184.8'
3676.2 TRAIL N.W.
5280 SET POST COR OF SECS 2,3,10,11 BUR OAK 10 S11E 175.56'; BUR OAK 10 N6W 132'
PG 17 (EAST) RANDOM BETWEEN 11 & 14
5272.08 INTERSECTED SEC LINE 36.96 SOUTH OF POST
LAND ROLLING 2ND RATE LINE RUNNING BORDER OF PRAIRIE
TIMBER OAK & HICKORY
WEST COR BETWEEN SECS 11 & 14
2636.04 SET 1/4 SEC POST HICKORY 12 N18E 27.06'; BUR OAK 15 S47E 42.9
4158 YELLOW OAK 12 IN DIAMETER
5272.08 SEC COR.
PG 17 NORTH BETWEEN SECS 14 & 15
2005.08 YELLOW OAK 10 IN
2583.9 BUR OAK 22 IN DIAMETER
2640 SET 1/4 SEC POST BUR OAK 10 IN N50E 68.64; BUR OAK 10 IN S29W 27.72
3699.3 WHITE OAK 18 IN
4404.18 YELLOW OAK 10
5082 ENTER PRAIRIE
5280 SET POST COR OF 10,11,14,15
BUR OAK 22 IN N75E 252.12'; BUR OAK 10 IN S27-30W 67.98'
LAND 2ND RATE GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY OAK & HAZE U.G.
- 1871 COLLINS REMONUMENTATION NOTES
PG 169 WEST BETWEEN 10 & 15 VARIATION 3
2659.14 SET 1/4 STONE (UNDER BRIDGE) BY WITNESS TREE
CONTINUED WEST SAME VARIATION
5345.34 SECTION CORNER
PG 157 NORTH BETWEEN 10 & 11 VARIATION 5-50
2666.4 INTERSECT 1/4 LINE 4.62' EAST OF CORNER. SET 1/4 STONE IN PLACE
OF OLD STAKE FOUND BY STUMP OF WITNESS TREE. VARIATION
CORRECTED 5-44
CONTINUED NORTH VARIATION 5-20
5334.78 SET STONE FOR CORNER OF 2,3,10,11 BY ROOTS OF WITNESS TREES.
PG 156 EAST BETWEEN 11 & 14 VARIATION 9
2644.62 SET 1/4 STONE BY ROOTS OF WITNESS TREES
CONTINUED EAST VAR 8-30
5282.64 SEC CORNER. OCT 20 1871
PG 155 NORTH BETWEEN 14 & 15 VARIATION 7-10
2648.58 INTEREST 1/4 LINE 11.88' WEST OF CORNER. SET 1/4 STONE BY STUMP
AND ROOTS OF WITNESS TREE. CORRECTED VAR 7-25
CONTINUED NORTH VARIATION 6-20
5298.48 SET STONE FOR CORNER OF 10,11,14,15 IN PLACE OF OLD STAKE
FOUND BY ROOTS OF WITNESS TREES
- 1963 BATTERMAN VOL 4 PG 168 IN SW PART OF INT. FD 6X6 CUT STONE. SET MON.
BOX & REFERENCED SAME.

SHEET 1 OF 2

Donald Brewer
6-29-01

1970 SHIMEALL CSM 1 PG 296 1333.0 FROM W 1/4 COR SEC 11 TO W 1/16TH COR OF SW 1/4 SEC 11.
1984 LEUENBERGER CSM 11 PG 439 2647.76 TO W 1/4 COR SEC 14
1991 BARNES J-17 FD PK 2' EAST OF WEST EDGE OF N/S PVMT, 3' SOUTH OF CENTER OF E/W PVMT & OLD REFERENCE PIPES. TIE DISTANCES ARE IN HARMONY WITH RECORD DISTANCES.

PLACED MAG NAIL IN TOP OF FD CUT LIMESTONE THAT IS IN MON. BOX. 6.3' WEST CENTER N/S PVMT; 3.5' SOUTH E/W CENTER PVMT. FD REFERENCE PIPES AS SHOWN IN J-17.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION AS MONUMENTED BY THE FD CUT L.S.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal



emboss

6-29-01

SHEET 2 OF 2

CORNER CODE **J-17(1)**

A-E 7.08 REQUIREMENT