

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1N., R. 11E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6						5				4				3				2					1	
D																									
E																									
F																									
G	1						8				9				10				11					12	
H																									
I																									
J																									
K																									
L	18						17				16				15	◆	14							13	
M																									
N																									
O																									
P	19						20				21				22				23					24	
Q																									
R																									
S																									
T	30						29				28				27				26					25	
U																									
V																									
W																									
X	31						32				33				34				35					36	
Y																									
Z																									

NEWARK TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL ◆ AT PROPER LOCATION ON ABOVE INDEX

◆ CORNER MONUMENT

○ WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

Fd TRES FROM L-17

OBSERVATION SHEET ~~477~~ 477

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE L-17(1)

NE558

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 17 NORTH BETWEEN SECS 14 & 15  
2005.08 YELLOW OAK 10 IN  
2583.9 BUR OAK 22 IN DIAMETER  
2640 SET 1/4 SEC POST BUR OAK 10 IN N50E 68.64; BUR OAK 10 IN S29W 27.72  
3699.3 WHITE OAK 18 IN  
4404.18 YELLOW OAK 10  
5082 ENTER PRAIRIE  
5280 SET POST COR OF 10,11,14,15  
BUR OAK 22 IN N75E 252.12'; BUR OAK 10 IN S27-30W 67.98'  
LAND 2ND RATE GENTLY ROLLING 2ND RATE TIMBER OAK &  
HICKORY OAK & HAZE U.G. (UNDER GROWTH)
- 1871 COLLINS REMONUMENTATION NOTES  
PG 155 NORTH BETWEEN 14 & 15 VARIATION 7-10  
2648.58 INTEREST 1/4 LINE 11.88' WEST OF CORNER. SET 1/4 STONE BY STUMP  
AND ROOTS OF WITNESS TREE. CORRECTED VAR 7-25  
CONTINUED NORTH VARIATION 6-20  
5298.48 SET STONE FOR CORNER OF 10,11,14,15 IN PLACE OF OLD STAKE  
FOUND BY ROOTS OF WITNESS TREES
- 1881 LEE VOL 2 PG 329 FD MON. VAR 6-30 FOR E/W 1/4 LINE SEC 14  
1963 BATTERMAN VOL 4 PG 168 FD 6"X6" CUT STONE SET MON BOX &  
REFERENCED SAME.  
1977 BARNES VOL 5 PG 332. FD MON BOX & CUT L.S. MON BOX IS 0.3' DEEP. SET  
ALUM. INSIDE BOX  
1984 LEUENBERGER CSM 11 PG 439 2647.76 TO NW COR SEC 14  
1991 BARNES L-17 FD ALUM. MON. 3' WEST OF N/S CENTER OF PVMT. REFERENCED  
SAME.  
1996 COMBS #8347 2644.21 TO SW COR SEC 14 & 2626.76 TO CENTER OF SEC 14  
1997 LEUENBERGER CSM 20 PG 202 2664.28 TO SW COR SEC 14 & AN ANGLE OF 88-37-  
00 @ SW COR SEC 14 FROM W 1/4 TO S 1/4 CORNERS OF SEC 14

FD SQUARE NAIL IN TOP OF CUT LIMESTONE IN MON. BOX.


(C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

(D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal  
  
emboss

Number of included sheets 0

6-29-01

CORNER CODE L-17(1)