

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 2 N., R. 11 E

CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6																							
C		5																						
D																								
E																								
F																								
G	1																							
H		8																						
I																								
J																								
K																								
L	18																							
M		17																						
N																								
O																								
P	19																							
Q		20																						
R																								
S																								
T	30																							
U		29																						
V																								
W																								
X	31																							
Y		32																						
Z																								

PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

PLYMOUTH TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT

○ WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

OBSERVATION SHEETS 70,580, 593

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE R-25(1)

PL593

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 MULLETT *NORTH ON EAST SIDE SECTION 25*
2640 SET QUARTER SECTION POST BLACK OAK 12 S9W
117.48' BLACK OAK 8 N1W 314.16'
3168 ENTER PRAIRIE
3762 LEAVE PRAIRIE AND ENTER MARSH
5280 SET POST CORNER SECTION 24 & 25 AND RAISED A
MOUND LAND FIRST $\frac{3}{4}$ ROLLING SECOND RATE
TIMBERED WITH WHITE BLACK AND BUR OAK ASPENS
C LAST $\frac{1}{4}$ MARSH
NORTH ON EAST SIDE SECTION 24
2620.2 STREAM 49.5' C SE
2640 SET QUARTER SECTION POST IN CREEK
3762 LEAVE MARSH
4158 LEAVE TIMBER AND ENTER MARSH
5280 SET POST CORNER SECTION 13 & 24 BUR OAK 8
S4W 132' BUR OAK 12 N42W 198' LAND MOSTLY
LEVEL WITH MARSH
- 1833 HARRISON *EAST BETWEEN SEC 24 & 25*
2640 TEMP $\frac{1}{4}$ P
3630 LEFT TIMBER & ENTER MARSH
5294.52 INT. E BDY 76.56' N OF P LAND HIGH RICH &
ROLLING FOR THE 1ST $\frac{1}{4}$ MILE WITH TIMBER HIGHY,
W.O. BURR O RED O & LAST $\frac{1}{2}$ LEVEL & WET 3RD
RATE BEING MARSH
WEST COR. WEST
2442 HICKY 12
2647.26 QUARTER SEC COR {W.O. 24 S73W 14.52' W.O. 36
S15E 40.92' W.O. 24 W.O. 36} MARKED
5148 BUR O 24
5294.52 SEC COR.
- 1834 HARRISON *WEST ON RAND BETW 19 & 30 T2N R12E*
231 MARSH
2640 QUARTER SEC COR
3201 33' CRS SOUTH
5323.56 W BDY IN MARSH 40.92' N OF P MARKED SAME
FOR COR TO SECS 19 & 30 LAND ALL MARSH
COR EAST
2683.56 QUARTER SEC COR POST & MOUND OF TUSSACKS
IN MARSH.
5323.56 SEC COR
- 1853 TWP RD REC BK 1 PG 30 & 31 "" HWY BE LAID OUT IN SAID
TOWN OF THE WIDTH OF 66' WIDE AND HAVE CAUSED A
SURVEY THERE OF TO BE MADE AS FOLLOWS: THE CENTER
LINE OF THE SAID HWY IS TO COMMENCE 1320' EAST OF THE
SW COR OF SEC 23; THENCE RUNNING EAST ON THE SEC LINE
TO THE SW COR OF SEC 24; THENCE EAST 825' RUNNING 33'
SOUTH AND PARALLEL WITH SECTION LINE BETWEEN SECS 24
AND 25; THENCE EAST ON THE SECTION LINE BETWEEN 24
AND 25 TO THE EAST LINE OF SAID TOWN.
- 1854 TOWN ROAD RECORDS BK 1 PG 35 BEGINNING AT THE NE COR
OF SEC 25 IN THE TOWN OF PLYMOUTH RUNNING THENCE
SOUTH ON THIS TOWN LINE BETWEEN SAID TOWNS TO THE
SOUTH LINE OF THE TOWNS AFORESAID; AND THAT THE ""
- 1867 TWP ROAD RECORDS BK 2 PG 1, 3 COMMENCING AT THE NE
COR OF SEC 25 IN THE TOWN OF PLYMOUTH AND SEC 30 IN
THE TOWN OF ROCK; THENCE RUNNING SOUTH 2640' TO THE
 $\frac{1}{4}$ POST ON THE EAST LINE OF SAID SEC 25.
- 1868 LOCKE PG4 *SOUTH ON EAST SIDE OF SEC 25 VAR 6-50*
1320 LEFT MARSH
2659.8 INTERSECTED $\frac{1}{4}$ LINE 20.46' E OF COR FOUND
STUMPS OF B.T.S AND OLD STAKE COR 1.32' EAST
AND 17.49' SOUTH OF COR POST TO FENCE ON
WEST SIDE OF LANE RUNNING NORTH VAR
CORRECTED 6-23 $\frac{1}{2}$

SHEET 1 OF 4 CORNER CODE R-25(1)

Donald Barnes

4

3-07-03

PL593

CONTINUED SOUTH FROM 1/4 COR WITH VAR 6-45

5308.71 INTERSECTED SOUTH BOUNDARY AT COR. FOUND
STONE (SET BY CHURCH) & WHERE B.T.S WERE
DUG OUT COR IN CENTER OF HIGHWAYS.

PG 26 NORTH ON EAST LINE SEC 24 VAR 7-25

2640 SET TEMPORARY 1/4 COR COR LOST.

4003.89 CENTER OF RR TRACK

5295.84 INTERSECTED NORTH BOUNDARY 7.26' EAST OF
COR. FOUND NORTH BT AND STUMP OF SOUTH BT
COR 0.66' NORTH OF COR POST TO FENCE

2647.92 SET PERMANENT 1/4 COR 7.92' NORTH AND 3.63'
WEST OF TEMPORARY 1/4 COR. COR ABOUT 33' E AND
33' N OF CREEK SURROUND MONUMENT WITH
MOUND OF TUSSACKS VAR CORRECTED 7-30 AUG
25.1868

PG3 EAST BETWEEN SECS 24 & 25

0 SET OFF 14.85' SOUTH VAR 6-30E

1320 SET OFF 8.58' SOUTH

2661.45 INTERSECTED 1/4 LINE 2.64' NORTH OF 1/4 COR
FOUND STUMPS OF B.T.S & OLD STAKE COR IN
CENTER OF HIGHWAY & IN LINE WITH FENCES
RUNNING NORTH AND SOUTH VAR CORRECTED 5-56

CONTINUED EAST FROM 1/4 COR WITH VAR 6-10

3498 SET OFF 46.2' SOUTH

5332.47 INTERSECTED EAST BOUNDARY 15.18' NORTH OF
COR. FOUND MOUND IN LINE WITH FENCES
RUNNING SOUTH & EAST VAR CORRECTED 4-50
AUG 18, 1868

1892 BLEEDORN VOL 2 PG 466 FD MON AT SE COR SEC 24
PLYMOUTH TWP. SHOWS A DISTANCE OF 2663.10' TO S 1/4 COR
& 2645.28' TO E 1/4 COR OF SEC 24.

1895 TWP RD REC BK 2 PG 19 COMMENCING AT THE NORTH END OF
A HWY AT OR NEAR THE S.W. COR OF THE NW 1/4 OF SEC 30 OF
THE TOWN OF ROCK AND THE S.E. COR OF THE NE 1/4 OF SEC
25 OF THE TOWN OF PLYMOUTH; THENCE RUNNING NORTH
ABOUT 1 MILES TO THE 1/4 POST OF SEC 24, OF THE TOWN OF
PLYMOUTH AND OF SEC 19 OF THE TOWN OF ROCK; THENCE AT
AN ANGLE OF 20 TO A PT 33' EAST OF THE LINE BETWEEN THE
SAID TOWNS, THENCE NORTH UPON SAID 33' EAST OF
PARALLEL WITH SAID TOWN LINE ABOUT 247.5'; THENCE WEST
AT AN ANGLE OF 20 DEGREES TO THE TOWN LINE BETWEEN
SAID TOWNS, THENCE NORTH UPON THE TOWN LINE BETWEEN
SAID TOWNS TO THE NE COR SEC 24 OF THE TOWN PLYMOUTH
AND THE NW COR OF SEC 19 OF THE TOWN OF ROCK TO
INTERSECT A HWY IN THE TOWN OF ROCK RUNNING EAST FROM
SAID PT OF TERMINATION, THE SAME BEING AN ACCURATE
SURVEY THEREOF CAUSED BY US TO BE MADE AND SAID HWY
BEING UPON THE TOWN LINE BETWEEN SAID TOWNS OR AS
NEAR TO AS THE SITUATION OF THE GROUND WILL ADMIT, THE
LINE OF SAID SURVEY IS THE CENTER OF SAID HWY AND THE
SAME IS LAID OUT OF THE WIDTH OF 66'.

1961 BATTERMAN VOL 4 PG 16 RESET 1" PIPE FROM OLD TIES
AND REFERENCED SAME. SHOWS WPL COORDINATES OF N/S
224,905.56; E/W 2,234,298.70

1972 LEE VOL 4 PG 577 SHOWS DISTANCE FROM NW TO N 1/4 COR
OF SEC 30 AS 2689.88 & 2658.64 FROM NW TO W 1/4 COR OF
SEC 30.

1981 COMBS CSM VOL 10 PG 367 CI

1981 BARNES R-21 2666.42 TO N 1/4 COR SEC 25.

1981 BARNES VOL 6 PG 144 SHOWS WPL BEARING AND DISTANCE
OF S89-55-15E 2690.37 FROM NW TO N 1/4 COR OF SEC 30 &
N1-002-37W 2658.70 FROM NW TO W 1/4 COR SEC 30.

1982 BARNES VOL 6 PG 282 SHOWS A DISTANCE FROM NW COR
OF SEC 30 TO S 1/4 COR OF SEC 24 PLYMOUTH TWP AS
2666.42

SHEET 2 OF 4 CORNER CODE R-25(1)

Donald Barnes

03-07-03

PL593

1989 BARNES R-25 FD CAST IRON MON. LEE STATED THAT HE DID NOT DIG FOR THE CUT LIMESTONE. DUG & FOUND CUT LIMESTONE N23-01-55E 0.52' OF THE CAST IRON MON. CAST IRON MON. WAS REMOVED AS A RESULT OF THE EXCAVATION. CUT LIMESTONE IS 2.1' DEEP. PLACED MAGNETS 17 INCHES BELOW THE TOP OF THE STONE. REFERENCED SAME. 1 EAST OF CENTER OF PVMT. & SOUTH OF CMP.

1992 COMBS CSM10-367 C.I.

1992 KREBS MAP #11229 FD ALUM 2666.50 TO N1/4 COR SEC 25

1996 KREBS CSM VOL 19 PG 353 ALUM. 2659.20 TO E 1/4 COR SEC 25

1996 KREBS MAP #8905 ALUM. MON. N88-07-41W 2666.57 TO S 1/4 COR SEC 24 & N0-08-23W 2647.48 TO E 1/4 COR SEC 24.

2001 COMBS MAP #7940 FD ALUM.

2001 COMBS CSM 24 PG 224 CUT L.S. 2679.03 TO N 1/4 COR SEC 25

2002 ERICKSON FED PRELIMINARY N89-20-38W 2666.45 NAD83 TO S 1/4 COR SEC 24 & N01-21-21W 2647.44 NAD83 TO E 1/4 COR SEC 24.

FD ALUM. MON. & VERIFIED WITH TIES.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED ALUM. MON ON TOP OF CUT L.S.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

U.S. PUBLIC MONUMENT RECORD R-25 SHOWS DISCREPANCY WITH LEE'S C.I. MON. & THE FD CUT L.S.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal
Donald Barnes

Emboss

3-07-03

SHEET 3 OF 34

CORNER CODE

R-25(1)

A.E. 7.08 REQUIREMENT

