U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In: WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT REV 10/23/2004 T. $\angle N$. R. $\angle / \underline{3}$ E. 4th P.M. USMONREC.DWG CORNER CODE INDEX 7URTLE TWP A B **ROCK COUNTY WI** C D IF AVAILABLE D E ROCK COUNTY COORDINATES PERFERRED E G G H North Elev. H K East L M Hor. Datum _____ Vert. Datum o LATITUDE ELLIPS. HT. Q S LONGITUDE NAD83(91) _____NETWORK ADJ. YR W GPS (X) ____ TRAVERSE (X) BASED ON THE FOLLOWING CONTROL: 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX **♦ CORNER MONUMENT WITNESS MONUMENT** (a)

BEARINGS ARE BASED ON:_____

FIELD BOOK _____ PAGE # ____ SHEET _/ OF ____ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

TU544

- (B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.
- 1836 LYON SET QUARTER SECTION POST & MADE MOUND OF EARTH & SOD. CALLS FOR 2640 TO SE & SW CORNERS OF SEC 8.
- 1854 MCVEAN VOL 1 PG 24 CENTER OF CREEK ON N/S CENTER LINE OF SEC 8 TO S 1/4 COR SEC 8 IS 3587.1.
- 1882 LEE VOL 2 PG 369 1/4 CORNER AGREED UPON AS BEING IN CENTER OF ROAD. 2640.99 TO SE COR SEC B. USED TO SUBDIVIDE SEC B. 2647.92 FROM CENTER B TO E 1/4 COR SEC B.
- 1961 BATTERMAN VOL 4 PG 100 SET CONCRET MONUMENT USING R.H.
 LEE'S MEASUREMENT 1964. REFERENCED SAME. SHOWS CORNER
 IS 3.7' EAST OF CENTER OF PAVEMENT. 2655.17 TO NW SEC 17 &
 2640.62 TO NE COR SEC 17
- 1962 DOT #11222 CTH S R/W PLANS STATES NOTHING ABOUT MON. JUST SHOWS SYMBOL IN RD. SHEET 4.5, PROJECT SO1451(S)
- 1972 LEE CSM VOL 2 PG 196 SET CONCRETE MON. 4.57' EAST OF PIPE @ CENTER OF SHOPIERE RD. SET PIPE 55.41 EAST OF CONC. MON.
- 1979 THOM JR. CSM VOL 9 PG 111 CALLS FOR COR 4.57' EAST OF PIPE @ CENTER OF SHOPIERE RD.
- 1980 COMBS CSM VOL 10 PG 129 STATES NOTHING ABOUT MON. PIPE 64.59' WEST OF 1/4 COR THENCE 284.37 SOUTHWESTERLY OF NORTH R/W LINE TO SE PROPERTY COR OF A 240.00' WIDE LOT.
- 1981 COMBS #4677 FD PIPE FD PIPE. SET PIPE 64.28' WEST OF COR.
- 1990 COMBS #13241 FD PIPE & 55.36 TO THE EAST FD PIPE
- 1995 BARNES J-7 FD 1" PIPE 0.4' DEEP & 3 REFERENCE PIPES. 2640.96' TO SE COR SEC 8.
- 1997 KREBS CSM VOL 20 PG 155 CALLS FOR PIPE @ N $^{1}\!\!/_{\!\!4}$ COR SEC 17 & 2654.87 TO PIN @ NW COR SEC 17.
- 1995 BARNES TWP PROJECT N89-18-13W 2654.77 TO NW COR SEC 17 & S89-46-53E 2640.88 TO NE COR SEC 17.
- 2005 HOULE #15240 & 15242 FD PIPE. S88-46-51E 2640.91 TO FD PIPE @ SE COR SEC 8

FD PIPE & TIES. REFERENCED CORNER. ROAD WILL BE REBUILT AS A 4 LANE RD WITH A START DATE OF APRIL 2007.

- C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

 ACCEPTED FD PIPE
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location. NO
- I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

SHEET 1 OF 2

CORNER CODE J-7(1)

Darle Bares
Apr 13,2007

