

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 3 N. R. 14 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

### CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											
B																											
C																											
D																											
E																											
F																											
G																											
H																											
J																											
K																											
L																											
M																											
N																											
O																											
P																											
Q																											
R																											
S																											
T																											
U																											
V																											
W																											
X																											
Y																											
Z																											

JOHNSTON TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_  
OR OBSERVATION SHEET \_\_\_\_\_

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE X-2(1)

J0619 E1/4CORSEC35

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1905 RUGER VOL 5 PG 321 FD REMAINS OF OLD STAKE DROVE  
STAKE DEEP & PUT LIMESTONE 9X6X2 -1/2 ON TOP. 2641.98  
TO CENTER OF SEC 35, VAR 1-40 5290.56 TO W 1/4 COR SEC  
35

1909 KERCH VOL 3 PG 55 FD STONE 2633.15 TO NE COR SEC 35.

1937 SUNNY VOL 3 PG 360 FD 4X6X12 L.S. OVER STK HOLE  
SURROUNDED BY 4 BOULDERS. SET 1 1/2 X 12" PIPE ON TOP  
FOR CORNER. REFERENCED SAME. 1' WEST OF N/S FENCE ON  
SOUTH SIDE. 2' WEST OF N/S FENCE ON NORTH SIDE.  
REFERENCED SAME.

1977 BARNES VOL 5 PG 237 FD 1 1/2 IP 0.2' BELOW RD SURFACE.  
REF SAME.

1977 BARNES VOL 5 PG 358 FD 1 1/2"X8" I.P. 2' DEEP FD 1" PIPE  
SURROUNDED BY 4 HH. SET ALUM. MON

1977 WOODMAN CSM VOL 6 PG 207 FD 1" PIPE. N84-30-00W TO FD  
1 1/4 PIPE @ W 1/4 COR SEC 35, N3-02-15E 33.03 TO SET 1"  
PIPE @ SE LOT COR. FRONT LOT IS 252.67

1999 SCHROEDER CSM VOL 22 PG 212 STATES NOTHING ABOUT  
MON.

2000 BARNES X-21 FD ALUM MON 0.25' DEEP & NORTH REFER PIPE  
PAVEMENT

0.6' FD ALUM WITH CAP BROKE OFF & LEANING. WITHIN 1-2 YEARS A  
PAVING PROJECT WILL DISTURB THE MONUMENT. FD ALL  
REFERENCE MONUMENTS AS SHOWN IN X-21 EXCEPT THE S2-25-15E  
48.31 MONUMENT.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?


ACCEPTED THE POSITION OF BASE

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

  
Donald  
Barnes

6-20-2012

SHEET 1 OF 3

CORNER CODE X-21(1)

A.E. 7.08 REQUIREMENT



