

Paper weight-110# (minimum) Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 1 N. R. 12 E. 4th P.M.
 CORNER CODE INDEX

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
 REV 10/23/2004 USMONREC.DWG

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5				4					3					2					1	B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
 PLACE MONUMENT SYMBOL **◆** AT PROPER LOCATION ON ABOVE INDEX

BELOIT TWP

ROCK COUNTY WI

IF AVAILABLE
 ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

◆ CORNER MONUMENT ○ WITNESS MONUMENT

BEARINGS ARE BASED ON: --- ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
 OR OBSERVATION SHEET _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE C-25(2)

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1835 BRINK SET QUARTER SECTION POST IN PRAIRIE IN MOUND. PIT EAST OF POST 3.96'.
- 1865 LOCKE VOL 1 PG 235 FOUND LARGE RED HH. 2634.26 TO SW COR SEC 6 & 2366.30 TO CENTER OF SEC 6.
- 1865 LOCKE MAP #4653
- 1882 HOLMES VOL 2 PG 357 LARGE RED HH USED TO SUB SEC 6.
- 1936 SUNNY VOL 3 PG 296 FOUND LARGE HH BROKEN IN 2. SET 1 1/2 IRON PIPE, GAPPED ON TOP. REFERENCED SAME.
- 1957 BATTERMAN VOL 3 PG 527 FOUND PIPE CALLS FOR 2642.72 TO SW 6,3085.10 TO NW 6,2674.36 TO CENTER OF SEC 1 BELOIT TWP,& ANGLE 179-12 AT W 1/4 6 FROM SW TO NW CORNERS OF SEC 6.
- 1960 BATTERMAN VOL 4 PG 357 REFERENCED CORNER & STATES NOTHING ABOUT CORNER.
- 1991 COMBS CSM 15 PG 180 MON BOX. 2645.90 TO CAST IRON MON @ SW COR SEC 6 TURTLE TWP
- 1990 KREBS C-25 FD PIN IN MON BOX & REFERENCED SAME.
- 1995 WPL COUNTY 230,073.91; 496,455.76
- 1995 BARNES C-1 FD PIN IN MON BOX & KREBS REFERENCE TIES. N/S 230,073.94'; N/S 496,455.53'
- 2012 BARNES COUNTY READJUSTMENT N/S 230,074.05'; N/S 496,455.42'
- 2012 COMBS PRELIM TIE 230,074.05; E/W 496,455.41 FOR LARGE NAIL IN BOX

FD LARGE NAIL IN MON BOX. BOX IS ABOUT .7' DEEP

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD NAIL IN MON BOX.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

SHEET 1 OF 2

BEAL
ENDORS
Donald Barnes
Sep 19, 2012

CORNER CODE C-25(1)

A.E. 7.08 REQUIREMENT

OBSERVATION SHEET TURTLE #514
 1990 KREBS C-25
 1960 BATTERMAN VOL 4 PG 57
 SET 1" PIPE
 1936 SUNNY VOL 3 PG 296
 SEARCHED
 FD NOTHING

FD LARGE NAIL
 IN MON. BOX
 @ PVMT CENTER

SECTION 1/4 COR
 BELDIT TWP

SECTION 1/4 COR
 TURTLE TWP

FD 3/4X24 REROD
 COMBS SET 3/4X24 REBAR

FD 1 1/4 PIPE
 S83-13-05E
 CELL FAR AWAY
 S81-00-02E 20,430'
 948TANK

5-11 S8-17E 46.0

FD PIPE IS
 DISTURBED

CELL
 NO-15-48E 10.456'

CTH G

N12-44-14E 11.98
 N12-47-21E 11.91
 FD PIPE

COMBS N12-44-14E 11.98
 COMBS N12-47-21E 11.91
 PIN 3/4

N8-26-26W 58.19
 N8-26-21W 58.14
 COMBS N8-26-21W 58.14

1960 62.79

SEARCHED &
 FD NOTHING

SHEET 2 OF 2

C-256

Donald Barnes
 EMBOSSED SEAL

Sep 19, 2012

S87-10-22E 90.64
 COMBS N85-32-09E 93.49
 N85-36-49E 93.44

S50-32-50E 59.52
 S61-39-52E 59.52
 S61-44-47E 55.21
 S31-02-20E 55.19
 S24-22-25E 55.16
 1960 59.10
 1990 59.69
 COMBS N53-09-49E 55.71
 COMBS N53-11-31E 55.67

1936 33.00
 S89-55-06E 33.07
 S89-53-06E 33.04
 COMBS S89-53-06E 33.04

1990 32.91
 S89-55-07E 32.91
 S89-44-52E 32.91
 COMBS S89-55-07E 32.91
 COMBS S89-44-52E 32.91

N51-56-52E 79.55
 N51-56-14E 60.10
 N51-56-52E 50.88
 N51-56-14E 60.10
 COMBS N51-56-14E 60.10

N66-49-22E 79.55
 COMBS N66-49-22E 79.55
 1960 97.00
 1990 80.89

FD 5/8 PIN

1960 88.74
 1990 87.63

S58-24-43E 15.612'
 ANT TUR
 1960 60.41
 S33-34-49E TANK

1990 92.46

COMBS N19-02-29E 35.33
 N19-00-06E 35.41

FD 1 1/4 PIPE

46.0'