

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B																										B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

FULTON TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: (a) \_\_\_\_\_

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE T-25(1)

FU600

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1836 BRINK NORTH EAST SIDE SECTION 25  
1417.02 BUR OAK 12 IN DIAMETER  
2640 SET QUARTER SECTION POST WHITE OAK 16  
S6W 77.88' WHITE OAK 18 N54W 140.58'  
5280 SET POST CORNER SECTIONS 24 & 25 BUR  
OAK 12 N21W 20.46' BUR OAK 11 S33 1/2W  
21.12' LAND & SAME
- 1864 LOCKE VOL 1 PG 220 & #1341 FD STUMPS OF B. TREES SET  
LIMESTONE 28X9X2 VAR 8-14 2622.84 TO CEN SEC 25,  
5245.68 TO W 1/4 COR SEC 25, VAR 7-15 2653.2 TO SE COR  
SEC 25, & 2648.58 TO NE COR SEC 25
- 1871 (AUG22) RUGER MILTON TWP REMON. SOUTH ON WEST LINE  
OF NW 1/4 OF SEC 30 ON A VAR 6-55 AT  
2657.16 INTERSECT 1/4 COR FOUND LIME STONE AT COR  
ALSO FOUND STUMPS OF SOUTH BARING  
TREES.  
SOUTH ON WEST LINE OF SW 1/4 OF SEC 30 ON  
A VAR 6-55 AT  
2655.18 INTERSECTED SOUTH BOUNDARY LINE 0.66'  
WEST OF COR. COR VAR 6-56  
PLACED 6"X6" CUT LIMESTONE
- 1970 ? VOL 5 PG 176 COPIED FROM FB #303 PG 3 SHOWS TIES.  
1976 COMBS CSM VOL 6 PG 15 STATES NOTHING ABOUT MON.  
1983 BARNES T-1 SET POLY MON. FROM REC TIES VOL 5 PG 176.  
2.8' EAST OF CENTER OF PVMT. & REF. SAME. ON LINE WITH  
E/W FENCE TO THE WEST.  
1983 BARNES REMON #6794 SO-14-17W 2658.85 TO SW COR SEC  
30 & NO-11-44E 2658.16 TO NW COR SEC 30 MILTON TWP  
1983 BARNES REMON #6795 NAD27 BY CO-ORDINATE  
TRANSFORMATION 286,617.51; 2,264,857.29  
2002 BARNES T-25 ALLIANT ENERGY COMPANY PROVIDED THE  
FOLLOWING STATE PLANE COORDINATES. THEY WERE  
DETERMINED BY RTK GPS. I CONVERTED THEM TO ROCK  
COUNTY PROJECTION. 286,624.84; 2,233,319.76  
305,292.47; 495,752.50  
2002 LATHROP #14491 FD ALUM. MON. 2659.12 TO ALUM MON @  
SE COR SEC 25.

FD POLY MON. & REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

IN HARMONY WITH RUGER'S DISTANCES.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

11-28-07  
Emboss

Donald  
Barnes

SHEET 1 OF 1

CORNER CODE  
A.E. 7.08 REQUIREMENT

**T-25(1)**