

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:
T. 3 N., R. 12 E

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

CORNER CODE INDEX

A	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																								
C	6																							
D																								
E																								
F																								
G	1																							
H																								
J																								
K																								
L	18																							
M																								
N																								
O																								
P	19																							
Q																								
R		20																						
S																								
T																								
U	30																							
V																								
W																								
X																								
Y																								
Z																								

JANESVILLE TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE X-11(2)

JACEN33

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1859 RUGER VOL 1 PG 99 USED CENTER & S 1/4 COR SEC 33 TO DESCRIBE R/W FOR HAYNER RD. 1/4 LINE VAR 9-53 & HAYNER R/W IS 33' EAST & WEST OF 1/4 LINE
- 1881 LEE VOL 2 PG 318 VAR 6-45 2657.82 TO E 1/4 COR SEC 33, VAR 6-44 2638.68 TO S 1/4 COR SEC 33. STATES NOTHING ABOUT MON.
- 1932 SUNNY VOL 3 PG 208 SET 1" PIPE 3' LONG 0.4' NORTH OF CENTER PVMT. 2655.0 TO W 1/4 COR SEC 33, 2659.1' TO E 1/4 COR SEC 33, 2662.95 TO S 1/4 COR SEC 33, & 2662.95 TO N 1/4 COR SEC 33.
- 1933 SUNNY VOL 3 PG 222 FD IRON PIPE AS SET BY SELF IN 1932. SURVEYED ADJACENT TO E/W 1/4 LINE 759.0' X 660' ON NORTH SIDE OF RD.
- 1961 BAPTIST MAP #5863 FD IRON PIN SURVEY OF 660' X 759.00 PARCEL ADJACENT TO E/W 1/4 LINE & NORTH OF COR.
- 1982 WIDOT PROJ #1704-03-21 FD 1" PIPE (248,894.47; 2,247,075.39) & AT E 1/4 COR SEC 33 1" PIPE (248,900.84; 2,249,734.92) {COMPUTED N89-51-46E 2659.54}
- 1984 COMBS MAP #13837 MORTGAGE INSPECTION OF 195 X 660' PARCEL ADJACENT & NORTH OF COR
- 1989 WIDOT PROJ 1704-03-22 FD 3/4" PIPE (248,892.55; 2,247,076.24) & PIN AT W 1/4 COR SEC 33 (248,883.47; 2,244,419.70) {COMPUTED N89-48-15E 2656.56}
- 19?? BARNES CENTER TWP PROJ
- 1990 WIDOT PROJ. #1704-03-22 FD 3/4" IRON PIPE (248,892.55; 2,247,076.24), 3/4" IRON PIPE AT E 1/4 COR SEC 33 (248,901.76'; 2,249,734.75), ALUM. AT S 1/4 COR SEC 33 (246,233.23; 2,247,179.05), & W 1/4 COR SEC 33 3/4" PIN (248,883.47; 2,244,419.70) {COMPUTED N89-48-05E 2658.53 TO E 1/4 COR SEC 33; S89-48-15W 2656.56 TO W 1/4 COR SEC 33; S2-12-50E 2661.31 TO S 1/4 COR SEC 33}
- 1990 WIDOT X-11 BARNES DREW TIES FROM DOT MEASUREMENTS. MONUMENT WILL BE DESTROYED BY CONSTRUCTION. CORNER AS DESCRIBED IN PREVIOUS U.S. PUBLIC LAND SURVEY MONUMENT RECORD IS BEING PERPETUATED. DOT 596+88
- 1992 BARNES X-11(1) FOUND DOT DISK. DID NOT ACCEPT DOT DISK. ACCEPTED TIES OF RECORD. THE DISK IS 0.08' NORTH & 0.04' EAST OF CORRECT LOCATION. FD & MEASURED TO TIES OF RECORD
- 1999 COMBS CSM VOL 20 PG 306-308 FD DOT MON. 2656.57 TO DOT MON AT W 1/4 COR SEC 33. SURVEY OF 265.08' X 457.95' PARCEL ADJACENT TO E/W 1/4 LINE JUST 70.30' WEST OF COR.

ESTABLISHED SHORT TIES SO WIDOT CONSULTANT COULD PLACE DISK IN CONCRETE. FD DISK & 3 REFERENCE DISKS. USED TIES THAT I ESTABLISHED EARLIER AND DRILLED HOLE IN DISK & TIED IN NEW REFERENCE DISKS

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED DISK

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal


Emboss

May 9 2003

SHEET 1 OF 2

CORNER CODE **X-11(2)**

A.E. 7.08 REQUIREMENT

