		LAND SURVEY NT RECORD
A 2 3 4 5 B C D E F G H J K L M N C C	Land Survey Corners in:  2 N., R//E  CORNER CODE INDEX  6 7 8 9 10 11 12 13 14 15 16 17 18 19 202	ROCK COUNTY WI  IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED  North Elev  Hor. Datum Vert. Datum
PLACE M LOCATIO	ONLINENT SYMBOL AT PROPER IN ON ABOVE INDEX  CORNER MONUMENT	LATITUDEELLIPS. H  LONGITUTE  GPS (X) TRAVERSE (X)  BASED ON THE FOLLOWING CONTROL:
BEAFINGS ARE BASED ON:	FOR T1 1983	es 366 C-25

OBSERVATION SHEET 1538
FIELD BOOK \_\_\_\_\_PAGE # \_\_\_\_ SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

## PL520

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETT NORTH ON EAST SIDE OF SEC 1

429 LEAVE MARSH AND ENTER PRAIRIE

2640 SET QUARTER SECTION POST IN PRAIRIE AND RAISED A MOUND

5280 SET POST CORNER TOWNSHIPS 2 & 3 N RANGES 11 & 12E IN PRAIRIE AND RAISED A MOUND LAND ROLLING PRAIRIE AND RAISED A MOUND . LAND ROLLING PRAIRIE FIRST RATE SEPT 11<sup>TH</sup> 1833

1854 MCVEAN VOL 1 PG 23 2655.84 TO NE COR SEC 1, 2636.7 TO SE COR SEC 1, VAR 6  $\frac{1}{2}$  5283.3 TO E  $\frac{1}{4}$  COR SEC 6 ROCK.

1866 LOCKE VOL 1 PG 265 FENCES AT JUNCTION ON COR.

2650.56 TO CEN SEC 6 ROCK TWP & 5318.28 TO E 1/4 COR SEC 6 1868 LOCKE PG 33 NORTH ON EAST LINE SEC 1 VAR 6-40

SET OFF 10.56' EAST

2657.82 INTERSECTED 1/4 LINE 23.1' EAST OF COR. FOUND STONE SET AT END OF SOD FENCE. VAR CORRECTED 6-56

CONTINUED NORTH FROM 1/4 COR WITH VAR 6-40

5315.64 INTERSECTED NORTH BOUNDARY 20.79' EAST OF COR. FOUND STONE & UNDERNEATH REMAINS OF STAKE. COR. IN CENTER OF HIGHWAY AND NEARLY IN LINE WITH N & S FENCES. VAR CORRECTED 7-07

1870 RUGER VOL 2 PG 43 STONE MON. SET BY LOCK VAR 5-28 TO E 1/4 COR SEC 6 ROCK TWP

1933 SUNNY VOL 3 PG 234 FD 6"X6" CUT STONE MON. AT JUNCTION OF FENCE. 2657.8 TO NE COR COR SEC 1.

1974 LEE VOL 5 PG 53 2651.43 TO CEN SEC 6 ROCK TWP & 5308.28 TO E 1/4 COR SEC 6

1975 SCHROEDER VOL 5 PG 111 DUG & FD CUT STONE MON. 1' BELOW SURFACE. 2650.92 TO CEN SEC 6 ROCK TWP & 5307.25 TO E 14/ COR SEC 6.

1983 COMBS CSM 11PG 329 FD CUT LIMESTONE

1983 BARNES C-25 FD CUT LIMESTONE 0.7' DEEP. SET CARSONITE POST & REFERENCED SAME. L.S. IS 1.5' EAST OF N/S FENCE & ON LINE WITH E/W FENCE.

1988 BARNES VOL 6 PG 389 RECORD MEASUREMENTS

1989 WIDOT PROJ#1704-03-22 CUT LIMESTONE 243,480.31; 2,233,952.77 NO-42-30E 2607.55 TO NE COR SEC 1 MAP #16694

1997 COMBS CSM 20-66 E ¼ COR SEC 1 FD CUT L.S. & @ SE COR SEC 1 PK. 2661.63 FROM E ¼ COR SEC 1 TO SE COR SEC 1.

2001 LATHROP CSM VOL 25 PG 164 CUT L.S. 5335.94 TO W 1/4 COR

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND CUT L.S. USED MY OLD OBSERVATIONS

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

SHEET 1 OF 1

None | Exerces May 12 2003

CORNER CODE C-25(1)

A.E. 7.08 REQUIREMENT