

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in the

T. 1 N., R. 13 E

CORNER CODE INDEX

TURTLE TWP
ROCK COUNTY WI

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
B																																							
C																																							
D																																							
E																																							
F																																							
G																																							
H																																							
I																																							
J																																							
K																																							
L																																							
M																																							
N																																							
O																																							
P																																							
Q																																							
R																																							
S																																							
T																																							
U																																							
V																																							
W																																							
X																																							
Y																																							
Z																																							

IF AVAILABLE
ROCK COUNTY COORDINATES PERFORMED

North 200,998.40 Elev. _____

East 498,839.94

Hor. Datum COUNTY Vert. Datum _____

GRS (X) _____ TRAVERSE (X)

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

Fd C.1

Fd TIES IN 23

BEARINGS ARE BASED ON:

FIELD BOOK _____ PAGE # _____

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. THE CORNER MONUMENT SHALL HAVE THE FOLLOWING CHARACTERISTICS: 1) HAVE A LEAST TWO PREDETERMINED BREAK-OFF POINTS. 2) IF BROKEN LEAVE A PERMANENTLY MAGNETIZED REMNANT AT THE ORIGINAL POINT. 3) MUST BE EXTENDABLE. 4) THE CAP IS INSCRIBED "ROCK COUNTY SURVEY MONUMENT - PENALTY FOR DISTURBING MARKET". 5) OR AN EXISTING CUT LIMESTONE. AN IRON PIPE 1 1/2" 4" DIAMETER MAY BE USED IN AREAS WHERE GROUND WATER IS WITHIN ONE FOOT OF THE SURFACE. IF THE CORNER IS OCCUPIED BY AN IMPROVEMENT (WAPPOLE BURIED CABLE, ETC) AND DURABLE, DISTINCT MONUMENT MAY BE USED. CORNERS SHALL BE REPERCEIVED WITH AT LEAST 4 DURABLE WITNESS MONUMENTS. WITNESS MONUMENTS SHALL BE MADE OF CONCRETE, METAL OR OTHER EQUALLY DURABLE MATERIAL EXCEPT WOOD. DESCRIBE THE CORNER AND THE WITNESS MONUMENTS.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982
WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

SHEET _____ OF _____

CORNER CODE

23(1)

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1874 RUGER VOL 2 PG 149 FOUND OLD STAKE PUT IN ITS PLACE L.S. 17X10X7. SUBDIVIDED SECTION 31. 2641.98 VAR 4-25 TO SW COR SEC 31 & 2641.32 VAR 5-34 TO CENTER OF SEC 31.

1974 SCHROEDER VOL 5 PG 65 SET CI. 22' SOUTH OF SOUTH EDGE PVMT & REFERENCE SAME.

1974 SCHROEDER VOL 5 PG 74 DUG & FOUND NOTHING SET CORNER BY PRORATION. SAME TIES AS IN VOL 5 PG 65.

1989 BARNES Z-3 FOUND C.I. AS REFERENCED IN VOL 5 PG 74. MON MAY BE DESTROYED BY INSTALLATION OF WATER MAIN. REFERENCED CORNER.

FOUND CI. MONUMENT & REFERENCE TIES IN Z-3.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?
ACCEPTED FOUND PERPETUATED LOCATION.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
NO

I, Donald Barnes, hereby certify that the corner points as identified by the corner code index were, in a field survey on, 1994, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with the regulations and rules as required in the current manual of survey instructions of the United States Department of Interior, Bureau of Land Management.

seal
Donald Barnes
7/12/95

COUNTY SURVEYOR FILING DATA

Date of computer entry _____

Date microfilmed _____

Number of included sheets _____

CORNER CODE

EMBOSS LAND SURVEYOR SEAL

A-E 7.08 REQUIREMENT