

Paper weight-110# (minimum)

Black nonfading ink required

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 12 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

### CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25		
A																											A
B																											B
C																											C
D																											D
E																											E
F																											F
G																											G
H																											H
J																											J
K																											K
L																											L
M																											M
N																											N
O																											O
P																											P
Q																											Q
R																											R
S																											S
T																											T
U																											U
V																											V
W																											W
X																											X
Y																											Y
Z																											Z

FULTON TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

NAD83(91) \_\_\_\_\_ NETWORK ADJ. YR \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: \_\_\_\_\_

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 1

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE X-17

FU618^

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1836 (JULY 11) BURNHAM NORTH BETWEEN SECTIONS 34 & 35  
1568.82 BUR OAK 10 IN DI  
2640 SET 1/4 SEC POST BUR OAK 18 S24 1/2W 29.7'  
BUR OAK 16 N22E 80.52'  
4305.18 BUR OAK 10 IN DI  
5280 SET POST COR TO 26,27,34, & 35 BUR OAK 12  
N37E 49.5' BUR OAK 24 S7W 34.98' FIRST  
RATE BUR OAK OPENINGS

1875 RUGER VOL 2 PG 188 FD OLD STAKE & WHERE STUMP OF SW  
BT HAD BEEN DUG UP SET LIMESTONE 36X12X2 1/2 AT COR &  
SURROUNDED BY 4 HH STONES VAR 6-46 2643.80 TO CEN  
SEC 35, 5301.62 TO E 1/4 COR SEC 35, VAR 5-46 2643.14 TO  
SW COR SEC 35, & VAR 5-43 2652.54 TO NW COR SEC 35.

1875 RUGER VOL 2 PG 189 & #6571 SEE PAGE 143

1877 RUGER VOL 2 PG 229 COR EST. BY SELF SEE SEC 35 PG 143

1967 BATTERMAN VOL 4 PG 299 DUG & FD LS SURROUNDED BY  
HH's & REF. SAME.

1977 BARNES VOL 5 PG 345 FD PK & SET ALUM. MON. REF SAME.

1978 NORTHROP VOL 5 PG 443 FD ALUM. MON 2673.53 TO CEN  
SEC 34, 2643.49 TO SE COR SEC 34, & 5310.79 TO W 1/4 COR  
SEC 34

1978 NORTHROP CSM VOL 8 PG 14 BEARINGS ARE  
REFERENCED TO TRUE NORTH BY SOLAR OBSERVATIONS  
MADE ON JUNE 21, 1978. ALUM. S89-49-13W 2673.53 TO  
CEN SEC 34, S89-49-13W 5310.79 TO W 1/4 COR SEC 34

1980 BARNES VOL 6 PG 17 SHOWS RECORD DISTANCES

1991 COMBS #11746 CALLS FOR BUT STATES NOTHING ABOUT  
MON.

1993 COMBS CSM VOL16 PG 286 ALUM. 2643.55 TO SW COR SEC  
35.

1999 KREBS CSM VOL 23 PG 20 ALUM. 2643.45 TO SE COR SEC 34

1999 COMBS #7548 ALUM. 2673.81 TO CEN SEC 34 & 5310.76 TO  
W 1/4 COR SEC 34

2004 COMBS CMS VOL 27 PG 250 ALUM. MON. 2643.45 TO ALUM  
@ SE COR SEC 34

2005 COMBS #15158 ALUM MON 2643.45 TO ALUM @ SE COR SEC  
34

FD ALUM. MON. & REFERENCE MONUMENTS.


C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD ALUM. MON.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

NONE

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal  
  
Emboss

SHEET 1 OF 1

Barnes

12/03/07

CORNER CODE X-17  
A.E. 7.08 REQUIREMENT