

Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 11 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	A
B		6				5					4				3					2					1	B
C																										C
D																										D
E																										E
F																										F
G																										G
H																										H
J																										J
K																										K
L																										L
M																										M
N																										N
O																										O
P																										P
Q																										Q
R																										R
S																										S
T																										T
U																										U
V																										V
W																										W
X																										X
Y																										Y
Z																										Z

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

PORTER TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR _____

GPS (X) _____ TRAVERSE (X) _____

BASED ON THE FOLLOWING CONTROL:

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: _____

FIELD BOOK _____ PAGE # _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE 2-21(1)

PO631 SEC35/36

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 (SEP 15TH) MULLETT & BRINK WEST ON SOUTH SIDE SECTION 36 T4N R11E

- 2640 SET QUARTER SECTION POST BUR OAK 8 N55 1/2E 80.52' BUR OAK 12 N78W 8.58'
- 5280 SET POST CORNER SECTIONS 35 & 36 BUR OAK 16 N42W 63.36' BUR OAK 16 N46E 67.98' LAND ROLLING AND STONY SECOND RATE TIMBER WHITE BLACK AND BUR OAK VAR 8-45' [DIAGRAM]

1833 (SEP 15) MULLETT & BRINK T4N R11E 4TH MERIDIAN WEST ON SOUTH SIDE SEC 35

- 2640.0 SET QUARTER SECTION POST BUR OAK 12 N63E 34.98'; BUR OAK 12 N62W 14.52'
- 3531.0 TRAIL
- 5280.0 SET POST CORNER SECTION BLACK OAK 24 N81E 31.02'; BUR OAK 12 N70W 20.46' LAND SAME AS LAST MILE

1833 HARRISON (OCT 29TH) T4N R11E 4TH MER. NORTH BET. 35 & 36 (VAR 8-40E)

- 1618.98 TO A BURR OAK 18 IN DIAM
- 2640.0 QUARTER SEC COR. {BURR OAK 18 N74E 23.76'; BURR OAK 18 S86W 10.56' {BURR OAK 18; BURR OAK 18} MARKED
- 4154.70 BURR OAK 10 IN DIAM. & ENTER PRAIRIE
- 4933.50 TRAIL CRS N.E.
- 5280.0 SET A POST & RAISED A MOUND OF EARTH & SOD FOR COR TO SECS 25,26,35,36 ON LEVEL PRAIRIE LAND 1ST 3/4 OF THE GENTLY ROLLING 2ND RATE WITH A HANDSOME GROVE OF BURR OAK TIMBER

1833 HARRISON (OCT/NOV) T3N R11E 4TH MER. NORTH BET. 1 & 2 (VAR 8-40E)

- 330.0 BED OF FREE STONE ROCK
- 506.88 RED OAK 20 INCHES
- 1396.56 WHITE OAK 18 INCHES
- 2180.64 BURR OAK 14 INCHES
- 2640.0 SET POST FOR TO 1/4 SEC OF SECS 1 & 2 BEARINGS {BURR OAK 12 S87W 11.88'; BURR OAK 14 S13E 27.72' {BURR OAK 12; BURR OAK 14} MARKED
- 4169.22 BURR OAK 12 INCHES IN DIAM.
- 5162.52 INT. NORTH BDY 125.4' WEST OF POST BEARINGS {BURR OAK 18 S27W 50.16'; BURR OAK 20 S22E 68.64' {BURR OAK 18; BURR OAK 20} MARKED LAND LEVEL 2ND RATE WITH BURR OAK TIMBER ??? WHITE OAK & BURR ??? GRASS & WEEDS. TUESDAY NOV. 26TH 1833

1833 ORIG GOV PLAT NW COR SEC 1 CENTER TWP IS 125.40' WEST OF SW COR SEC 36 PORTER TWP.

1847 PORTER TWP RD REC BK 1 PG 1 BEGINNING AT THE 1/4 POST ON THE SEC LINE BETWEEN SECTIONS 23, & 24 T4N R11E EAST; THENCE SOUTH ON THE SEC LINE TWO & HALF MILES TO THE SOUTH WEST COR OF SEC 36 OF TOWN AND RANGE. THE LENGTH OF SAID ROAD IS 2 1/2 MILES. COURSES GIVEN ACORDING TO THE TRUE MERIDIAN. VARIATION OF NEEDLE 7 3/4. WE DO HEREBY CERTIFY THAT THE ABOVE ROAD WAS LAID AND SURVEYED ACCORDING TO OUR ORDERS & DIRECTIONS. JUNE 28 1847

1847 STEBBINS -PORTER TWP RD REC BK 1 PG 1 BEGINNING @ A POINT ON THE SOUTH LINE OF SEC 36 T4N R11E 1122' WEST OF THE SE COR OF SAID SECTION; THENCE N44 1/2W SHEET 1 OF 3

CORNER CODE Z-21(1)

Donald Barnes
6-09-09

PO631 SEC35/36

3742.2' TO A STAKE; THENCE N56 1/2 W 3006.96' TO THE CENTER OF THE EAST AND WEST ROAD NEAR J. STEVENS; THENCE N40W 5016' TO STAKE; THENCE N34 1/2 W 2,344.98' TO THE SEC LINE BETWEEN 26 & 27 419.76' SOUTH OF THE NW COR OF SEC 26; THENCE NORTH ON SAID SECTION LINE AND THE BETWEEN 22 & 23 3059.76' TO THE 1/4 POST ON THE SEC LINE BETWEEN SECTION 22 & 23 OF SAID TOWN & RAND AND THE WHOLE LENGTH OF THE ROAD IS 17,169.9' COURSES GIVEN ACCORDING TO THE TRUE MERIDIAN VARIATION OF NEEDLE 7-34. HARRISON STEBBINS-COUNTY SURVEYOR

- 1864 LOCKE VOL 1 PG 216 & 217 & #677 @ SW COR SEC 36 FOUND EAST BEARING TREE. NW COR SEC 1 CENTER TWP IS 131.34' WEST OF SW COR SEC 36. @ NW COR SEC 1 FD STUMPS OF BTS SET HH 15X12X7. FROM NW COR SEC 1 TO W 1/4 COR SEC 1 IS VAR 8-05' 2541.00'. STATEMENT IN NORTH HALF OF NW 1/4 OF SEC 1 IS "THIS WAS DIVIDED EQUAL AS DEED SEEMED TO CALL HALF OF THE 1/4 SEC." SET HH 27X12X6 ON N/S 1/4 LINE MIDWAY BETWEEN THE N 1/4 COR & CENTER OF SEC 1.
- 1869 LEE VOL 1 PG 355 & #683 AT NE COR SEC 2 CENTER TWP FD HH 15X9X12, NE COR SEC 2 IS 131.34' WEST OF SW COR SEC 36, VAR 7-15 2601.56 FROM NE TO N 1/4 COR SEC 2 CENTER TWP. CALLS FOR N 1/4 COR SEC 2 AS WEST OF S 1/4 COR SEC 35.
- 1883 RUGER VOL 2 PG 411 & #684 FOUND HARD HEAD STONE AND STUMP OF NE BEARING TREE. FD REMAINS OF STUMP OF SE BT & REMAINS OF STUMP OF SW BT, DROVE STAKE. NE COR SEC 2 CENTER TWP IS 126.06 WEST OF SE COR SEC 35. 2648.58 FROM SE TO S 1/4 COR SEC 35 PORTER TWP. 2633.4 FROM NE TO N 1/4 COR SEC 2 CENTER TWP.
- 1966 BATTERMAN JR. VOL 4 PG 281 @ SW COR SEC 36 FOUND LARGE HARD HEAD STONE AS RECORD. PLACED REFERENCE TIES. SHOWS ON LINE WITH N/S RD TO THE NORTH.
- 1971 LEE VOL 4 PG 502. SET 1" PIPE AND REFERENCED CORNER. SHOWS A JOG OF 125.50 WITH THE PORTER CORNER EAST OF THE CENTER CORNER. CORNER SHOWN AS ON N/S CENTER LINE OF FOX RD TO THE NORTH AND EAST OF EAST PVMT EDGE. @ NE COR SEC 2 FD 3 HHS, SET CI & REFERENCED SAME. COR NORTH OF SEEMAN RD & ON LINE CENTER OF FOX RD TO THE SOUTH
- 1971 SCHIMEALL CSM VOL 2 PG 59 STATES NOTHING ABOUT MON.
- 1978 LEE VOL 5 PG 466 SEC COR 277,872.73; E/W 2,225,302.92 FOR NE COR SEC 2 CENTER TWP
- 1989 BARNES A-21 FOUND BENT 1" PIPE. CORNER IS 125.54' EAST OF THE CENTER TOWNSHIP CORNER. ACCEPTED FOUND PERPETUATED LOCATION. REFERENCED SAME
- 1991 SCHROEDER CSM VOL 15 PG 327 STATES NOTHING ABOUT NE COR SEC 2 CENTER TWP MON.

FD CI @ NW COR SEC 1 & PIPE @ SE COR SEC 35.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FD MONUMENTS. CI MON @ NW COR SEC 1 CENTER TWP. IS IN E/W DITCH. SW COR SEC 36 IS ON NORTH SIDE OF DRIVEWAY. THE C.I IS 1.5' EAST OF A E/W CMP. IF LEE'S 1869 JOG OF 131.34 IS CORRECT THEN THE CULVERT WOULD HAVE DESTROYED HIS MONUMENT.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seal

Donald
Barnes
6-09-09

SHEET 2 OF 3

CORNER CODE **Z-21(1)**

