Paper weight-110# (minimum)

Black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

T. \(\frac{1}{2} \) N. R. \(\frac{1}{2} \) E. 4th P.M. CORNER CODE INDEX A \(\frac{1}{2} \) 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 B C D C D C C C C C C C C C C C C C C C	WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT REV 10/23/2004 USMONREC.DWG FOR TERM TWP ROCK COUNTY WI IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED
G A B 9 A	G H North Elev
K C A A A	K East
M N O O O O O O O O O O O O O O O O O O	M Hor. Datum Vert. Datum
P O O O O O O O O O O O O O O O O O O O	P LATITUDE ELLIPS. HT
	R S LONGITUDE
V	v NAD83(91)NETWORK ADJ. YR
x x x x x x x x x x x x x x x x x x x	X GPS (X) TRAVERSE (X)
Z 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX	Z BASED ON THE FOLLOWING CONTROL
(a) CORNER MONUMENT	WITNESS MONUMENT

BEARINGS ARE BASED ON:_

FIELD BOOK _____ PAGE # ____ OF ____ OF SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

SE COR SEC 11

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1833 HARRISON (OCT 29TH) T4N R11E 4TH MER. NORTH BET. 13 & 14
 - 346.50 CAT-FISH CREEK CR S.E. SET MEANDER POST BURR DAK 10 S10W 55.44'; BURR DAK 18 N77W 15.84
 - 570.90 LEAVE CAT-FISH SET MEANDER POST {RED DAK 12 S75E 134.64'
 - CAT-FISH CRS S.W. SET MEANDER POST {RED 1307.46 **DAK 12 525E 77.22'**
 - 1534.50 LEAVE CAT-FISH & SET MEANDER POST {BURR DAK 12 N15E 66.66'; BURR DAK 12 N6DW 43.56'
 - SET POST FOR COR TO QUARTER SEC (BURR OAK 2640.0 12 S25W 35.64'; BURR OAK 18 N10W 43.56'
 - 2854.50 CAT-FISH CRS S.E. SET MEANDER POST {BURR OAK 18 522E 29.70'; BURR OAK 20 N81W 30.36'
 - LEAVE CAT-FISH SET MEANDER POST (BURR DAK 3127.08 12 N7DE 18.48'; BURR DAK 8 N19W 33.66'
 - TO A BROOK 6.6' CRS S.W 3678.18
 - 4654.98 **ENTER PRAIRIE**
 - 5280.0 SET POST & RAISED MOUND FOR COR TO SECS 11,12,13,14 LAND ROLLING 2ND RATE TIMBER ??? BURR DAK UNDERGROUWTH HAZEL, ??, GRASS
- 1833 (OCT 29) HARRISON EAST ON RAND BET SECS 12 & 13 T4N R11
 - 1056 TRAIL CRS NORTH
 - 2640 TEMPY 1/4 SEC COR
 - 4290 LEAVE PRAIRIE & ENTER SMALL SCATTERING TIMBER OF BURR & RED O
 - 5273.4 INT. E. BDY 39.6' S OF P. LAND FOR THE 1st 3/4 OF A MILE ? ROLLING PRAIRIE 1 ST RATE ? ROLLING 2ND RATE WITH RED & BUR D COR WEST BET SECS 12 & 13
 - 2636.7 QUARTER SEC COR. SET A POST & RAISED MOUND ON GROUND HIGH & ROLLING
 - 5273.40 INT. SEC. COR
- 1833 HARRISON (OCT 29TH) T4N R11E 4TH MER. NORTH BET. 11 & 12
 - 1980.0 TRAIL CRS N.W.
 - 2640.0 SET A POST AND RAISED A MOUND OF EARTH & SOD FOR COR TO QUARTER SECTION
 - 4834.0 TRAIL CRS N.W.
 - 5280.0 SET POST FOR COR TO SECS 1,2,11,12 NEAR THE NORTHERN EDGE OF PRAIRIE SET POST & RAISED MOUND. LAND ROLLING 1ST RATE PRAIRIE GROWTH GRASS & WEEDS
- 1833 HARRISON (OCT 31st) TAN R11E 4TH MER. EAST ON RAND. BET. 11 & 14
 - 495.0 LEAVE PRAIRIE & ENTER TIMBER
 - 2178.0 CAT-FISH CRK SET MEANDER POST
 - 2482.26 LEFT CAT-FISH CRS S SET MEANDER POST
 - 2640.0 TEMPY 1/4 SEC COR
 - ENTER PRAIRIE 5214.0
 - 5332.80 INT. E BDY 16.5' NORTH OF POST LAND ROLLING 2ND RATE RED, BURR & WHITE DAK TIMBER

WEST COR. WEST BETW. SECS 11 & 14

QUARTER SEC. COR {WHITE DAK B S60W

39.60'

SHEET 1 OF 4 CORNER CODE J-21(1)

PO551 SE COR SEC 11

2850.54 CAT-FISH SET MEANDER POST ON A RED OAK 10 IN DIAM.

3154.80 LEAVE CAT-FISH WHITE OAK 14 588W 6.6' 5332.80 SEC COR

- 1854 STEBBIN #3585 COPIED BY BARNES IN 1977. STATES NOTHING ABOUT MON.
- STEBBIN PORTER TWP RD REC BK 1 PG 9 BEGINNING AT THE 1857 1/4 POST ON THE SEC LINE BETWEEN SEC 11 & 12 T4R11; THENCE SOUTH ON THE LINE 2640' TO SE COR OF SEC 11; THENCE S15 1/2E 785.4' TO A STAKE; THENCE S6W 669.24' TO BLACK DAK ON BANK OF SPRING BROOK; THENCE S5E 907.5' TO THE CATFISH RIVER; THENCE S47W 233.64' TO CENTER OF A RD ON THE E & W CENTER LINE OF SEC 14, 15,576' WEST OF THE 14 POST ON THE EAST LINE OF SEC 14; THENCE NORTH ON SAID CENTER LINE 1131.24' TO A POINT 33' EAST OF THE LINE THAT DIVIDED THE EAST 1/2 OF SEC 14; THENCE SOUTH PARALLEL WITH AND 33' FROM THE LINE DIVIDING THE SE 1/4 OF SEC 14 AND THE NE 1/4 OF SEC 23, 5280' INTERSECTING THE ROAD RUNNING E & W THROUGH SECTION 23 AND THE WHOLE LENGTH OF THE RD IS 11,779.02' THE COURSES ARE GIVEN ACCORDING TO THE TRUE MERIDIAN. VARIATION OF NEEDLE 8. """" A PUBLIC HIGHWAY 66' WIDE. H. STEBBINE, RODMAN IDE, E.D. BARNARD{SUPERVISORS OF PORTER.
- PORTER TWP RD REC BK 2 PG B "" AND IS HEREBY LAID OUT PURSUANT TO SAID APPLICATION WHEREOF AN ACCURATE SURVEY HAS BEEN MADE, WHICH IS AS FOLLOWS, TO WIT: BEGINNING AT THE QUARTER POST OF SEC LINE BETWEEN SECTIONS 11 & 12 T4 & R 11; THENCE SOUTH ON SAID LINE 2640.00 TO THE SE COR OF SEC 11; THENCE S14E 785.40 TO A STAKE; THENCE S3 1/4E 972.18 TO A STAKE; THENCE S80W 122; THENCE S40W 231; THENCE S7E 198; THENCE S46E 280.5; THENCE S45W ACROSS THE CATFISH RIVER 416.46 TO A POINT ON THE EAST AND WEST QUARTER LINE OF SEC 14 58.74 WEST OF THE QUARTER POST BETWEEN SEC 13 AND 14. THE LINE OF SAID SURVEY TO BE THE CENTER OF SAID HIGHWAY. THE SAME IS ESTABLISHED 66 IN WIDTH
- PORTER TWP RD REC BK 2 PG 8 BEGINNING AT THE QUARTER POST OF SEC LINE BETWEEN SECTIONS 11 & 12 T4 AND R11; THENCE SOUTH ON SAID LINE 2640 TO THE SE COR OF SEC 11; THENCE S14E 785.4 TO A STAKE; THENCE S3 1/4E 972.18 TO A STAKE; THENCE S80W 122; THENCE S40W 231; THENCE S7E 198; THENCE S46E 280.5; THENCE S45W ACROSS THE CATFISH RIVER 416.46 TO A POINT ON THE EAST & WEST QUARTER LINE OF SEC 14, 58.74 WEST OF THE QUARTER POST BETWEEN SEC 13 & 14. THE LINE OF SAID SURVEY TO BE THE CENTER OF SAID HIGHWAY. THE SAME IS ESTABLISHED 66 IN WIDTH
- 1871 RUGER VOL 2 PG 63 FOUND OLD STAKE AND HARDHEAD STONE ON TOP OF IT DROVE OLD STAKE DOWN AND PUT ON TOP OF IT HARD HEAD STONE 18X11X6. USED CORNER TO ESTABLISH THE S 1/4 CORNER OF SECTION 12.
- 1886 RUGER VOL 2 PG 282 FD COR AS SET BY SELF IN FORMER SURVEY VAR 5-35 2753.52 TO E 1/4 COR SEC 11, VAR 5-84? 2722.50 TO S 1/4 COR SEC 11, VAR 5-84? 5445.00 TO SW COR SEC 11
- 1958 BATTERMAN JR. VOL 3 PG 566 DUG HOLE S 1/2 FEET DEEP FOUND HH 18X11X6 WITH WOODEN STAKE BENEATH IT, AS DESCRIBED BY RUGER IN VOL 2 PG 63.
 REFERENCED SAME. TIES SHOW COR ON LINE WITH E/W FENCE TO THE EAST & ON THE WESTERN SIDE OF N/S RD.

SHEET TOF 4
CORNER CODE J-21(1)

NOV 5 2007

- PO551 SE COR SEC 11
 BELOIT SET CALLS FOR THE COR ON THE PROJECTION OF
 THE CENTER OF PVMT FROM THE NORTH
- 1961 BATTERMAN VOL 3 PG 566 BELOIT SET. RESET 1" PIPE 0.2' WEST OF WEST EDGE OF BLACKTOP.
- 1965 BATTERMAN JR. VOL 4 PG 223 STATES SEE P 566 VOL 3.
 SHOWS 2647.80 TO S 1/4 CORNER OF SECTION 12. WORK
 DONE BY SURVEYORS OF W.P. & L CO. RUGER 2642.81
 FROM SW TO S 1/4 COR SEC 12
- 19?? WPL #3592 & 3625 FD 6X11X18 HH 2647.X TO LS @ N 1/4 COR SEC 13
- 1978 KARNS VOL 5 PG 465. FOUND 1" PIPE SET OVER FOUND STONE ON WEST EDGE OF BLACKTOP. PIPE FOUND FROM 1958 TIE SHEET. SHOWS 2657.26 TO THE W 1/4 CORNER OF SECTION 13.
- 1978 KARNS CSM VOL 8 PG 152 GOV. COR. STATES NOTHING ABOUT MON.
- 1978 LEE CSM VOL 8 PG 202 FD 1" PIPE SOUTH 2657.34 TO CI @ E 1/4 COR SEC 14.
- 1989 LEE CSM VOL 14 PG 238 ALUM. MON.
- 1991 BARNES J-21 FD 1" PIPE & REFERENCE PIPES. PIPE IS 0.7 WEST? OF WEST PVMT EDGE OF WALLIN RD.
- 1991 BARNES VOL 6 PG 412 FD PIPE, NOO-01-47W 2755.93 TO FD PK @ E 1/4 COR SEC 11, S89-32-55W 2723.42 TO FD ALUM @ S 1/4 COR SEC 11
- 1992 COMBS CSM VOL 15 PG 418 CI 2657.34 TO IP @ NW COR SEC 13.
- 1999 COMBS #07381 FD PIPE. SOUTH 2657.30 TO CI @ W 1/4 COR SEC 13. N88-53-50E FROM W 1/4 COR SEC 13 TO ALUM @ E 1/4 COR SEC 13.
- 1999 COMBS #13159 STATES NOTHING ABOUT MON. SOUTH 1069.37 TO PIPE ON SOUTH R/W OF RD, SOUTH 1866.74 TO PIPE ON NORTH R/W LINE OF CALEDONIA RD.
- 2005 LATHROP #15276 FD PIPE 2645.55 TO FD STONE @ N 1/4 COR SEC 13

USED MY 1991 OBSERVATIONS TO THE FD PIPE.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED PERPETUATED PIPE.

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

ACCEPTED FOUND PIPE.

- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.
- I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Seul

SHEET 3 OF 4

CORNER CODE **J-21(1)**

A.E. 7.08 REQUIREMENT

NOV 5 2009

