

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 1 N., R. 11 E

CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B																									
C	6																								
D																									
E																									
F																									
G	7																								
H																									
I																									
J																									
K																									
L	18																								
M																									
N																									
O																									
P	19																								
Q																									
R																									
S	30																								
T																									
U																									
V																									
W																									
X	31																								
Y																									
Z																									

NEWARK TWP

ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FD TIES FROM N11

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET \_\_\_\_\_ OF \_\_\_\_\_

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE N11(1)

NE566

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1834 MILLER PG 27 EAST RANDOM BETWEEN SECS 16 & 21  
211.2 CREEK S 6.6'  
858 LEAVE CREEK BOTTOM  
3696 MARSH (CIRCULAR)  
4620 LEAVE SAME  
5264.82 INTERSECT SEC LINE 5.94' SOUTH OF POST  
LAND GENTLY ROLLING 2ND RATE TIMBER OAK & HICKORY OAK &  
HAZEL U.G. (UNDER GROWTH)  
WEST CORRECTED BETWEEN SECS 16 & 21  
2632.08 SET 1/4 SEC POST BUR OAK 16 N6W 31.68; BUR OAK 12 S77E 40.26'  
2921.82 YELLOW OAK 14 IN DIA  
3806.22 BUR OAK 15 IN DIA  
5264.82 SEC COR
- 1871 COLLINS REMONUMENTATION NOTES  
PG 180 EAST BETWEEN 16 & 21 VARIATION 4-45  
231 CREEK  
2638.02 INTERSECT 1/4 LINE 4.62' NORTH OF CORNER SET 1/4 STONE IN PLACE  
OF STAKE AND STONES. CORRECTED VARIATION 4-51  
CONTINUED EAST VARIATION 4-30  
5276.7 SECTION CORNER
- 1964 BATTERMAN JR. VOL 4 PG 193 FOUND CUT STONE MONUMENT AT S 1/4  
CORNER OF SECTION 16. PLACED 4 REFERENCE TIES.
- 1976 BARNES VOL 5 PG 144. SHOWS EDM DISTANCE OF 2635.77 TO THE SOUTHEAST  
CORNER OF SECTION 16.
- 1976 LEUENBERGER CSM VOL 5 PG 230 2645.28 TO CENTER OF SEC 16 & CALLS FOR  
A CUT STONE.
- 1979 COMBS CSM 8 PG 397 2647.52 TO CENTER OF SEC 21.
- 1989 SCHROEDER CSM VOL 14 PG 169 USED CORNER BUT STATES NOTHING ABOUT  
IT.
- 1989 BARNES VOL 6 PG 401 FOUND 2637.34 TO SW COR SEC 16, 2645.20 TO CENTER OF  
SEC 16, 5309.38 TO N 1/4 COR SEC 16, ANGLE OF 89-02-02 @ S 1/4 COR SEC 16 FROM  
SW TO CENTER OF SEC 16, ANGLE OF 180-00-04 @ CENTER OF SEC 16 FROM N  
1/4 TO S 1/4 CORNERS OF SEC 16.
- 1989 COMBS #305 ANGLE OF 90-48-22 @ CENTER OF SEC 16 FROM S 1/4 COR SEC 16 TO  
W 1/4 COR SEC 16. SET PIN.

Donald Barnes  
6-29-01

SHEET 1 OF 2

N11(1)

- 1991 LEUENBERGER CSM VOL 18 PG 255 2635.68 TO SE COR SEC 16
- 1991 KREBS #11604 2635.62 TO SE COR SEC 16, ANGLE OF 90-58-53 @ S 1/4 COR SEC 16 FROM CENTER OF SEC 16 TO SE COR SEC 16 2645.14 TO CENTER OF SEC 16, ANGLE OF 89-04-38 @ SE COR SEC 16 FROM S 1/4 TO E 1/4 CORNERS OF SEC 16, ANGLE OF 89-11-28 @ CENTER OF SEC 16 FROM E 1/4 COR TO S 1/4 COR SEC 16.
- 1992 BARNES N-11 REFERENCED FD ALUM. MON WITH TOP BROKE OFF AND SOUTHEAST AND SOUTHWEST REFERENCE PIPES. THE NORTHWEST REFERENCE PIPE WAS LAYING HORIZONTALLY AND THE NORTHEAST PIPE WAS COVERED BY SEVERAL LARGE ROCKS. REFERENCED SAME. MON IS 2.5 SOUTH OF CENTER OF E/W PVMT & 4 EAST OF THE N/S CENTER OF PVMT.
- 1997 HOULE CSM 20 PG 351 TO SW COR SEC 16 & 2170.53 TO CENTER OF SEC 21. & ANGLE OF 90-42-37 @ N 1/4 COR SEC 21 FROM CENTER OF SEC 21 TO NW COR SEC 21.

FD ALUM. MON. WITH TOP BROKE OFF. SET PK FROM FD TIES. 2.7' SOUTH OF E/W CENTER OF PVMT & 3' EAST OF N/S FENCE.

*C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?*

ACCEPTED FOUND PERPETUATED LOCATION.

*D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.*

*(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.*

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal



emboss

SHEET 2 OF 2

CORNER CODE **N-11(1)**

A-E 7.08 REQUIREMENT